

Time-Out Plus

Floor Stripper



Applications:

Dilute with unheated tap water according to the dilution rates listed below. Apply solution to a manageable area and let it work for 5 to 8 minutes. Agitate the solution, pick up and rinse well.

Benefits:

- Can be used on all floor types
- Cuts through layers of floor finish and sealers quickly and efficiently
- Works quickly with minimum effort
- Excellent for high traffic areas
- APE and butyl free and non-ammoniated
- No fumes or odours

Codes:

- **Product Codes:** 50238 (4 L)
50239 (20 L)
- **UPC:** 0 56069 50238 2 (4 L)
0 56069 50239 9 (20 L)

Specifications:

Colour	Orange
DIN	No
Odour	Mild
pH	11.4 - 12.4
Viscosity	Not determined
Solvent	No
Phosphates	No
WHMIS	Yes
ECOLOGO	Yes
Food Safe	No
Kosher	Yes
Shelf Life	Up to 3 years after manufacturing

Dilution Rates:

Auto-Scrubber /
Floor Machine

1:48

Heavy Duty Stripping

1:15



UL ECOLOGO (UL 2777) /
Normal Stripping

1:20

Available Formats:



4 L



20 L

Packaging:

Bottle: 5.8" x 5.8" x 12.3" (14.7 x 14.7 x 31 cm)
10 lbs (4.5 kg)

Pail: 12" x 12" x 16" (30.5 x 30.5 x 41 cm)
48 lbs (22 kg)

Box (4 L): 11.6" x 11.6" x 12.9"
40 lbs (18 kg)
4 per case

