

Attac®

Stripper

Attac $^{\circ}$ Stripper is a professional strength stripper designed for the removal of "tough to strip" finishes and sealers.

Features & Benefits

- Formulated for effective stripping the first time, reducing the need for additional restrips
- Fast penetration of built up finishes and sealer layers, and specially formulated to penetrate and emulsify the toughest finishes and sealers
- Cost effective solution with variable dilution rates utilizing cool water
- Pleasant cherry almond fragrance reduces complaints regarding floor stripping odors

Applications

- Designed for floor finish removal on VCT, terrazzo and concrete flooring
- Test for softening or color bleeding on asphalt floors before using







Use Instructions

- Use appropriate personal protective equipment
- Dilute product as follows:

Light Build-up of Floor Finishes: Dilute product between 1:8 (16 fl. oz. / gal.) and 1:10 (13 fl. oz. / gal.) with cool water **Heavy Build-up of Floor Finishes:** Dilute product between 1:4 (32 fl. oz. / gal.) and 1:6 (24 fl. oz. / gal.) with cool water **Heavy Build-up of Concrete Sealers:** Dilute product at 1:2 (64 fl. oz./ gal.) with cool water

- Blockade areas to be stripped. Floors will be very slippery when stripper is applied. Exercise caution.
- Apply liberal amounts of solution uniformly to floor with a mop. Start with the edges to give them more soak time. If splashing occurs, wipe off surfaces with a clean rag dampened with water.
- Let stripper solution soak for 10-15 minutes. Mop agitate to loosen finish or sealer. Re-wet as necessary, do not allow stripper to dry on the floor. Longer soak times may be necessary in cases of extreme buildup.
- Hand or machine scrub thoroughly using appropriate stripper pads or stripping brush
- Pick-up all of the solution with a clean mop, wet vac or automatic scrubber
- Mop up any "tracks" left by wet vacs or automatic scrubbers before they dry. Thoroughly rinse floor with clean water, using a mop and bucket.
- Let floor dry completely before applying recommended Diversey brand floor sealer or finish

Important

• Do not use on wood, linoleum, rubber, marble, painted surfaces, on surface colored and acid dyed concrete floors as this product may harm these surfaces. Test for softening or color bleeding on asphalt floors before using.

Technical data	Attac [®] Stripper
Color/Form	Clear, liquid
рН	13
Scent	Cherry almond
Shelf Life	2 Years

Product	Pack size	Dilution	Product code	
Attac® Stripper	1 x 5 gal. / 18.9 L Envirobox ^{TM/MC}	1:2, 1:10	95032386	I+I

Safe handling

Please make sure your employees read and understand the product label and Safety Data Sheet before using this product. The label contains directions for use; and both the label and SDS contain hazard warnings, precautionary statements and first aid procedures. SDS are available online at www.diversey.com or by calling 888.352.2249. Improper use or dilution may result in damage to surfaces and may result in health and physical hazards that match those of the concentrate. Please refer to the Diversey HazMat Library, only available through Internet Explorer, http://naextranet.diversey.com/dot/, for up-to-date shipping information.