

Poly Studio Small Room Bundle for Zoom Rooms: Studio R30 USB Video Bar and HP PC w/TC10 TAA (9D9R3AA)

Overview



Smarter rooms, better meetings

Elevate virtual meetings with Al-driven features for immersive collaboration. Enjoy high-resolution video, noise-blocking, smart camera framing, and a secure conferencing PC in Zoom Rooms. Experience the future with Poly Studio Room Bundles.

A better way to meet and share

Poly Studio Room bundles for Zoom Rooms give you distraction-free meetings with innovative Poly camera tech. From small to large conference rooms, stay productive with technology that empowers the whole team, wherever they work.

Engineered for your enterprise

It's easy to make every Zoom Room a Poly Studio Room. Certified and purpose built, these cutting-edge meeting solutions fit perfectly into office workflows, offer a consistent user experience and are simple for IT to setup.

Peace of mind you can call on

Our Poly+ device support team is available 24/7, across the world. This extensive global network of support professionals help you confidently plan and successfully deploy Zoom Rooms.

Additional specifications

Audio	Poly NoiseBlockAI technology; Poly Acoustic Fence technology; Poly Acoustic Clarity technology
Audio standards	UAC Plug and Play compatible
Camera features	Manual pan, tilt and zoom control; Automatic meeting experience powered by Poly DirectorAI including speaker framing, presenter tracking, and conversation mode
Camera resolution	2160p, 4K UHD (3840 x 2160); 1080p, FHD (1920 x 1080); 720p, HD (1280 x 720)
Camera type	Single-lens
Certified collaboration software	Microsoft Teams; Zoom
Color	Sand
Diagonal field of view (dFoV)	120°
Horizontal field of view (hFoV)	110°
Lens cover capabilites	Integrated
Management Software	Poly Lens
Manufacturer Warranty	Poly standard one-year limited warranty
Microphone type	Three-microphone element beamforming array
Minimum dimensions (W x D x H)	17.5 \times 3.4 \times 3.2 in (with monitor clamp); 17.5 \times 2.7 \times 3.2 in (without monitor clamp)
Minimum dimensions (W x D x H)	445 x 86 x 81 mm (with monitor clamp); 445 x 68 x 81 mm (without monitor clamp)
Minimum order quantity	1
Non-Operating Humidity Range	5 to 95%
Operating altitude	3,000 m
Operating altitude	10,000 ft
Operating humidity range	15 to 80%
Operating temperature range	0 to 40 °C
Operating temperature range	32 to 104 °F
Physical security	Standard Kensington lock slot
Ports	1 USB Type-C® 5Gbps signaling rate; 2 USB 2.0 Type-A; 1 4.5 mm power adapter
Power	12V/3A
Power adapter port	1 x 4.5 mm
Power supply type	External
SMART camera technology	Poly DirectorAl with speaker framing; People framing; Group framing; Presenter tracking; DirectorAl perimeter

Sensitivity (speaker)	84 dB
Speaker type	Single speaker
Special features	Adjustable monitor clamp; Standard tripod thread; Inverted mounting option
UNSPSC code	45111902
Video standards	UVC Plug and Play compatible
Weight	1 lb (with monitor clamp); 1 lb (without monitor clamp)
Weight	822 g (with monitor clamp); 737 g (without monitor clamp)
What's in the box	Poly Studio R30; Monitor clamp; AC power adapter; Power cable; USB Type-C® to USB Type-A cable; Setup sheet; Removable privacy cap
Zoom capability	5x (without tracking); 4x (with auto tracking)

Disclaimer — Copyright

© Copyright 2024 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Generated by Dynamic Collateral Tool – (ww-en) – Mar 06, 2024 2:14 AM UTC+0000