

Floor Finishes

Protect your investment



All System (UHS) Products

Floor finishes make a great impact in a room – they provide a clean, luxurious look. The visual appearance of the floor can shape the perceptions of how clean and sanitary the entire building is. Our floor finishes are developed for use in high profile areas where the ultimate “wet look” gloss and durability are desired. They maintain their exceptional appearance and gloss even in high traffic areas – they even resist black heel marks, scuffs, and water damage. Their high solid content builds the required film thickness with fewer coats.

- Exceptional gloss
- Wear and scuff resistant
- Easy to maintain
- Detergent resistant
- Protects both resilient and non-resilient floors
- High and low flow rates

**Gloss rating statistics based on 5 coats of floor protective layers (sealer and floor finish combination).*



Coverage, 4 L: 1600 ft² to 2500 ft²
Number of Coats: 1-3
Drying Time: 30 minutes
Refractive Index: 25.0
Non-Volatile Solids: 20%
Gloss Rating: 87%*
COF: 0.7

Coverage, 5 L: 1480 ft² to 2410 ft²
Number of Coats: 1-3
Drying Time: 30 minutes
Refractive Index: 31.7 - 32.1
Non-Volatile Solids: 25%
Gloss Rating: 89-92%*
COF: 0.6

Coverage, 5 L: 2000 ft² to 3200 ft²
Number of Coats: 1-3
Drying Time: 15 minutes
Refractive Index: 23.9 - 24.3
Non-Volatile Solids: 20%
Gloss Rating: 87-89%*
COF: 0.5

Coverage, 5 L: 1830 ft² to 3014 ft²
Number of Coats: 1-3
Drying Time: 30 minutes
Refractive Index: 27.3 - 27.9
Non-Volatile Solids: 20%
Gloss Rating: 85-89%*
COF: 0.6

Coverage, 5 L: 1830 ft² to 3014 ft²
Number of Coats: 1-3
Drying Time: 30 minutes
Refractive Index: 23.9 - 24.3
Non-Volatile Solids: 18%
Gloss Rating: 85-89%*
COF: 0.6

Codes:

Orbit

52064 (4 L)
 52066 (20 L)

Runway ★★★

52163 (4 L)
 52164 (20 L)

Acclamation ★★

52060 (5 L)
 52061 (20 L)

Elite ★★

52051 (5 L)
 52052 (20 L)

Endurance ★★

52158 (5 L)
 52159 (20 L)

