



CANADA CATALOGUE



2020 EQUIPMENT CATALOGUE

QUICK SERVE RESTAURANT	FULL SERVICE	HEALTHCARE	COLLEGE & UNIVERSITY	AMUSEMENT & LEISURE	OFFICE SYSTEM	LODGING & HOSPITALITY	CONVENIENCE STORE	SPECIALTY
COFFEE	COFFEE	COFFEE	COFFEE	COFFEE	COFFEE	COFFEE	COFFEE	COFFEE
INFUSION SERIES® ICB	INFUSION SERIES® ICB	INFUSION SERIES® ICB	INFUSION SERIES® ICB	INFUSION SERIES® ICB	INFUSION SERIES® ICB	INFUSION SERIES® ICB	INFUSION SERIES® SH	INFUSION SERIES® ICB
AXIOM® DBC®	AXIOM® DBC®	INFUSION SERIES® SH	INFUSION SERIES® SH	VP17-1, VP17-2, VP17-3	VP17-1, VP17-2, VP17-3	INFUSION SERIES® SH	INFUSION SERIES® ICB	INFUSION SERIES® SH
CW-TC	CW-TC	VP17-1, VP17-2, VP17-3	VP17-1, VP17-2, VP17-3	SMARTWAVE® THERMAL	SMARTWAVE® THERMAL	VP17-1, VP17-2, VP17-3	AXIOM® DBC®	CW-TC
CW-APS	CW-APS	SMARTWAVE® THERMAL	SMARTWAVE® THERMAL	AXIOM® DBC®	CW-TC	SMARTWAVE® THERMAL	CW-TC	CW-APS
CWTF	CWTF	AXIOM® DBC®	AXIOM® DBC®	CW-TC	CW-APS	AXIOM® DBC®	CW-APS	CWTF-APS
CWTF-APS	CWTF-APS	CW-TC	CW-TC	CW-APS	CWTF	CW-TC	CWTF	ICB
ICB	ICB	CW-APS	CWA-APS	CWTF	CWTF-APS	CW-APS	CWTF-APS	GPR SINGLE
GPR SINGLE	GPR SINGLE	CWTF	CWTF	CWTF-APS	ICB	CWTF	ICB	GPR DUAL
GRINDERS	GPR DUAL	CWTF-APS	CWTF-APS	ICB	GRINDERS	CWTF-APS	GPR SINGLE	TITAN®
LPG	TITAN®	ICB	ICB	GRINDERS	LPG	ICB	GPR DUAL	SURE TAMP® AUTO
FPG-2 DBC	TITAN® DUAL	GPR SINGLE	GPR SINGLE	G9-2T HD	BEAN-TO-CUP	GPR SINGLE	TITAN®	SURE TAMP® STEAM
MHG	GRINDERS	GPR DUAL	GPR DUAL	MHG	CRESCENDO®	GPR DUAL	TITAN® DUAL	TRIFECTA®
G9WD RH	G9-2T HD	TITAN®	TITAN®	G9WD RH	SURE IMMERSION®	TITAN®	U3	GRINDERS
COLD COFFEE	G2, G3	TITAN® DUAL	TITAN® DUAL	BEAN-TO-CUP	COLD COFFEE	TITAN® DUAL	GRINDERS	LPG
NITRON ₂ ®	GVH	U3	U3	CRESCENDO®	NITRON ₂ ®	U3	LPG	G9-2T HD
IC3	MHG	GRINDERS	GRINDERS	SURE IMMERSION®	IC3	GRINDERS	G9-2T HD	FPG-2 DBC
ICED TEA	G9WD RH	G9-2T HD	G9-2T HD	COLD COFFEE	HOT WATER	G9-2T HD	FPG-2 DBC	G2, G3
INFUSION SERIES® ITB	BEAN-TO-CUP	MHG	MHG	NITRON ₂ ®	HW2	FPG-2 DBC	G2, G3	GVH
TB3, TB3Q	CRESCENDO®	G9WD RH	G9WD RH	IC3	COLD WATER	MHG	GVH	MHG
HOT CHOCOLATE/ CAPPUCCINO	SURE IMMERSION®	BEAN-TO-CUP	BEAN-TO-CUP	ICED TEA	BUNN REFRESH®	G9WD RH	MHG	G9WD RH
IMIX-3	COLD COFFEE	CRESCENDO®	CRESCENDO®	INFUSION SERIES® ITCB		BEAN-TO-CUP	G9WD RH	BEAN-TO-CUP
IMIX-3S+	NITRON ₂ ®	SURE IMMERSION®	SURE IMMERSION®	ITCB		CRESCENDO®	BEAN-TO-CUP	CRESCENDO®
IMIX-5	IC3	COLD COFFEE	COLD COFFEE	HOT CHOCOLATE/ CAPPUCCINO		SURE IMMERSION®	CRESCENDO®	SURE IMMERSION®
IMIX-5S+	ICED TEA	NITRON ₂ ®	NITRON ₂ ®	IMIX-3		COLD COFFEE	SURE IMMERSION®	COLD COFFEE
JUICE	INFUSION SERIES® ITB	IC3	IC3	IMIX-3S+		NITRON ₂ ®		NITRON ₂ ®
JDF-2S	TB3A, TB3QA	ICED TEA	ICED TEA	IMIX-5		IC3	COLD COFFEE	IC3
JDF-4S	HOT CHOCOLATE/ CAPPUCCINO	INFUSION SERIES® ITCB	INFUSION SERIES® ITCB	IMIX-5S+		ICED TEA	NITRON ₂ ®	ICED TEA
HOT WATER	IMIX-3	ITCB	ITCB	JUICE		TB3, TB3Q	IC3	INFUSION SERIES® ITB
H3E ELEMENT	IMIX-3S+	HOT CHOCOLATE/ CAPPUCCINO	HOT CHOCOLATE/ CAPPUCCINO	JDF-2S		HOT CHOCOLATE/ CAPPUCCINO	ICED TEA	TB3, TB3Q
H5X ELEMENT	IMIX-5	IMIX-3	IMIX-3	JDF-4S		IMIX-3	INFUSION SERIES® ITB	HOT CHOCOLATE/ CAPPUCCINO
HW2	IMIX-5S+	IMIX-3S+	IMIX-3S+	HOT WATER		IMIX-3S+	TB3, TB3Q	IMIX-3
H5E PC	JUICE	IMIX-5	IMIX-5	H3E ELEMENT		IMIX-5	HOT CHOCOLATE/ CAPPUCCINO	IMIX-3S+
COLD WATER	JDF-2S	IMIX-5S+	IMIX-5S+	H5X ELEMENT		IMIX-5S+	IMIX-3	IMIX-5
BUNN REFRESH®	JDF-4S	JUICE	JUICE	H5E PC		JUICE	IMIX-3S+	IMIX-5S+
FROZEN GRANITA/ SLUSHY	HOT WATER	JDF-2S	JDF-2S	COLD WATER		JDF-2S	IMIX-5	HOT WATER
ULTRA-2	H3E ELEMENT	JDF-4S	JDF-4S	BUNN REFRESH®		JDF-4S	IMIX-5S+	H3E ELEMENT
	H5X ELEMENT	HOT WATER	HOT WATER	FROZEN GRANITA/ SLUSHY		COLD WATER	JUICE	H5X ELEMENT
	COLD WATER	H3E ELEMENT	H3E ELEMENT	ULTRA-2		BUNN REFRESH®	JDF-2S	HW2
	BUNN REFRESH®	H5X ELEMENT	H5X ELEMENT			FROZEN GRANITA/ SLUSHY	JDF-4S	H5E PC
	FROZEN GRANITA/ SLUSHY	COLD WATER	COLD WATER			ULTRA-2	COLD WATER	COLD WATER
	ULTRA-2	BUNN REFRESH®	BUNN REFRESH®				BUNN REFRESH®	BUNN REFRESH®
		FROZEN GRANITA/ SLUSHY	FROZEN GRANITA/ SLUSHY				FROZEN GRANITA/ SLUSHY	
		ULTRA-2	ULTRA-2				ULTRA-2	



TABLE OF CONTENTS

BREWED BEVERAGES

COFFEE	3
<i>Infusion Series® Brewers</i>	3
<i>GPR Series Brewers</i>	10
<i>Thermal Brewers</i>	11
<i>Decanter Brewers</i>	15
<i>Pourover Brewers</i>	20
<i>Single Cup</i>	22
<i>High Volume Brewers</i>	25
GRINDERS	28
BEAN-TO-CUP	35
ESPRESSO	38
COLD COFFEE	42
COFFEE & TEA COMBOS	45
ICED TEA	50

DISPENSED BEVERAGES

LIQUID COFFEE	54
COLD COFFEE	60
HOT CHOCOLATE/CAPPUCCINO	64
JUICE	68
HOT WATER	72
COLD WATER	77
FROZEN GRANITA/SLUSHY	80

ACCESSORIES/EXTRAS

SERVING & HOLDING	83
WATER FILTRATION SYSTEMS	93
PAPER FILTERS	95
ACCESSORIES	97

A glass mug filled with dark coffee sits on a dark surface, surrounded by scattered coffee beans. The image is overlaid with a blue geometric pattern of overlapping squares and diamonds. The word "COFFEE" is written in white capital letters across the middle of the mug.

COFFEE

Infusion Series® Platinum Edition®

The New Infusion Series Platinum Edition line of brewing equipment is equipped with an intuitive 10.9cm touch screen, providing an enhanced user experience when operating and programming the brewers

ICB DV AND DV TALL

Intuitive 10.9cm touchscreen with user interface provides an enhanced experience when operating and programming the brewers

The powerful duo of a BUNN-exclusive Peak Extraction® Sprayhead coupled with SmartWAVE® technology delivers increased turbulence in the coffee bed, unrivaled uniformity of extraction, and complexity in the finished beverage

USB port for easy programming

Digital readout displays in English, Spanish, or French—for easier programming and control

Electronic funnel lock prevents removal of each brew funnel until drip- through is complete

ICB DV PE 53300.6100 and ICB TF PE 54300.6100 are compatible with new TF 3.8L & 5.7L Baseless ThermoFresh® Servers, all previous generations of TF 3.8L Baseless TF Servers, and Airtots

ICB DV TALL PE 53300.6101 and ICB TF 1.5 PE 54300.6101 are compatible with new TF 3.8L & 1.8L ThermoFresh® Servers (with Base), all previous generations of TF 5.7L TF Servers (with Base), Titan® 5.7L servers, and Airtots

Dual Voltage (DV) model can operate at 120V/15 amp or 120/208-240V/17 amp



ICB TF PE



ICB DV PE

Servers sold separately

DESCRIPTION								PAPER FILTER	CAPACITY	ELECTRICAL
Product #	Model	Finish	Funnel Type	Faucet	Dimensions Height x Width x Depth (Centimeters)			BUNN #	236mL cups/hr	Volts
53300.6100	ICB DV PE	STAINLESS	STAINLESS/SMART	NO	68.07	25.40	59.44	20138.1000	82	120
									136	120/208
									164	120/240
53300.6101	ICB DV TALL PE	STAINLESS	STAINLESS/SMART	NO	88.90	25.40	59.44	20138.1000	82	120
									136	120/208
									181	120/240
54300.6100	ICB TF PE	STAINLESS	STAINLESS/SMART	YES	64.11	30.84	59.46	20138.1000	164	120/240
54300.6101	ICB TF 1.5 PE	STAINLESS	STAINLESS/SMART	YES	86.33	30.84	56.62	20138.1000	164	120/240

Product #s listed as 120/208V or 120/240V require 3 wires plus ground (2 hot, 1 neutral, ground) and must be connected to 208V service or 240V service, respectively. Please refer to the installation manual for more information.



Infusion Series® Platinum Edition®

The New Infusion Series Platinum Edition line of brewing equipment is equipped with an intuitive 10.9cm touch screen, providing an enhanced user experience when operating and programming the brewers

ICB DV TWIN AND DV TWIN TALL

- Intuitive 10.9cm touchscreen with user interface provides an enhanced experience when operating and programming the brewers
- The powerful duo of a BUNN-exclusive Peak Extraction® Sprayhead coupled with SmartWAVE® technology delivers increased turbulence in the coffee bed, unrivaled uniformity of extraction, and complexity in the finished beverage
- The ICB Twin Infusion Series coffee brewer delivers twice the brew capacity, from a single platform
- Multiple recipes from one footprint --- with the flexibility to choose 1, 2 or 3 batch sizes per recipe
- Large 21.2L tank provides back-to-back brewing capacity USB port for easy programming
- Digital readout displays in English, Spanish, or French for easier programming and control
- Electronic funnel lock prevents removal of each brew funnel until drip- through is complete
- ICB Twin TF 53400.6100 and 54200.6100 are compatible with new TF 3.8L & 5.7L Baseless ThermoFresh® Servers, all previous generations of TF 3.8L Baseless TF Servers, and Airpots
- ICB Twin TF 53400.6101 and 54200.6101 are is compatible with both new TF 3.8L & 5.7L ThermoFresh® Servers (with Base), all previous generations of TF 5.7L TF Servers (with Base), Titan® 5.7L servers, and Airpots

Servers sold separately



ICB TWIN
TF PE



ICB TWIN
TALL PE

DESCRIPTION								PAPER FILTER	CAPACITY	ELECTRICAL
Product #	Model	Finish	Funnel Type	Faucet	Dimensions Height x Width x Depth (Centimetres)			BUNN #	236mL cups/hr	Volts
53400.6100	ICB TWIN PE	STAINLESS	STAINLESS/SMART	NO	68.07	51.31	61.98	20138.1000	280	120/240
53400.6101	ICB TWIN TALL PE	STAINLESS	STAINLESS/SMART	NO	88.90	51.31	56.64	20138.1000	280	120/240
54200.6100	ICB TWIN TF PE	STAINLESS	STAINLESS/SMART	YES	63.86	57.40	59.69	20138.1000	280	120/240
54200.6101	ICB TWIN TF 1.5 PE	STAINLESS	STAINLESS/SMART	YES	86.33	57.40	56.85	20138.1000	280	120/240

Infusion Series® Platinum Edition® with Soft Heat® Servers

The New Infusion Series Platinum Edition line of brewing equipment is equipped with an intuitive 10.9cm touch screen, providing an enhanced user experience when operating and programming the brewers

ICB SH AND TWIN SH

Intuitive 10.9cm touchscreen with user interface provides an enhanced experience when operating and programming the brewers

The powerful duo of a BUNN-exclusive Peak Extraction® Sprayhead coupled with SmartWAVE® technology delivers increased turbulence in the coffee bed, unrivaled uniformity of extraction, and complexity in the finished beverage

USB port for easy programming

Digital readout displays in English, Spanish, or French—for easier programming and control

Electronic funnel lock prevents removal of each brew funnel until drip- through is complete

New Infusion Soft Heat® servers [sold separately] are ergonomic, lighter weight, energy efficient and now offer programmable recipe/ batch-based holding times and temperatures, alerting staff when freshness has expired or server is empty

Wireless Server monitoring on some models allows for remote tracking of coffee freshness on mobile devices

Compatible with new Infusion SH servers, new TF 5.7L ThermoFresh® Servers (with Base), and all previous generations of TF 5.7L TF Servers (with Base)



Infusion Series® Soft Heat® Twin
(Stainless)



Infusion Series® Soft Heat®
(Stainless)

 Servers sold separately

DESCRIPTION							PAPER FILTER	CAPACITY	ELECTRICAL
Product #	Model	Finish	Funnel Type	Dimensions Height x Width x Depth (Centimetres)			BUNN #	236mL cups/hr	Volts
52100.6100	ICB SH PE	STAINLESS	STAINLESS/SMART	83.30	30.00	58.42	20138.1000	140	120/240
53600.6100	ICB TWIN SH PE	STAINLESS	STAINLESS/SMART	83.31	55.63	58.42	20138.1000	280	120/240

Product #s listed as 120/208V or 120/240V require 3 wires plus ground (2 hot, 1 neutral, ground) and must be connected to 208V service or 240V service, respectively. Please refer to the installation manual for more information.



Infusion Series® Standard Edition

The Infusion Series coffee and tea equipment platform provides Best Result in the Cup™ performance with the proven industry knowledge to deliver the lowest cost of ownership

ICB DV AND DV TALL

Three brew buttons for three separate brewing profiles; two programmable switches for full and half batches

Designed to brew into 2.5-3.8L airpots 3.8L and 5.7L ThermoFresh® servers without stand; also available in a tall model designed to brew into 3.8L & 5.7L TF servers with base

The exclusive Peak Extraction® Sprayhead features grooves that capture minerals and isolate the directional stream holes which then spray the whole coffee bed, providing full saturation and the ideal uniformity of extraction.

Dual voltage model; can operate at 120V/15 amp or 120/208-240V/17amp

Servers sold separately



ICB DV



ICB DV Tall

DESCRIPTION							PAPER FILTER	CAPACITY	ELECTRICAL
Product #	Model	Finish	Funnel Type	Dimensions Height x Width x Depth (centimeters)			BUNN #	236mL cups/hr	Volts
53100.6100	ICB-DV	STAINLESS	BLACK/SMART	68.1	25.4	55.9	20138.1000	82	120
								136	120/208
								181	120/240
53100.6101	ICB-DV Tall	STAINLESS	BLACK/SMART	88.9	25.4	55.9	20138.1000	82	120
								136	120/208
								181	120/240

Infusion Series® Standard Edition

The Infusion Series coffee and tea equipment platform provides Best Result in the Cup™ performance with the proven industry knowledge to deliver the lowest cost of ownership

ICB TWIN AND TWIN TALL

Double the options for brewing profiles and batch control

Large 21.2L tank provides back-to-back brewing capacity

Designed to brew into 2.5-3.8L airpots 3.8L and 5.7L ThermoFresh® servers without stand; also available in a tall model designed to brew into 3.8L & 5.7L TF servers with base

The exclusive Peak Extraction® Sprayhead features grooves that capture minerals and isolate the directional stream holes which then spray the whole coffee bed, providing full saturation and the ideal uniformity of extraction.



ICB Twin Tall



ICB Twin

 Servers sold separately

DESCRIPTION							PAPER FILTER	CAPACITY	ELECTRICAL
Product #	Model	Finish	Funnel Type	Dimensions Height x Width x Depth (centimeters)			BUNN #	236mL cups/hr	Volts
53200.6100	ICB TWIN	STAINLESS	BLACK/SMART	68.1	51.31	62.00	20138.1000	280	120/240
53200.6101	ICB TWIN TALL	STAINLESS	BLACK/SMART	88.9	51.31	62.00	20138.1000	280	120/240

Product #s listed as 120/208V or 120/240V require 3 wires plus ground (2 hot, 1 neutral, ground) and must be connected to 208V service or 240V service, respectively. Please refer to the installation manual for more information.



Infusion Series® Soft Heat® Edition

BUNN-exclusive Soft Heat technology supplies controlled heat to the brewed coffee within the server whenever it's docked on the brewer, ensuring ideal holding temperatures and optimal flavor for longer periods

ICB TWIN SH

Sleek modernized design language on the brewer and servers

The exclusive Peak Extraction® Sprayhead features grooves that capture minerals and isolate the directional stream holes which then spray the whole coffee bed, providing full saturation and the ideal uniformity of extraction.

Six brew buttons and three batch sizes allow for multiple brewing profiles

Easy Pulse programing automatically adjusts contact time for optimal flavor profile

Compatible with BrewWISE® intelligence

Wireless Server monitoring on some models allows for remote tracking of coffee freshness on mobile devices

New Infusion Soft Heat® servers [sold separately] are ergonomic, lighter weight, energy efficient and now offer programmable recipe/ batch-based holding times and temperatures, alerting staff when freshness has expired or server is empty

Compatible with new Infusion SH servers, new TF 5.7L ThermoFresh® Servers (with Base), and all previous generations of TF 5.7L TF Servers (with Base)

Servers sold separately



Infusion Series® Twin Soft Heat®
Stainless



Infusion Series®
Black/Stainless

DESCRIPTION							PAPER FILTER	CAPACITY	ELECTRICAL
Product #	Model	Finish	Funnel Type	Dimensions Height x Width x Depth (centimeters)			BUNN #	236mL cups/hr	Volts
51200.6100	ICB TWIN SH	STAINLESS	BLACK/SMART	94.23	65.79	71.37	20138.1000	280	120/240
51200.6101	ICB TWIN SH	BLACK/STAINLESS	BLACK/SMART	94.23	65.79	71.37	20138.1000	280	120/240
51200.6102	ICB TWIN SH	STAINLESS	BLACK/SMART	94.23	65.79	71.37	20138.1000	280	120/208
51200.6103	ICB TWIN SH W/WIRELESS COMM	STAINLESS	BLACK/SMART	94.23	65.79	71.37	20138.1000	280	120/240
51200.6104	ICB TWIN SH W/WIRELESS COMM	BLACK/STAINLESS	BLACK/SMART	94.23	65.79	71.37	20138.1000	280	120/240

For info regarding the new family of Infusion Series® equipment, call your BUNN Representative at 800-263-2256

Infusion Series® Soft Heat® Edition

BUNN-exclusive Soft Heat technology supplies controlled heat to the brewed coffee within the server whenever it's docked on the brewer, ensuring ideal holding temperatures and optimal flavor for longer periods

ICB SH

Sleek modernized design language on the brewer and servers

The exclusive Peak Extraction® Sprayhead features grooves that capture minerals and isolate the directional stream holes which then spray the whole coffee bed, providing full saturation and the ideal uniformity of extraction.

Three brew buttons and three batch sizes allow for multiple brewing profiles

Easy Pulse programing automatically adjusts contact time for optimal flavor profile

Compatible with BrewWISE® intelligence

Wireless Server monitoring on some models allows for remote tracking of coffee freshness on mobile devices

New Infusion Soft Heat® servers [sold separately] are ergonomic, lighter weight, energy efficient and now offer programmable recipe/batch based holding times and temperatures, alerting staff when freshness has expired or server is empty

Compatible with new Infusion SH servers, new TF 5.7L ThermoFresh® Servers (with Base), and all previous generations of TF 5.7L TF Servers (with Base)

Dual Voltage (DV) model can operate at 120V/15 amp or 120/208-240V/17 amp



Infusion Series® Soft Heat®
Stainless



Infusion Series® Soft Heat®
Stainless

 Servers sold separately

DESCRIPTION							PAPER FILTER	CAPACITY	ELECTRICAL
Product #	Model	Finish	Funnel Type	Dimensions Height x Width x Depth (centimeters)			BUNN #	236mL cups/hr	Volts
51100.6100	ICB SH	STAINLESS	BLACK/SMART	83.3	30.00	59.4	20138.1000	140	120/240
51100.6102	ICB SH	STAINLESS	BLACK/SMART	83.3	30.00	59.4	20138.1000	140	120/208
51100.6103	ICB SH W/WIRELESS COMM	STAINLESS	BLACK/SMART	83.3	30.00	59.4	20138.1000	140	120/240
51100.6105	ICB SH W/WIRELESS COMM	STAINLESS	BLACK/SMART	83.3	30.00	59.4	20138.1000	140	120/208

Product #s listed as 120/208V or 120/240V require 3 wires plus ground (2 hot, 1 neutral, ground) and must be connected to 208V service or 240V service, respectively. Please refer to the installation manual for more information.



GPR Series

GPR brewer design features a warmer stand, and 1.5 gallon (5.7 liter) portable reservoirs are included with each model

Coffee extraction controlled with programmable features

Troubleshoot all switches and electrical components from the front panel with advanced diagnostic service tools

GPR

Simple switch control

Single model includes choice of stainless or Smart Funnel® (compatible with BrewWISE® grinders)

Dual model includes choice of plastic or stainless funnel

Hot water faucet

AXIOM® SINGLE WITH GPR SERVER

Smaller footprint than Single GPR DBC

Gourmet C funnel allows use of heavier throw weights

Servers sold separately



GPR Dual



Single GPR DBC



GPR Single



Single AXIOM-15




Dual GPR DBC

DESCRIPTION								PAPER FILTER	CAPACITY	ELECTRICAL
Product #	Model	Batch Size Settings	Funnel Type	Faucet Location	Dimensions Height x Width x Depth (centimeters)			BUNN #	236mL cups/hr	Volts
23050.6000	SINGLE	THREE	STAINLESS	UPPER	74.4	45.72	49.02	20138.1000	169	120/208
23050.6001	SINGLE	THREE	STAINLESS	UPPER	74.4	45.72	49.02	20138.1000	81	120
23050.6003	SINGLE	THREE	STAINLESS	UPPER	74.4	45.72	49.02	20138.1000	182	120/240
20900.6007	DUAL	THREE	STAINLESS	UPPER	74.4	45.72	49.02	20138.1000	260	120/208
20900.6010	DUAL	THREE	STAINLESS	UPPER	74.4	45.72	49.02	20138.1000	302	120/240
38700.6143	SINGLE AXIOM-15	TWO	GOURMET C	UPPER	66.3	21.34	55.88	20157.0001	72	120
38700.6145	SINGLE AXIOM-35	TWO	GOURMET C	UPPER	66.3	21.34	55.88	20157.0001	120-144	120/208-240

AXIOM® Thermal Brewers

Medium volume brewing solution featuring *Digital Brewer Control™* for precise extraction control

Servers sold separately 

APS equipment brews directly into 1.9 to 3L airpots

TC equipment brews directly into thermal carafes up to 8.5" (21.6cm) tall

Programmable "Energy Saver Mode" reduces operating cost during idle periods

AXIOM-DV-APS, AXIOM-DV-TC

Voltage easily converts by flipping a switch and changing the power cord

AXIOM-TWIN-APS

Twin brew head system brews 15gal (56.8L) per hour



DESCRIPTION							PAPER FILTER	CAPACITY	ELECTRICAL
Product #	Model	Server Type	Funnel Type	Dimensions Height x Width x Depth (centimeters)			BUNN #	236mL cups/hr	Volts
38700.6010	AXIOM DV APS	AIRPOT	BLACK PLASTIC	59.94	22.86	46.99	20115.6000	67	120
								120	120/208
								120	120/240
38700.6011	AXIOM DV TC	THERMAL CARAFE	BLACK PLASTIC	45.2	22.86	57.15	20115.6000	67	120
								120	120/208
								120	120/240
38700.6013	AXIOM TWIN APS	AIRPOT	STAINLESS	59.7	40.64	56.39	20115.6000	120	120/240
38700.6016	AXIOM-35 APS	AIRPOT	STAINLESS	59.94	22.86	57.2	20115.6000	120	120/240
38700.6017	AXIOM-15 APS	AIRPOT	BLACK PLASTIC	59.94	22.86	57.2	20115.6000	67	120
38700.6034	AXIOM DV APS	AIRPOT	GOURMET	59.94	22.86	57.2	20115.6000	67	120
								120	120/208
								120	120/240
38700.6041	AXIOM DV APS	AIRPOT	STAINLESS	59.94	22.86	57.2	20115.6000	67	120
								120	120/208
								120	120/240
38700.6043	AXIOM DV APS W/PO	AIRPOT	STAINLESS	53.34	21.34	56.13	20115.6000	67	120
								120	120/208
								120	120/240
38700.6044	AXIOM-35 APS W/PO	AIRPOT	STAINLESS	53.34	21.34	56.13	20115.6000	120	120/240
38700.6050	AXIOM-15 TS (BLACK TRUNK)	THERMAL SERVER	BLACK PLASTIC	59.7	40.64	44.96	20115.6000	67	120
38700.6054	AXIOM-35 TS (BLACK TRUNK)	THERMAL SERVER	STAINLESS	59.7	40.64	44.96	20115.6000	120	120/240
38700.6057	AXIOM DV TS (BLACK TRUNK)	THERMAL SERVER	STAINLESS	59.7	40.64	44.96	20115.6000	67	120
								120	120/208
								120	120/240
38700.6063	AXIOM-35 TC W/PO	THERMAL CARAFE	STAINLESS	45.21	22.86	57.15	20115.6000	120	120/240
38700.6085	AXIOM-15 TC	THERMAL CARAFE	STAINLESS	45.21	22.86	57.15	20115.6000	67	120
38700.6088	AXIOM TWIN APS	AIRPOT	GOURMET	59.7	40.64	57.15	20115.6000	240	120/240

Product #s listed as 120/208V or 120/240V require 3 wires plus ground (2 hot, 1 neutral, ground) and must be connected to 208V service or 240V service, respectively. Please refer to the installation manual for more information.

SmartWAVE® Thermal Brewers

BUNN exclusive brewing technology that increases turbulence in the funnel for uniformity of extraction

Adjustable low profile design can accommodate a variety of thermal servers

Brews into a portable thermal carafe, pitcher, airpot or thermal server

Narrow footprint conserves countertop space

SPECIALTY

Choice of 14 pulse brew settings with touch button BrewMETER® simplifies changes to water contact time during brew cycle

Includes Gourmet C funnel for larger throw weights

Large 17-hole sprayhead maximizes uniformity of extraction

Four-digit LED display for programming and brewer status (Ready, Heating, Brewing)

STANDARD

Choice of 14 pulse brew settings with touch button BrewMETER® simplifies changes to water contact time during brew cycle

Four-digit LED display for programming and brewer status (Ready, Heating, Brewing)

SILVER

Choice of three pulse brew routines to adjust your flavor profile

Ensures coffee brew quality with cold brew lock out capability

Analog switches accompanied by red/green LED for programming



WAVE Specialty
(with Gourmet C funnel)



WAVE Silver
(with booster tray extended)



WAVE Standard
(with legs extended)

DESCRIPTION								PAPER FILTER	CAPACITY	ELECTRICAL
Product #	Model	Series	Funnel Type	Faucet	Dimensions Height x Width x Depth (centimeters)			BUNN #	236mL cups/hr	Volts
39900.6005	WAVE15-APS	STANDARD	BLACK PLASTIC	TRUNK	47.47	24.66	43.79	20115.6000	62	120
39900.6006	WAVE15-S-APS	SILVER	BLACK PLASTIC	TRUNK	47.47	24.66	43.79	20115.6000	62	120
39900.6008	WAVE-APS	STANDARD	BLACK PLASTIC	TRUNK	47.47	24.66	43.79	20115.6000	102	120/240
39900.6009	WAVE-S-APS	SILVER	BLACK PLASTIC	TRUNK	47.47	24.66	43.79	20115.6000	102	120/240



Automatic Thermal Brewers

Plumbed simple switch control brewing system brews directly into portable insulated servers that keep coffee at optimal temperature

CWTF-APS

Brew directly into 1.9 to 3L airpots

Hot water faucet with pourover backup feature

Choose from black plastic, stainless or Gourmet C funnel types

CWT15-APS

No hot water faucet

CWTF-DV

Voltage converts easily by flipping a switch



CWTF-DV

Servers sold separately

DESCRIPTION						PAPER FILTER	CAPACITY	ELECTRICAL
Product #	Model	Funnel Type	Dimensions Height x Width x Depth (centimeters)			BUNN #	236mL cups/hr	Volts
23001.6006	CWT15-APS (BLACK TRUNK)	BLACK PLASTIC	59.9	22.9	47	20115.6000	60	120
23001.6039	CWTF15-APS	STAINLESS	59.9	22.9	47	20115.6000	60	120
23001.6012	CWTF15-APS (BLACK TRUNK)	BLACK PLASTIC	59.9	22.9	47	20115.6000	60	120
23001.6013	CWTF15-APS	BLACK PLASTIC	59.9	22.9	47	20115.6000	60	120
23001.6017	CWTF35-APS (BLACK TRUNK)	BLACK PLASTIC	59.9	22.9	47	20115.6000	120	120/208-240
23001.6018	CWTF15-APS (BLACK TRUNK)	STAINLESS	59.9	22.9	47	20115.6000	60	120
23001.6016	CWTF35-APS	STAINLESS	59.9	22.9	47	20115.6000	120	120/208-240
23001.6054	CWTF35-APS	STAINLESS	59.9	22.9	47	20115.6000	120	120/208-240
23001.6056	CWTF-APS DV	BLACK PLASTIC	59.9	22.9	47	20115.6000	62	120
							107	120/208
							120	120/240
23001.6059	CWTF-APS DV	BLACK PLASTIC/ STAINLESS	59.9	22.9	47	20115.6000	62	120
							107	120/208
							120	120/240
23001.6074	CWTF-APS DV	GOURMET	59.9	22.9	47	20115.6000	62	120
							107	120/208
							120	120/240

Product #s listed as 120/208V or 120/240V require 3 wires plus ground (2 hot, 1 neutral, ground) and must be connected to 208V service or 240V service, respectively. Please refer to the installation manual for more information.



Automatic Thermal Brewers

Plumbed simple switch control brewing system brews directly into portable insulated servers that keep coffee at optimal temperature

CWTF-TC

- Accepts thermal carafe up to 21.6cm tall
- Use in a quick-turn environment where high quality coffee is continuously refreshed
- Hot water faucet and pourover backup feature
- Dual Voltage (DV) model can operate at 120V/15 amp or 120/208-240V/17 amp



CWTF15-TC

DESCRIPTION						PAPER FILTER	CAPACITY	ELECTRICAL
Product #	Model	Funnel Type	Dimensions Height x Width x Depth (centimeters)			BUNN #	236mL cups/hr	Volts
12950.6104	CWTF-15 TC	STAINLESS	46.22	22.86	47	20115.6000	62	120
12950.6107	CWTF-35 TC	BLACK PLASTIC	46.22	22.86	47	20115.6000	84	120/240
12950.6123	CWTF DV TC	BLACK PLASTIC	46.22	22.86	47	20115.6000	62	120
							107	120/208
							120	120/240
23400.6047	CWTF TWIN TC	STAINLESS	45.97	40.64	57.15	20115.6000	240	120/240
23000.6006	CWT-15 TS (BLACK TRUNK)	BLACK PLASTIC	70.1	22.86	47	20115.6000	62	120
23000.6012	CWTF-15 TS (BLACK TRUNK)	BLACK PLASTIC	70.1	22.86	47	20115.6000	62	120
23000.6016	CWTF-35 TS (BLACK TRUNK)	BLACK PLASTIC	70.1	22.86	47	20115.6000	120	120/240

AXIOM® RFID Decanter Brewer

Plumbed, medium volume brewing solution with RFID serving tracker and Digital Brewer Control™ for precise extraction control

RFID Coffee Server Management technology automatically tracks and communicates the age of brewed coffee

Works with glass decanters with replaceable RFID chip collar or thermal carafes

Automatic warmers shut off when glass RFID carafe is removed from the warmer plate or freshness expires

Dual voltage model can operate at 120V/15 amp or 120/208-240V/20 amp

Large 5.9L tank provides back-to-back brewing capacity



 Servers sold separately

AXIOM DV-3 RFID
(Upper Warmers)

DESCRIPTION								PAPER FILTER	CAPACITY	ELECTRICAL
Product #	Model	Finish	Warmers	Funnel Type	Dimensions Height x Width x Depth (centimeters)			BUNN #	236mL cups/hr	Volts
38700.6072	AXIOM-DV-3 RFID	STAINLESS	TWO UPPER/ ONE LOWER	STAINLESS	50.4	21.36	54.36	20115.6000	67	120
									120	120/208
									120	120/240
38700.6075	AXIOM-35-3 RFID	STAINLESS	TWO UPPER/ ONE LOWER	STAINLESS	50.4	21.36	54.36	20115.6000	120	120/240

Product #s listed as 120/208V or 120/240V require 3 wires plus ground (2 hot, 1 neutral, ground) and must be connected to 208V service or 240V service, respectively. Please refer to the installation manual for more information.

AXIOM® Decanter Brewer

Plumbed, medium volume brewing solution with Digital Brewer Control™ for precise extraction control

Large 5.9L tank provides back-to-back brewing capacity

Dual voltage model can operate at 120V/15 amp or 120/208-240V/20 amp

Coffee extraction controlled with programmable features



AXIOMP-DV-3

AXIOM 15-3
(Lower Warmers)

AXIOM 15-3
(Upper Warmers)

Servers sold
separately

DESCRIPTION									PAPER FILTER	CAPACITY	ELECTRICAL
Product #	Model	Pourover Feature	Finish	Warmers	Funnel Type	Dimensions Height x Width x Depth (centimeters)			BUNN #	236mL cups/hr	Volts
38700.6000	AXIOM-15-3	NO	STAINLESS	TWO UPPER/ ONE LOWER	BLACK PLASTIC	48.01	21.59	54.36	20115.6000	67	120
38700.6001	AXIOM-35-3	NO	STAINLESS	TWO UPPER/ ONE LOWER	BLACK PLASTIC	48.01	21.59	54.36	20115.6000	120	120/240
38700.6004	AXIOM-15-3	NO	STAINLESS	THREE LOWER	BLACK PLASTIC	42.67	41.91	54.36	20115.6000	67	120
38700.6008	AXIOM-DV-3	NO	STAINLESS	TWO UPPER/ ONE LOWER	BLACK PLASTIC	48.01	21.59	54.36	20115.6000	67	120
										120	120/208 120/240
38700.6009	AXIOM-DV-3	NO	STAINLESS	THREE LOWER	BLACK PLASTIC	42.67	41.91	54.36	20115.6000	67	120
										120	120/208 120/240
38700.6023	AXIOMP-DV-3	YES	STAINLESS	TWO UPPER/ONE LOWER	BLACK PLASTIC	54.34	21.59	54.36	20115.6000	67	120
										120	120/208 120/240

Automatic Decanter Brewers with Upper Warmers

Plumbed, medium volume brewing solution with simple switch controls

CWT

Faucet is not included on this model

Pourover backup

CWTF

Plastic or stainless funnel options

Hot water faucet and pourover backup on all models

Dual voltage model can operate at 120V/15 amp or 120/208-240V/20 amp



CWT

CWTF15
(with faucet)

Servers sold separately

DESCRIPTION								PAPER FILTER	CAPACITY	ELECTRICAL
Product #	Model	Faucet	Warmers	Funnel Type	Dimensions Height x Width x Depth (centimeters)			BUNN #	236mL cups/hr	Volts
12950.6009	CWT15-2 (BLACK TRUNK)	NO	ONE UPPER/ONE LOWER	BLACK PLASTIC	48.01	21.59	45.21	20115.6000	62	120
12950.6013	CWT15-3 (BLACK TRUNK)	NO	TWO UPPER/ONE LOWER	BLACK PLASTIC	48.01	21.59	45.21	20115.6000	62	120
12950.6033	CWTF15-2 (BLACK TRUNK)	YES	ONE UPPER/ONE LOWER	BLACK PLASTIC	48.01	21.59	45.21	20115.6000	62	120
12950.6038	CWTF15-3 (BLACK TRUNK)	YES	TWO UPPER/ONE LOWER	BLACK PLASTIC	48.01	21.59	45.21	20115.6000	62	120
12950.6053	CWTF35-3 (BLACK TRUNK)	YES	TWO UPPER/ONE LOWER	BLACK PLASTIC	48.01	21.59	45.21	20115.6000	120	120/240
12950.6054	CWTF35-3	YES	TWO UPPER/ONE LOWER	STAINLESS	48.01	21.59	45.21	20115.6000	120	120/240
12950.6065	CWTF15-3 (BLACK TRUNK)	YES	TWO UPPER/ONE LOWER	STAINLESS	48.01	21.59	45.21	20115.6000	62	120
12950.6066	CWTF35-3 (BLACK TRUNK)	YES	TWO UPPER/ONE LOWER	STAINLESS	48.01	21.59	45.21	20115.6000	120	120/240
12950.6115	CWTF35-3	YES	TWO UPPER/ONE LOWER	STAINLESS	48.01	21.59	45.21	20115.6000	120	120/240
12950.6118	CWTF-DV-3	YES	TWO UPPER/ONE LOWER	STAINLESS	48.01	21.59	45.21	20115.6000	62	120
									104	120/208
									120	120/240
12950.6100	CWTF-DV-3	YES	TWO UPPER/ONE LOWER	BLACK PLASTIC	48.01	21.59	45.21	20115.6000	62	120
									104	120/208
									120	120/240

Product #s listed as 120/208V or 120/240V require 3 wires plus ground (2 hot, 1 neutral, ground) and must be connected to 208V service or 240V service, respectively. Please refer to the installation manual for more information.

Automatic Decanter Brewers with Lower Warmers

Plumbed, medium volume brewing solution with simple switch controls and low-profile for undercabinet placement

CWT

Faucet is not included on this model

Pourover backup

CWTF

Hot water faucet and pourover backup on all models

Dual voltage model can operate at 120V/15 amp or 120/208-240V/20 amp

CRTF

Hot water faucet and pourover backup on all models

Five separately controlled warmers

VLPF

Makes good use of under-cabinet space with low profile height of 17.4" (44.2cm)

Faucet included

Two individually controlled warmers



CWT15-3



CRTF5-35



CWTF15-3



VLPF



DESCRIPTION									PAPER FILTER	CAPACITY	ELECTRICAL
Product #	Model	4" Legs	Faucet	Warmers	Funnel Type	Dimensions Height x Width x Depth (centimeters)			BUNN #	236mL cups/hr	Volts
12950.6031	CWTF15 (BLACK TRUNK)	NO	YES	ONE LOWER	BLACK PLASTIC	43.94	21.59	54.36	20115.6000	62	120
12950.6035	CWTF15-3 (BLACK TRUNK)	NO	YES	THREE LOWER	BLACK PLASTIC	43.94	41.66	54.36	20115.6000	62	120
12950.6051	CWTF35-3	NO	YES	THREE LOWER	BLACK PLASTIC	43.94	41.66	54.36	20115.6000	120	120/240
12950.6064	CWTF15-3 (BLACK TRUNK)	NO	YES	THREE LOWER	STAINLESS	43.94	41.66	54.36	20115.6000	62	120
12950.6097	CWTF35-4 (BLACK TRUNK)	YES	YES	3L-RIGHT/1U	STAINLESS	18.90	41.66	54.36	20115.6000	120	120/240
12950.6098	CWTF35-4 (BLACK TRUNK)	YES	YES	3L-LEFT/1U	STAINLESS	18.90	41.66	54.36	20115.6000	120	120/240
12950.6011	CWT15-3 (BLACK TRUNK)	NO	NO	THREE LOWER	BLACK PLASTIC	43.94	41.66	54.36	20115.6000	62	120
12950.6070	CWTF35-3	NO	YES	THREE LOWER	STAINLESS	43.94	41.66	54.36	20115.6000	120	120/240
12950.6101	CWTF-DV-3	NO	YES	THREE LOWER	STAINLESS	43.94	41.66	54.36	20115.6000	62	120
										104	120/208
										120	120/240
13250.6003	CRTF5-35	NO	YES	FIVE LOWER	BLACK PLASTIC	44.20	59.69	33.27	20115.6000	120	120/240
13250.6004	CRTF5-35	NO	YES	FIVE LOWER	STAINLESS	44.20	59.69	33.27	20115.6000	120	120/240
07400.6001	VLPF (BLACK TRUNK)	NO	YES	TWO LOWER	BLACK PLASTIC	44.20	59.69	33.27	20115.6000	62	120

Automatic Decanter Brewers with Twin Brewhead Systems

Plumbed high volume decanter brewing solution with Digital Brewer Control for precise extraction control

AXIOM® 4/2, 0/6

Coffee extraction controlled with programmable features

Electronic diagnostics and built-in tank drain make service easier

Six individually controlled warmers available in either lower or upper/lower design



AXIOM 4/2



AXIOM 0/6

⚠ Servers sold separately

DESCRIPTION								PAPER FILTER	CAPACITY	ELECTRICAL
Product #	Model	4" Legs	Warmers	Funnel Type	Dimensions Height x Width x Depth (centimeters)			BUNN #	236mL cups/hr	Volts
23400.6001	CWTF 2/2 TWIN	YES	TWO UPPER /TWO LOWER	STAINLESS	48.77	40.64	50.04	20115.6000	240	120/240
23400.6002	CWTF 4/2 TWIN	YES	FOUR UPPER /TWO LOWER	STAINLESS	48.77	40.64	50.04	20115.6000	240	120/240
38700.6014	AXIOM 4/2 TWIN	NO	FOUR UPPER /TWO LOWER	STAINLESS	48.51	41.66	56.90	20115.6000	240	120/208-240
38700.6015	AXIOM 0/6 TWIN	YES	SIX LOWER	STAINLESS	43.94	21.34	47.75	20115.6000	240	120/208-240

Product #s listed as 120/208V or 120/240V require 3 wires plus ground (2 hot, 1 neutral, ground) and must be connected to 208V service or 240V service, respectively. Please refer to the installation manual for more information.

Pourover Decanter Brewers

Ideal simple switch control office coffee service that does not require plumbing or special wiring

VP17 SERIES

One, two, or three separately controlled warmers

SplashGard® funnel deflects hot liquids away from the hand

VPR SERIES

Two individually controlled warmers

Side-to-side design rests against wall, freeing countertop space

Internal components are constructed from stainless steel

VPS SERIES

Three individually controlled warmers

SplashGard® funnel deflects hot liquids away from the hand



VP17-1

VP17-2

VPR

VPS

VP17-3 Stainless

Servers sold separately

DESCRIPTION								PAPER FILTER	CAPACITY	ELECTRICAL
Product #	Model	Finish	Warmers	Includes Decanter	Dimensions Height x Width x Depth (centimeters)			BUNN #	236mL cups/hr	Volts
13300.6001	VP17-1	STAINLESS	ONE LOWER	NO	43.94	21.34	47.75	20115.6000	60	120
13300.6003	VP17-2	STAINLESS	ONE UPPER/ONE LOWER	NO	48.26	21.34	47.75	20115.6000	60	120
13300.6005	VP17-3	STAINLESS	THREE LOWER	NO	43.94	41.15	47.75	20115.6000	60	120
13300.6011	VP17-3 W/STAINLESS FUNNEL	STAINLESS	TWO UPPER/ ONE LOWER	NO	48.26	21.34	47.75	20115.6000	60	120
13300.6000	VP17-1	BLACK	ONE LOWER	NO	43.94	21.34	47.75	20115.6000	60	120
13300.6002	VP17-2	BLACK	ONE UPPER/ONE LOWER	NO	48.26	21.34	47.75	20115.6000	60	120
13300.6004	VP17-3	BLACK	THREE LOWER	NO	43.94	41.15	47.75	20115.6000	60	120
13300.6028	VP17-3	BLACK	TWO UPPER/ONE LOWER	NO	48.26	21.34	47.75	20115.6000	60	120
04275.6014	VPS	BLACK	ONE UPPER /TWO LOWER	NO	48.77	58.42	20.32	20115.6000	62	120
33200.6000	VPR	BLACK	ONE UPPER/ONE LOWER	NO	51.31	41.15	20.32	20115.6000	62	120
33200.6001	VPR	BLACK	ONE UPPER/ONE LOWER	EASY POUR	51.31	41.15	20.32	20115.6000	62	120

Pourover Thermal Brewers

Simple switch design requires no plumbing or special wiring, and brews directly into portable insulated servers

CW15-APS SERIES

Simple switch controls

Brews directly into 1.9 to 3L airpots

CW15-TC SERIES

Models are space-saving 22.9cm wide

Accepts thermal carafes up to 21.6 cm tall

VPR-APS SERIES

Internal components are constructed from stainless steel

Accommodates 1.9 to 3L airpots

VPR-TC SERIES

Brew directly into 64oz (1.9L) thermal carafes with brew-thru lid

Side-to-side design rests against wall, freeing countertop space



VPR-APS

 Servers sold separately



CW15-APS



CW15-TC



VPR-TC

DESCRIPTION								PAPER FILTER	CAPACITY	ELECTRICAL
Product #	Model	Finish	Includes 2.2L Airpot	Funnel Type	Dimensions Height x Width x Depth (centimeters)			BUNN #	236mL cups/hr	Volts
23001.6000	CW15-APS	STAINLESS	NO	BLACK PLASTIC	59.94	22.86	46.99	20115.6000	61	120
23001.6001	CW15-APS	BLACK	NO	BLACK PLASTIC	59.94	22.86	46.99	20157.0001	61	120
23001.6057	CW15-TC	STAINLESS	NO	BLACK PLASTIC	46.74	22.86	49.53	20115.6000	62	120
23001.6058	CW15-TC	STAINLESS	NO	STAINLESS	46.74	22.86	49.53	20115.6000	62	120
33200.6010	VPR-APS	BLACK	NO	BLACK PLASTIC	67.56	40.39	20.32	20115.6000	62	120
33200.6011	VPR-TC	BLACK	NO	BLACK PLASTIC	54.10	40.39	20.32	20115.6000	62	120

Product #s listed as 120/208V or 120/240V require 3 wires plus ground (2 hot, 1 neutral, ground) and must be connected to 208V service or 240V service, respectively. Please refer to the installation manual for more information.



My Café® Cartridge

Commercial-grade single serve cartridge system

SINGLE CUP MY CAFÉ® MCO

Ideal for office and small business environments

Designed to be compliant with ADA self service requirements

Flip tray accommodates a wide range of cup sizes and travel mugs



MCO

DESCRIPTION				CAPACITY	ELECTRICAL
Product #	Model	Type	Dimensions Height x Width x Depth (centimeters)		Volts
44500.6000	MCO MY CAFE OFFICE	AUTOMATIC	42.55	29.72 52.32	60 120

My Café® Pod

Commercial-grade, single serve pod system

MY CAFÉ® AP

Automatically disposes of spent pods after each brew

Control extraction utilizing pulse-brew technology with BrewMETER®

New single tank pump design provides consistent brew quality on varying water pressures

MY CAFÉ® MCP & MCA

Accommodates 45mm to 61mm pods

A drawer style pod holder keeps hands allows for mess-free pod disposal

Fast brew coffee in about 30 seconds

Stainless steel heating tank uses a thermostat to hold water at the perfect ready-to-brew temperature

MY CAFÉ® MCP POUROVER

Pourover unit requires no plumbing, and is easy to use and maintain with a removable water reservoir

MY CAFÉ® MCA AUTOMATIC

Automatic model is connected to a water line, eliminating the need to manually refill the water reservoir



My Café
Pourover (MCP)



My Café
Automatic (MCA)



My Café
AutoPod®

DESCRIPTION							CAPACITY	ELECTRICAL
Product #	Model	Type	High Altitude	Dimensions Height x Width x Depth (centimeters)			236mL cups/hr	Volts
42300.6000	MY CAFE AP	AUTOMATIC	N/A	40.13	24.64	38.61	60	120
35400.6000	MCP	POUROVER	NO	37.75	20.32	26.67	60	120
35400.6008	MCA Hi Alt	AUTOMATIC	YES	34.54	20.32	26.67	60	120
35400.6013	MCA	AUTOMATIC	YES	34.54	20.32	26.67	60	120

Product #s listed as 120/208V or 120/240V require 3 wires plus ground (2 hot, 1 neutral, ground) and must be connected to 208V service or 240V service, respectively. Please refer to the installation manual for more information.



Trifecta®

Tech-enabled, barista-crafted single cup brewer that heightens the quality of coffee and tea

TRIFECTA BREWING PHASES

Wetting: The saturation of the coffee grounds and specialty loose leaf tea can be controlled to get the percentage of water and pause appropriate for the selected varieties.

Extraction: Air is injected into the chamber so that the grounds are agitated using Air Infusion technology. The result: uniformity of extraction and a complex beverage complex beverage that coffee and tea enthusiasts will enjoy.

Hydrolysis: Air presses the beverage through a permanent metal screen that filters out coffee grounds or tea leaves while preserving oils and aromatics for a deep-bodied, unique flavor experience.



trifecta
silver



trifecta
white

DESCRIPTION						ELECTRICAL
Product #	Model	Finish	Dimensions Height x Width x Depth (centimeters)			Volts
41200.6000	TRIFECTA	SILVER	67.89	30.20	30.15	120
41200.6005	TRIFECTA	WHITE	67.89	30.20	30.15	120

Titan® Series

High volume solution using fresh ground coffee and featuring Digital Brewer Control™ for precise extraction control

Coffee extraction controlled with pre-infusion and pulse brew, digital temperature control, and large sprayhead; variable bypass controls coffee strength

BrewMETER® allows automatic programming of pulse routine

Funnel has 794 grams capacity and paper filter retainers to eliminate fold-over



Titan Single



Titan Dual

Servers sold separately

DESCRIPTION							PAPER FILTER	CAPACITY	ELECTRICAL	
Product #	Model	Faucet	Funnel Type	Dimensions Height x Width x Depth (centimeters)			BUNN #	236mL cups/hr	Volts	Phase
39200.6000	TITAN DUAL	LOWER	STAINLESS	101.65	90.50	55.22	20111.0000	560	120/208	THREE
								382	120/208	SINGLE
39200.6001	TITAN DUAL	LOWER	STAINLESS	101.65	90.50	55.22	20111.0000	560	120/240	THREE
								382	120/240	SINGLE
39300.6000	TITAN SINGLE	LOWER	STAINLESS	101.65	54.10	55.22	20111.0000	360	120/208	THREE
								272	120/208	SINGLE
39400.6000	TITAN TF SERVER 3GAL	N/A	N/A	60.20	34.80	43.43	N/A	N/A	N/A	N/A
46300.6000	TITAN TF SERVER 1.5GAL	N/A	N/A	58.17	29.72	38.86	N/A	N/A	N/A	N/A

Product #s listed as 120/208V or 120/240V require 3 wires plus ground (2 hot, 1 neutral, ground) and must be connected to 208V service or 240V service, respectively. Please refer to the installation manual for more information.



Urns

Unique urn brewer design ensures low evaporation loss

U3 TWIN

Large water tank holds over 20gal (75.7L)

Half-batch option

Draw off hot water during brew cycle without affecting coffee quality



U3 - Twin

DESCRIPTION								PAPER FILTER	CAPACITY	ELECTRICAL
Product #	Model	Faucet	Finish	Funnel Type	Dimensions Height x Width x Depth (centimeters)			BUNN #	236mL cups/hr	Volts
20500.6000	U3	YES	STAINLESS	BLACK PLASTIC	82.30	87.63	53.34	20109.0000	268	120/208
20500.6002	U3 W/BYPASS	YES	STAINLESS	BLACK PLASTIC	82.30	87.63	53.34	20109.0000	268	120/208
20500.6006	U3 W/BYPASS	YES	STAINLESS	BLACK PLASTIC	82.30	87.63	53.34	20109.0000	310	120/240
20500.6024	U3 (DOUBLE SERVICE)	YES	STAINLESS	BLACK PLASTIC	82.30	87.63	53.34	20109.0000	268	120/208
20500.6028	U3 (DOUBLE SERVICE)	YES	STAINLESS	BLACK PLASTIC	82.30	87.63	53.34	20109.0000	310	120/240
20500.6004	U3	YES	STAINLESS	BLACK PLASTIC	82.30	87.63	53.34	20109.0000	310	120/240
20500.6072	U38	YES	STAINLESS	BLACK PLASTIC	82.30	87.63	53.34	20109.0000	499	120/208
20500.6076	U38	YES	STAINLESS	BLACK PLASTIC	82.30	87.63	53.34	20109.0000	499	120/240



GRINDERS

G Series VH Grinder

Users have 340° of grind resolution on the “no-click” selection dial, giving them complete freedom when dialing-in their ideal grind particle size.

- Available in .45kg, .91kg and 1.36kg versions. the GVH series features tinted hoppers that are sleek and durable.
- Versatile design allows grinding into bags, cans, and cups and other containers to meet a multitude of customer needs
- Fast grinding – one pound (.45kg) in about 30 seconds – maximizes speed of service
- 340° dial resolution for precise tuning of grind particle size
- Ergonomic clamp for holding smaller size bags and containers in place for hands-free operation
- Easy to use cleaning lever for complete removal of coffee from grind chamber ensures the customer gets all the coffee ground for them
- Precision Rockwell 65C hard burrs provide consistency, grind after grind
- Bag switch prevents grinding before bag/container is in place
- Four-year warranty on grinding burrs



DESCRIPTION						CAPACITY	ELECTRICAL
Product #	Model	Finish	Dimensions Height x Width x Depth (centimeters)			Per Hopper	Volts
55600.6100	GVH-1	STAINLESS	58.70	17.80	40.40	.45kg	120
55600.6200	GVH-2	STAINLESS	62.50	17.80	40.40	.9kg	120
55600.6300	GVH-3	STAINLESS	65.50	17.80	40.40	1.4kg	120

Multi-Hopper Series Grinder and Storage System

An intuitive, portion-controlled coffee grinding system that handles multiple bean varieties

- Portion-controlled for the right amount of coffee every time, with 3 batch sizes per hopper
- Convenient front-loading hoppers are easy to clean and store individual coffee grind weight profiles
- Choice of black or stainless finish

BrewWISE® intelligence means the Smart Funnel® manages the grinding and brewing process from start to finish:

- Grinder adjusts the grind time for each batch to deliver just the right grind volumes
- Grinder communicates coffee batch size and coffee name to the Smart Funnel during grinding process
- BrewWISE brewer reads the information in the Smart Funnel, adjusts the recipe, and brews a flavorful batch of coffee

RACK AND HOPPER

Store and display coffee varieties and promote fresh ground coffee program

Hoppers with locking lids serve as storage containers when not in the grinder
(lock for lids sold separately)



4 Position Storage System



2 Position Storage System



Hopper Assembly



MHG

DESCRIPTION							CAPACITY	ELECTRICAL
Product #	Model	Finish	Number of Hoppers	Dimensions Height x Width x Depth (centimeters)			Per Hopper	Volts
35600.6020	MHG	STAINLESS	TWO	73.91	23.77	45.72	2.7KG	120
35600.6022	MHG	BLACK	TWO	73.91	23.77	45.72	2.7KG	120
36760.0000	TWO POSITION RACK	N/A	N/A	29.21	25.40	41.20	N/A	N/A
36760.0001	FOUR POSITION RACK	N/A	N/A	61.72	23.77	45.72	N/A	N/A
36845.7000	HOPPER ASSEMBLY	N/A	N/A	N/A	N/A	N/A	2.7KG	N/A

Product #s listed as 120/208V or 120/240V require 3 wires plus ground (2 hot, 1 neutral, ground) and must be connected to 208V service or 240V service, respectively. Please refer to the installation manual for more information.



Weight Driven Series Grinder

Weight-based, portion-control for the right amount of coffee every time with three batch sizes

Unparalleled grind weight accuracy

Front-loading, removable hopper is easy to clean

BrewWISE® intelligence means the Smart Funnel® manages the grinding and brewing process from start to finish:

Grinder communicates coffee weight to the Smart Funnel during the grinding process

BrewWISE brewer reads the information in the Smart Funnel, adjusts the recipe, and brews a flavorful batch of coffee



G9WD-RH

DESCRIPTION							CAPACITY	ELECTRICAL
Product #	Model	Finish	Number of Hoppers	Dimensions Height x Width x Depth (centimeters)			Per Hopper	Volts
40700.6001	G9WD-RH	STAINLESS	ONE	75.69	20.68	48.26	2.7KG	120
36845.7000	HOPPER ASSEMBLY	N/A	N/A	N/A	N/A	N/A	2.7KG	N/A

Portion Control Series Grinder

With three batch sizes per hopper and Digital Brewer Control

G9-2T DBC

Two hoppers hold 6lbs (2.7kg) each of regular and decaf or specialty beans

Stores individual coffee grind profiles

BrewWISE® intelligence means the Smart Funnel® manages the grinding and brewing process from start to finish:

Grinder adjusts the grind time for each batch to deliver just the right grind volumes

Grinder communicates coffee batch size and coffee name to the Smart Funnel during the grinding process

BrewWISE brewer reads the information in the Smart Funnel, adjusts the recipe, and brews a flavorful batch of coffee

FPG-2 DBC

Two hoppers hold 3lbs (1.4kg) each of regular and decaf or specialty beans

Accommodates up to 8" (20.3cm) tall French Press or funnel for drip-style brewer

Multi-batch setting allows users to specify a French Press brew size or grind enough coffee into a funnel to brew larger amounts of drip-style coffee

French press for display purposes only, not available for purchase



FPG-2 DBC



G9-2T DBC

DESCRIPTION				CAPACITY			ELECTRICAL	
Product #	Model	Finish	Number of Hoppers	Dimensions Height x Width x Depth (centimeters)			Per Hopper	Volts
33700.6000	G9-2T DBC	STAINLESS	TWO	68.83	21.08	45.72	2.7kg	120
33700.6001	G9-2T DBC	BLACK	TWO	68.83	21.08	45.75	2.7kg	120
36400.6000	FPG-2 DBC	STAINLESS	TWO	45.90	21.08	25.40	1.4kg	120

Product #s listed as 120/208V or 120/240V require 3 wires plus ground (2 hot, 1 neutral, ground) and must be connected to 208V service or 240V service, respectively. Please refer to the installation manual for more information.



Portion Control Series Grinder

Coffee grinding systems with simple switch control operation

G9T HD - 1 HOPPER

Single hopper holds 9lbs (4.1kg)

Accommodates larger brew funnels

LPG - 1 HOPPER

Hopper holds 6lbs (2.7kg)

Low profile height and narrow footprint conserves countertop space

Easy access on back for grind weight adjustment

LPG2E - 2 HOPPERS

3lbs (1.4kg) capacity per hopper



LPG



LPG-2E



G9T HD

DESCRIPTION							CAPACITY	ELECTRICAL
Product #	Model	Finish	Number of Hoppers	Dimensions Height x Width x Depth (centimeters)			Per Hopper	Volts
05800.6001	G9T HD	STAINLESS	ONE	27.00	8.00	18.00	(4.2kg)	120
05800.6002	G9T HD WIRED INTERFACE	STAINLESS	ONE	27.00	8.00	18.00	(4.2kg)	120
24250.6001	G9-2T HD TALL WIRED INTERFACE	STAINLESS	TWO	63.50	20.32	45.72	(2.7kg)	120
20580.6000	LPG	STAINLESS	ONE	15.10	8.60	10.00	(2.7kg)	120
20580.6001	LPG	BLACK	ONE	15.10	8.60	10.00	(2.7kg)	120
26800.6000	LPG-2E	STAINLESS	TWO	17.50	8.60	10.90	3lbs (1.4kg)	120



Bulk Series Grinder

High volume grinding systems with turbo action that draws the coffee through the chamber for greater grinding speed and efficiency

G1, G3 HD

Grinds 1lb (.45kg) in approximately 30 seconds

Wide range of grinds can be selected



G1 HD



G3 HD

DESCRIPTION							CAPACITY	ELECTRICAL
Product #	Model	Switch	Finish	Dimensions Height x Width x Depth (centimeters)			Per Hopper	Volts
22100.6000	G3 HD	LIFT SWITCH EXTENDED SLOT	BLACK	69.09	18.80	40.64	(1.4kg)	120
22100.6002	G3 HD	LIFT SWITCH EXTENDED SLOT	RED	69.09	18.80	40.64	(1.45kg)	120
22100.6006	G3 HD	PIVOT SWITCH	BLACK	69.09	18.80	40.64	(1.4kg)	120
22104.6001	G1 HD	LIFT SWITCH EXTENDED SLOT	BLACK	57.91	18.54	40.64	(.45kg)	120
22104.6003	G1 HD	LIFT SWITCH EXTENDED SLOT	RED	57.91	18.54	40.64	(.45kg)	120
22104.6007	G1 HD	PIVOT SWITCH	BLACK	57.91	18.54	40.64	(.45kg)	120

Product #s listed as 120/208V or 120/240V require 3 wires plus ground (2 hot, 1 neutral, ground) and must be connected to 208V service or 240V service, respectively. Please refer to the installation manual for more information.



A top-down view of a coffee cup and saucer. The cup is filled with dark coffee and has a thick, light-colored foam head. The saucer is a dark, speckled teal color. Above the cup, a wooden spoon is filled with coffee beans. The background is a dark, textured surface. The image is overlaid with several semi-transparent geometric shapes in shades of blue and grey. The text "BEAN TO CUP" is centered in the cup.

BEAN TO CUP

Sure Immersion®

Fresh, expertly-extracted coffee from an intuitive touchscreen experience

Filter style coffee from a vacuum system with exclusive Air Infusion extraction control resulting in a clean, balanced cup with a smooth finish

Coffee selections include iced and hot options

Each recipe has programmable air-infusion and immersion control for the Best Result in the Cup™

Dispense fresh coffee in 5 portion sizes, programmable from 177 to 710ml cup plus carafe

312

Three bean hoppers, one grinder and two soluble hoppers for cafe style beverages

220

Two independent grinders with precision burrs for accurate grind profiles



Sure Immersion® 220



Sure Immersion® 312

DESCRIPTION						CAPACITY	ELECTRICAL
Product #	Model	Finish	Dimensions Height x Width x Depth (centimeters)			296mL cups/hr	Volts
44400.6100	SURE IMMERSION 220	STAINLESS/BLACK	100.20	40.90	50.16	50	120
44400.6200	SURE IMMERSION 312	STAINLESS/BLACK	102.30	51.00	58.00	50	120
44400.6240	SURE IMMERSION 312	STAINLESS/BLACK	102.30	51.00	58.00	50	120/208-240



Crescendo®

Authentic espresso served pure, or built into your choice of 9 café beverages

Touchpad features two programmable portion sizes, 230 and 350ml and 9 beverage choices, plus hot water

9 bar brew pressure used with a variable brew group produces an excellent single or double shot with beautiful crema

Engineered with three powder hoppers; two 3.3lb (1.5kg) hoppers for the larger demand flavors and a third 2.2lb (1kg) hopper that allows for additional flavor

1 kg bean hopper displays fresh, whole bean coffee

Pleasing design with a compact footprint



Crescendo®

DESCRIPTION						CAPACITY	ELECTRICAL
Product #	Model	Finish	Dimensions Height x Width x Depth (centimeters)			Shots/hr	Volts
44300.6201	CRESCENDO	BLACK/STAINLESS	79.44	35.88	47.94	40	120
44300.6240	CRESCENDO	BLACK/STAINLESS	79.44	35.88	47.94	40	120-208/240

A close-up photograph of a white ceramic espresso cup being filled with coffee from a machine. Two streams of dark coffee are pouring into the cup, which already contains a layer of white foam. The cup sits on a metal drip tray. The background is dark and out of focus. The image is overlaid with several semi-transparent blue and white diamond shapes. The word "ESPRESSO" is written in white capital letters across the middle of the cup.

ESPRESSO

Superautomatic Espresso

Reliably serve espresso from an intuitive touchscreen interface, with options to expand your espresso offerings into lattes, cocoa, and other flavors

- Modular design of systems makes maintenance simple
- Adjustable dispense spout
- Integrated 1gal (4L) single-milk refrigerator with milk-level and temperature monitoring

BLACK & WHITE4c CTM P F RS

- Two 2.2lb (1kg) bean hoppers for your choice of fresh espresso beans
- One 4.4lb (2kg) chocolate powder hopper and four flavors (standard syrup bottle) enable crafting of your favorite café treats, such as vanilla latte and seasonal offerings – your beverage menu is limited only by your imagination

BLACK & WHITE4c CTM P RS

- Two 2.2lb (1kg) bean hoppers for your choice of fresh espresso beans
- One 4.4lb (2kg) chocolate powder hopper to enable crafting of mochas and hot chocolates



B&W4c CTM P F RS



B&W4c CTM P RS

DESCRIPTION					CAPACITY	ELECTRICAL
Product #	Model	Dimensions Height x Width x Depth (centimeters)			shots/hr	Volts
55300.xxxx*	B&W4c CTM P RS	67.50	66.00	60.00	180	208
55300.xxxx*	B&W4c CTM P F RS	67.50	66.00	60.00	180	208

*For information regarding Espresso package options, contact your BUNN Representative by calling 800-263-2256

Superautomatic Espresso

Reliably serve espresso from an intuitive touchscreen interface, with options to expand your espresso offerings into lattes, cocoa, and other flavors

Modular design of systems makes maintenance simple

Adjustable dispense spout

BLACK & WHITE3 CTMC

Two 3.3lb (1.5kg) bean hoppers for your choice of fresh espresso beans

One 4.4lb (2kg) chocolate powder hopper to enable crafting of mochas and hot chocolates

Integrated milk refrigerator holds up to 1.32gal (5L) of milk

BLACK & WHITE3 CTMS

Two 3.3lb (1.5kg) bean hoppers for your choice of fresh espresso beans

Integrated milk refrigerator holds up to 1.32gal (5L) of milk

Intellisteam® wand automatically steams milk to proper temperature - no need to monitor with a thermometer

BLACK & WHITE3 CTS

Two 3.3lb (1.5kg) bean hoppers for your choice of fresh espresso beans

Intellisteam® wand automatically steams milk to proper temperature - no need to monitor with a thermometer

Ability to steam .26gal (1L) of milk in under one minute



B&W3-CTS



B&W3 CTMC



B&W3 CTMS

DESCRIPTION					CAPACITY	ELECTRICAL
Product #	Model	Dimensions Height x Width x Depth (centimeters)			shots/hr	Volts
43500.xxxx*	B&W3 CTS	70.00	52.00	60.00	240	208
43500.xxxx*	B&W3 CTMS	70.00	77.00	60.00	240	208
43500.xxxx*	B&W CTMC	78.00	77.00	60.00	240	208

*For information regarding Espresso package options, contact your BUNN Representative by calling 800-263-2256

Product #s listed as 120/208V or 120/240V require 3 wires plus ground (2 hot, 1 neutral, ground) and must be connected to 208V service or 240V service, respectively. Please refer to the installation manual for more information.



Superautomatic Espresso

BUNN exclusive design features constant and consistent tamping pressure throughout the brewing process

Sure Tamp®

Intellisteam® wand on SureTamp Steam model automatically steams to proper milk temperature

Two hoppers allow for your choice of fresh espresso beans

SureTamp Auto can be set up as self serve or crew serve

SureTamp Auto milk delivery system accommodates two milk types

Espresso Refrigerator

Designed to accommodate two standard 1gal (3.79L) milk jugs

Works in conjunction with Sure Tamp® to deliver two types of milk

Optional use: side-by-side or below-counter design



Espresso Refrigerator



Sure Tamp® Steam



Sure Tamp® Auto

DESCRIPTION					CAPACITY	ELECTRICAL
Product #	Model	Dimensions Height x Width x Depth (centimeters)			shots/hr	Volts
43400.xxxx*	SURE TAMP STEAM	76.35	31.50	64.21	180	208
43400.xxxx*	SURE TAMP AUTO	76.35	31.50	64.21	180	208
50214.0000	ESPRESSO REFRIGERATOR	42.42	22.86	56.64	n/a	120

*For information regarding Espresso package options, contact your BUNN Representative by calling 800-263-2256

A photograph of two tall glasses filled with cold coffee and ice cubes. The glass on the left contains a dark, rich coffee, while the glass on the right has a lighter, more milky coffee. Both glasses are set on a dark, textured slate surface. Scattered around the base of the glasses are several dark brown coffee beans. The background is dark and out of focus. The image is overlaid with a pattern of semi-transparent, diamond-shaped geometric shapes in shades of blue and grey.

COLD COFFEE

COLD COFFEE SOLUTIONS



BUNN offers a variety of profitable solutions for your Cold Coffee menu. From fresh-brewed tailored recipes by the batch to cold brew concentrate dispensers for multiple gallons of finished drinks, we have you covered.

PRODUCT	PAGE NUMBER
Infusion Series® Coffee Brewer Family - ICB	3-4, 6-7
IC3 DBC	43
Infusion Series® Tea & Coffee Combo Brewer Family - ITCB	45-47
Nitron₂® Family	60
Cold Dispensed - JDF	61-62
Ultra® Family	80-81

LEARN MORE: bunn.com/cold-coffee

IC3 DBC®

High volume brewer engineered specifically for consistently delivering tailored flavor profiles of iced coffee

Meet your volume needs; brew either 2 or 3 gallons (7.57 or 11.36 liters) of iced coffee at a time

SplashGard® funnel deflects hot liquids away from the hand

Brews 20 gallons (75.7 liters) of perfect iced coffee per hour

Customizable recipes

Designed to brew directly into the TDO-5 Dispenser

The exclusive Peak Extraction® Sprayhead features grooves that capture minerals and isolate the directional stream holes which then spray the whole coffee bed, providing full saturation and the ideal uniformity of extraction.



IC3 DBC

DESCRIPTION						CAPACITY	ELECTRICAL
Product #	Model	Finish	Dimensions Height x Width x Depth (Centimeters)			Liters/hr	Volts
45100.6101	IC3 DBC	STAINLESS	95.25	22.78	61.72	75.7	220-240

Product #s listed as 120/208V or 120/240V require 3 wires plus ground (2 hot, 1 neutral, ground) and must be connected to 208V service or 240V service, respectively. Please refer to the installation manual for more information.





COFFEE & TEA COMBOS

Infusion Series® Platinum Edition® Coffee and Tea Combo

The Infusion Series coffee and tea equipment platform provides Best Result in the Cup™ performance with the proven industry knowledge to deliver the lowest cost of ownership

ITCB-DV

Brews into all BUNN iced tea dispensers (except TDS-5), 1.9 to 3.8L airpots, thermal carafes and can accommodate BUNN® ThermoFresh® 1.0 Gallon Baseless Servers

Dual voltage adaptable; can operate at 120V/15amp or 208-240V/20amp

The exclusive Peak Extraction® Sprayhead features grooves that capture minerals and isolate the directional stream holes which then spray the whole coffee bed, providing full saturation and the ideal uniformity of extraction



ITCB

DESCRIPTION								PAPER FILTER		CAPACITY COFFEE	CAPACITY TEA	ELECTRICAL
Product #	Model	Flip Tray	Funnel Type Coffee	Funnel Type Tea	Dimensions Height x Width x Depth (centimeters)			BUNN # Coffee	BUNN # Tea	236mL cups/hr		Volts
73.66cm TRUNK HEIGHT												
52500.6100	ITCB-DV 73.66cm w/ Tray	YES	STAINLESS	QUICK TIP TEA	88.90	29.46	57.30	20138.1000	20100.0000	78	334	120
										136	334	120/208
										162	334	120/240
54000.6100	ITCB-DV-HV	NO	STAINLESS	QUICK TIP TEA	88.90	25.40	60.90	20138.1000	20100.0000	81	336	120
										136	336	120/208
										183	336	120/240
54100.6100	ITCB-HV TWIN	NO	STAINLESS	QUICK TIP TEA	88.90	52.10	66.10	20138.1000	20100.0000	280	672	120/240
Compatible Dispensers - TD4, TD4T, TDS-3, TDS-3.5, TDJ-4, TDO-5, TDO-N-3.5, TDO-N-4, TD3T-N Tea Dispensers, 3.8 and 5.7L ThermoFresh® Servers; With Flip Tray - 2.5 - 3.8L Airpots and 1.9L Thermal Carafes												



Infusion Series® Standard Edition Coffee and Tea Combo

High Volume

The Infusion Series coffee and tea equipment platform provides Best Result in the Cup™ performance with the proven industry knowledge to deliver the lowest cost of ownership

High volume model includes Smart Funnel for coffee; compatible with BrewWISE® grinders

Large 3gal (11.36L) tank provides back-to-back brewing capacity

Single model is dual voltage adaptable; can operate at 120V/15amp, 120/208V/20amp or 120/240V/20amp

The exclusive Peak Extraction® Sprayhead features grooves that capture minerals and isolate the directional stream holes which then spray the whole coffee bed, providing full saturation and the ideal uniformity of extraction



ITCB-DV HV



ITCB-Twin HV

DESCRIPTION							PAPER FILTER		CAPACITY COFFEE	CAPACITY TEA	ELECTRICAL
Product #	Model	Funnel Type Coffee	Funnel Type Tea	Dimensions Height x Width x Depth (centimeters)			BUNN # Coffee	BUNN # Tea	236mL cups/hr		Volts
52300.6100	ITCB-DV HV	BLACK/SMART	QUICK TIP TEA	88.90	25.40	61.72	20138.1000	20100.0000	82	334	120
									136	334	120/208
									181	334	120/240
52400.6100	ITCB Twin HV	BLACK/SMART	QUICK TIP TEA	88.90	52.07	60.45	20138.1000	20100.0000	280	672	120/240

Compatible Dispensers - TD4T, TDS-3, TDO-4, TDO-N-3.5, TDO-N-4 Tea Dispensers, 1 and 1.5gal ThermoFresh® Servers

Infusion Series® Standard Edition Coffee and Tea Combo

Medium Volume

The Infusion Series coffee and tea equipment platform provides Best Result in the Cup™ performance with the proven industry knowledge to deliver the lowest cost of ownership

ITCB-DV

Brews into all BUNN iced tea dispensers (except TDS-5),1.9 to 3.8L airpots, thermal carafes and can accommodate BUNN® ThermoFresh® Servers

Dual voltage adaptable; can operate at 120V/15amp or 208-240V/20amp

The exclusive Peak Extraction® Sprayhead features grooves that capture minerals and isolate the directional stream holes which then spray the whole coffee bed, providing full saturation and the ideal uniformity of extraction



ITCB

DESCRIPTION								PAPER FILTER		CAPACITY COFFEE	CAPACITY TEA	ELECTRICAL
Product #	Model	Sweetener	Funnel Type Coffee	Funnel Type Tea	Dimensions Height x Width x Depth (centimeters)			BUNN # Coffee	BUNN # Tea	236mL cups/hr	Volts	
73.66cm TRUNK HEIGHT												
52200.6100	ITCB-DV 29" w/Flip Tray	NO	BLACK PLASTIC	QUICK TIP TEA	88.90	29.46	55.37	20138.1000	20100.0000	72	120	
										136	120/208	
										136	120/240	
Compatible Dispensers - TD4, TD4T, TDS-3, TDS-3.5, TDJ-4, TDO-5, TDO-N-3.5, TDO-N-4, TD3T-N Tea Dispensers, 1 and 1.5gal ThermoFresh® Servers; With Flip Tray - 2.5 - 3.8L Airpots and 1.9L Thermal Carafes												

SmartWAVE® Low Profile Combo

Low profile brewer featuring SmartWAVE technology, simple operation, and flexible server options

- SmartWAVE technology increases turbulence in the brew funnel
- Iced Tea: 1.04L concentrate, 2.6L dilution
- Brew into 64oz (1.9L) thermal carafes using the slide-out booster tray
- Includes both coffee and tea funnels
- Adjustable legs to accommodate up to 3L lever-action and 2.5L push-button BUNN® airpots and thermal servers



WAVE Combo

DESCRIPTION							PAPER FILTER	CAPACITY	ELECTRICAL
Product #	Model	Series	Funnel Type	Dimensions Height x Width x Depth (centimeters)			BUNN #	236mL cups/hr	Volts
39900.6020	WAVE Combo	STANDARD	PLASTIC	44.20	24.64	45.21	20115.6000	62	120
Compatible Dispensers - 2.5L - 3.0L Lever-Action Airpots, 2.2L - Push Button Airpots, 1.9L Thermal Carafes, 1.9L Thermal Pitcher, 2.5L Thermal Server									

A glass of iced tea with lemons and ice cubes, overlaid with a geometric pattern of blue and white diamonds.

ICED TEA

Infusion Series® Standard Edition Iced Tea

Achieve a variety of flavor profiles and batch options in a single unit

Three recipe buttons and full/half options for maximum flexibility; brew counter tracks number of batches

Single button graphic overlay to customize user interface

Quickbrew (Q) funnel tip for easy conversion

ITB-DD DUAL DILUTION

Narrow footprint, designed to brew into two BUNN® TDO-N 3.5gal dispensers

Rotating brew basket, base adapter, color-coded decals, and dedicated dilution nozzles included

ITB & ITB-DD SWEETENER

Easily adjust sweetener volume with the Sweet Meter

Separate sweetener inlet - use existing CO₂ systems or external third party pump for sweetener delivery

ITB-LP LOW PROFILE

Brew directly into TDO-3.5 LP dispenser with brew-thru lid

Compact, low-profile styling for variety of spaces

The exclusive Peak Extraction® Sprayhead features grooves that capture minerals and isolate the directional stream holes which then spray the whole coffee bed, providing full saturation and the ideal uniformity of extraction.*



ITB-DD



ITB



ITB-LP

DESCRIPTION						PAPER FILTER	CAPACITY	CAPACITY W/Q FUNNEL TIP	ELECTRICAL
Product #	Model	Sweetener	Dimensions Height x Width x Depth (centimeters)			BUNN #	236mL cups/hr	236mL cups/hr	Volts
52000.6100	ITB	NO	88.90	29.46	55.40	20100.0000	336	523	120
Compatible tea dispensers - TDO-5, TDO-4, TD4T, TDS-3, TDS-3.5, TDO-N 3.5, TDO-N 4, TD3T-N									
52000.6300	ITB DD W/SWEETENER	YES	88.90	31.00	59.18	20100.0000	336	523	120
52000.6301	ITB DDIL	NO	88.90	31.00	59.18	20100.0000	336	523	120
Compatible tea dispensers -TDO-N 3.5, TDO-N 4, TD3T-N									
52000.6101	ITB-LP	NO	74.93	29.46	55.40	20100.0000	336	523	120
Compatible tea dispensers - TDO-3.5 LP									

Automatic Iced Tea Single

Fresh iced tea brewing solution with simple switch operation

TB3, TB3Q

Choose between 25.75" or 29" trunk heights (see table for compatible dispensers)

Dispenser sold separately (except TB3Q w/TD4T)

Quickbrew (Q) models include special funnel tip for shorter brewing cycle

TB3Q-LP LOW PROFILE

Brew directly into TDO-3.5 LP dispenser (included) with brew-thru lid

Quickbrew (Q) models include special funnel tip for shorter brewing cycle

Compact, low profile styling to accommodate a variety of space



TB3



TB3Q-LP



TB3QT w/TD4T

DESCRIPTION								PAPER FILTER	CAPACITY	ELECTRICAL
Product #	Model	Quickbrew	Ready Light	Dispenser Included	Dimensions Height x Width x Depth (Inches)			BUNN #	8oz cups/hr 236mL cups/hr	Volts
73.66cm TRUNK HEIGHT										
36700.6013	TB3Q	YES	NO	NO	86.36	29.46	55.88	20100.0000	523	120
36700.6041	TB3QT	YES	NO	YES (TD4T)	86.36	29.46	55.88	20100.0000	523	120
Compatible tea dispensers - TDO-5, TDO-4, TD4T (Included with TB3QT), TDS-3, TDS-3.5, TDO-N-3.5, TD3T-N, TDO-N-4										
65.41cm TRUNK HEIGHT										
36700.6030	TB3	NO	NO	NO	78.74	29.46	55.88	20100.0000	303	120
36700.6059	TB3Q	YES	NO	NO	78.74	29.46	55.88	20100.0000	523	120
Compatible tea dispensers - TD4, TDS-3, TDO-4										
LOW PROFILE										
36700.6100	TB3Q-LP	YES	NO	YES (TDON 3.5 LP)	73.03	29.39	55.55	20100.0000	523	120
Compatible tea dispensers - TDO-3.5 LP (Included)										

Product #s listed as 120/208V or 120/240V require 3 wires plus ground (2 hot, 1 neutral, ground) and must be connected to 208V service or 240V service, respectively. Please refer to the installation manual for more information.



Automatic Iced Tea Twin Narrow

Fresh iced tea brewing solution with simple switch operation

Specifically designed to accommodate and brew into two BUNN® Narrow Tea Dispensers (can also brew directly into standard tea dispensers)

Includes rotating brew basket, base platform adapter, dedicated dilution nozzles and brew selection switch

Quickbrew (Q) model includes special funnel tip for shorter brewing cycles



TB6

DESCRIPTION						PAPER FILTER	CAPACITY	ELECTRICAL
Product #	Model	Quickbrew	Dimensions Height x Width x Depth (centimeters)			BUNN #	236mL cups/hr	Volts
36700.6301	TB6Q	YES	86.36	30.99	57.40	20100.0000	523	120
Compatible tea dispensers - TDO-N-3.5, TDO-N-4, TD4T, TDS-3, TDS-3.5								



LIQUID COFFEE

Refrigerated Dispenser *Medium Volume*

Medium volume coffee-on-demand dispenser with refrigerated cabinet to extend product flavor profile

- Accommodates all .5gal (1.9L) and most 1gal (3.8L) BIB containers
- Serves two coffee products and hot water
- Convenient flip tray allows for dispensing into decanters or carafes
- Compatible with BUNNlink®
- Power Logic allows the machine to be wired/configured to operate on any voltage from 100 to 240V, (50 or 60 Hz)
- FlavorGard® technology continuously monitors extract-to-water ratio and assures flavor consistency



LCR-2

DESCRIPTION								CAPACITY	ELECTRICAL
Product #	Model	Connector Type	Product Ratio at 1.8oz/Second Dispense Rate	Product Ratio at 2.5oz/Second Dispense Rate	Dimensions Height x Width x Depth (centimeters)			148mL cups/hr**	Volts
34400.6036	LCR-2	SCHOLLE	45:1-100:1	65:1-100:1	96.52	30.99	63.25	125	120
								385	208
								512	240
34400.6060	LCR-2	SCHOLLE	25:1-45:1	25:1-65:1	96.52	30.99	63.25	125	120
								385	208
								512	240

Low Profile Dispenser

Low-to-medium volume coffee-on-demand dispenser designed to conveniently fit a variety of places

- Serves two coffee products and hot water
- Accommodates two .5gal (1.9L) BIB containers
- Programmable options for continuous dispense (by the cup) for self-serve applications or portion control by the cup or carafe



LCA-2 LP

DESCRIPTION			CAPACITY				ELECTRICAL	
Product #	Model	Connector Type	Product Ratio at 1.7oz/Second Dispense Rate	Dimensions Height x Width x Depth (centimeters)			148mL cups/hr	Volts
38800.6000	LCA-2 LP	SCHOLLE 1910LX	25:1-100:1	58.93	40.08	53.09	120	120
38800.6002	LCA-2 LP	SCHOLLE QC	25:1-100:1	58.93	40.08	53.09	120	120

Product #s listed as 120/208V or 120/240V require 3 wires plus ground (2 hot, 1 neutral, ground) and must be connected to 208V service or 240V service, respectively. Please refer to the installation manual for more information.

Ambient Product Holding

Low-to-medium volume coffee-on-demand dispensers for shelf-stable products

LCA-1

Compact, low profile design fits a variety of spaces

Accommodates one .5gal (1.9L) BIB container

Preset for push-and-hold dispense; optional portion control button can be programmed

LCA-2

Accommodates all .5gal (1.9L) and most 1gal (3.8L) BIB containers

Compatible with BUNNlink®

Serves two coffees

Equipped with Power Logic®. Power Logic allows the equipment to be wired/ configured to operate on any voltage from 100 to 240V, (50 or 60 Hz)

FlavorGard® technology continuously monitors extract-to-water ratio and assures flavor consistency



LCA-1



LCA-2

DESCRIPTION						CAPACITY			ELECTRICAL
Product #	Model	Portion Control	Connector Type	Product Ratio at 1.8oz/Second Dispense Rate	Product Ratio at 2.5oz/Second Dispense Rate	Dimensions Height x Width x Depth (centimeters)			Volts
44100.6000	LCA-1	NO	SCHOLLE 1910LX	25:1-100:1	25:1-100:1	45.21	26.92	49.53	120
34400.6001	LCA-2	NO	SCHOLLE 1910LX	45:1-100:1	65:1-100:1	76.20	30.99	63.25	120

Refrigerated Dispense *High Volume*

High volume coffee-on-demand dispenser meets the requirements of banquet halls, convention centers, stadiums and hotels

- 18gal (82L) tank capacity
- Refrigerated product cabinet extends product flavor profile, adjustable to maintain 41° to 65°F (5° to 18°C) in the product compartment
- Digital Brewer Control for programming and user interface
- Holds up to three 1gal (3.8L) BIBs
- Three-phase or single phase operation
- Three buttons allow operator to dispense three independent ratios



DESCRIPTION								CAPACITY	ELECTRICAL
Product #	Model	Connector Type	Product Ratio	Dispense Rate/Second	Dimensions Height x Width x Depth (centimeters)			237mL cups/hr**	Volts
40800.6000	LCR-3 HV	SCHOLLE QC	25:1-100:1	177mL	101.60	83.82	59.64	370	120/208 1P
								493	120/208 3P
								542	120/240 1P
								742	120/240 3P
40800.6001	LCR-3 HV	SCHOLLE 1910LX	25:1-100:1	177mL	101.60	83.82	59.64	370	120/208 1P
								493	120/208 3P
								542	120/240 1P
								742	120/240 3P

Product #s listed as 120/208V or 120/240V require 3 wires plus ground (2 hot, 1 neutral, ground) and must be connected to 208V service or 240V service, respectively. Please refer to the installation manual for more information.





COLD COFFEE

COLD COFFEE SOLUTIONS



BUNN offers a variety of profitable solutions for your Cold Coffee menu. From fresh-brewed tailored recipes by the batch to cold brew concentrate dispensers for multiple gallons of finished drinks, we have you covered.

PRODUCT	PAGE NUMBER
Infusion Series® Coffee Brewer Family - ICB	3-4, 6-7
IC3 DBC	43
Infusion Series® Tea & Coffee Combo Brewer Family - ITCB	45-47
Nitron ₂ ® Family	60
Cold Dispensed - JDF	61-62
Ultra® Family	80-81

LEARN MORE: bunn.com/cold-coffee

Nitron₂[®] Cold Draft

Keg-free design delivers authentic Cold Brew taste without need for a complex brewing process

Achieve a nitro infusion with no keys to change-out, store, clean, or sanitize. Various models available using either two 1-gal (3.8L) concentrate BIBs or BUNN refillable containers (for Ball-valve models), two 1/2-gal (1.9L) concentrate BIBs or a single 1-gal concentrate BIB (for Scholle models) that staff are already familiar with and each BIB yields multiple gallons of finished drinks

The Nitron Experience: No milk or sugar needed! BUNN's patented in-line gas infuser produces up to 3 minutes of cascading micro-bubbles*, resulting in a nitro cold brew crowned with a smooth, silky stout-like head that tastes distinctively creamy with a velvety soft mouthfeel.

Outfit the standard and nitro taps with separate beverages - your choice of cold brew coffee, iced coffee, or iced tea - all from one slim, 10-inch wide countertop design

At a rate of one 16oz drink per minute, can dispense 60 drinks before exceeding 41°F

**based on product concentrate used*



Nitron₂[®] Cold Draft
(Removable Graphic Door)



Nitron₂[®] Cold Draft
(All Black Door)

DESCRIPTION								ELECTRICAL
Product #	Model	Removable Graphic Door	All Black Door	°C	Dimensions Height x Width x Depth (Centimeters)			Volts
51600.6011	NITRON COLD DRAFT ALL NITRO 4:1 to 12:1	NO	YES	5	86.36	25.40	72.14	120
51600.6018	NITRON COLD DRAFT C-TOP 4:1 to 12:1	YES	NO	5	86.36	25.40	72.14	120



Iced Coffee – JDF-2S

Cold beverage concentrate dispenser with High Intensity® mixing chamber delivers superior quality from an operator friendly design

One dispenser delivers frozen and ambient concentrate products to maximize profitability by providing greater flexibility in product offerings

8lb (3.6kg) ice bank provides superior cold drink capacity

Push-and-Hold dispense and Single Size portion control dispense available on the same machine

Burst Capacity: at rate of one 355ml drink/min, 70 drinks before exceeding 5°C (24°C ambient and 24°C incoming water temp)



JDF-2S IC LD
(Lighted Door)

DESCRIPTION							ELECTRICAL
Product #	Model	Lighted Display	Cold Water Dispense	Dimensions Height x Width x Depth (centimeters)			Volts
37900.6009	JDF-2S IC LD	YES	NO	84.84	26.67	68.58	120

Product #s listed as 120/208V or 120/240V require 3 wires plus ground (2 hot, 1 neutral, ground) and must be connected to 208V service or 240V service, respectively. Please refer to the installation manual for more information.



Iced Coffee – JDF-4S

Cold beverage concentrate dispenser with High Intensity® mixing chamber delivers superior quality from an operator friendly design

One dispenser delivers frozen and ambient concentrate products to maximize profitability by providing greater flexibility in product offerings

18lb (3.6kg) ice bank provides superior cold drink capacity

Push-and-Hold dispense and Single Size portion control dispense available on the same machine

Burst Capacity: at rate of three 355ml drinks/min, 145 drinks before exceeding 5°C (24°C ambient and 24°C incoming water temp)

Cold water dispense



JDF-4S IC

DESCRIPTION							ELECTRICAL
Product #	Model	Lighted Display	Cold Water Dispense	Dimensions Height x Width x Depth (centimeters)			Volts
37300.6016	JDF-4S IC	NO	YES	84.84	39.88	69.85	120



CAPPUCCINO HOT CHOCOLATE

iMIX® 3

Sleek powdered beverage dispenser delivers hot drinks with exceptional reliability and taste - all from an operator friendly design

Three 8lb (3.6kg) hoppers

LED backlit door graphics

Variable speed motors allow control of product consistency in mixing chamber (.75 to 6.6g powder per second)

Left or top-hinged door option

Dispense 36 355ml cups in 14 minutes before dropping 5.6°C from first cup serving temperature

Display allows adjustments and service operational testing from front of machine, communicates machine status, technical support contact information, and advertising messages

iMIX-3S+

Set as push and hold or single size portion control



iMIX-3 (Top Hinge)



iMIX-3

DESCRIPTION							CAPACITY	ELECTRICAL
Product #	Model	Display	Top Hinge Door	Dimensions Height x Width x Depth (centimeters)			236mL cups/hr	Volts
36900.6000	iMIX-3	CAPPUCCINO	NO	83.31	31.24	61.21	72	120
36900.6004	iMIX-3	HOT CHOCOLATE	NO	83.31	31.24	61.21	72	120
36900.6009	iMIX-3 PC	CAPPUCCINO	NO	83.31	31.24	61.21	72	120
36900.6020	iMIX-3 PC	CAPPUCCINO	NO	83.31	31.24	61.21	72	120/240

iMIX® 5

Sleek powdered beverage dispenser delivers hot drinks with exceptional reliability and taste - all from an operator friendly design

Five 8lb (3.6kg) hoppers

LED backlit door graphics

Variable speed motors allow control of product consistency in mixing chamber (.75 to 6.6g powder per second)

Left or top-hinged door option

Display allows adjustments and service operational testing from front of machine, communicates advertising messages, machine status, and technical support contact information

Dispense 36 355ml cups in 14 minutes before dropping 5.6°C from first cup serving temperature

iMIX-5S+

Set as push and hold or single size portion control



iMIX-5S+



iMIX-5

DESCRIPTION							CAPACITY	ELECTRICAL
Product #	Model	Hot Water Dispense	Top Hinge Door	Dimensions Height x Width x Depth (centimeters)			236mL cups/hr	Volts
37000.6000	iMIX-5	NO	NO	83.31	49.02	60.96	72	120
37000.6020	iMIX-5	NO	YES	83.31	49.02	60.96	72	120
38100.6330	iMIX-5 S+	NO	YES	83.31	49.02	60.96	72	120

Fresh Mix

Variable speed motor allows control of product consistency in mixing chamber

FMD-1: One 8lb (3.6kg) hopper

FMD-2: Two 4lb (1.81kg) hoppers

FMD-3: Three 4lb (1.81kg) hoppers

FMD-5: Five 4lb (1.81kg) hoppers

Variable speed motors allow control of product consistency in mixing chamber
(.75 to 6.6g powder per second)

Lighted graphics for merchandising

Fast fill – perfect for quick service restaurants

Each mixing chamber has independent powder to water ratio



FMD-3



FMD-5



FMD-1

DESCRIPTION								CAPACITY	ELECTRICAL
Product #	Model	Decor	Display	Number of Hoppers	Dimensions Height x Width x Depth (centimeters)			236mL cups/hr	Volts
28700.6001	FMD-1	BLACK	MUG	ONE	84.07	39.88	69.85	67	120
28700.6007	FMD-1	BLACK	HOT CHOCOLATE	ONE	84.07	39.88	69.85	67	120
29200.6001	FMD-2	BLACK	MUG	TWO	84.07	39.88	69.85	67	120
28200.6000	FMD-3	BLACK	CAPPUCCINO	THREE	75.70	29.72	59.18	67	120
28200.6001	FMD-3	STAINLESS	CAPPUCCINO	THREE	75.70	29.72	59.18	67	120
28200.6002	FMD-3	BLACK	CAPPUCCINO	THREE	75.70	29.72	59.18	136	120/240
29250.6000	FMD-3 DBC	BLACK	CAPPUCCINO	THREE	75.70	29.72	59.18	67	120



A tall, clear glass filled with bright orange juice stands on a dark, textured surface. To the left of the glass, a slice of orange and a green leaf are visible. To the right, a whole orange and another slice are placed. The background is a blurred wooden surface. Overlaid on the image are several semi-transparent geometric shapes: blue squares and white squares, some of which are tilted. The word "JUICE" is printed in white, bold, sans-serif capital letters across the middle of the glass.

JUICE

Juice – JDF Segmented Door

Cold beverage concentrate dispenser with High Intensity® mixing system delivers quality cold beverages from an operator friendly design

New segmented LED lighted door features different display slots and eight different graphics allowing for easy adaptability to beverage menu

One dispenser delivers both frozen and ambient products increasing profits by lowering costs

Pumps and mixes 2+1 to 11+1 concentrated beverages, including 4+1 and 5+1 high viscosity concentrates accurately and consistently

Push and Hold and Portion Control models, (Push and Hold can also be reset for a single size portion dispense)

Burst Capacity: at rate of three 355ml drinks/min, 145 drinks before exceeding 5°C (24°C ambient and 24°C incoming water temp)



JDF-4S PC
(Segmented Lit Door)

DESCRIPTION							ELECTRICAL		
Product #	Model	Lighted Display	Portion Control	Remote Switches	Cold Water Dispense	Dimensions Height x Width x Depth (centimeters)	Volts		
37900.6064	JDF-4S PC	YES	NO	NO	NO	84.07 39.88 69.85	120		
37300.6080	JDF-4S PC	YES	YES	NO	NO	84.07 39.88 69.85	120		
37300.6079	JDF-4S PB	YES	NO	NO	NO	84.07 39.88 69.85	120		

Juice – JDF-2S

Cold beverage concentrate dispenser with High Intensity® mixing system delivers quality cold beverages from an operator friendly design

One dispenser delivers both frozen and ambient products increasing profits by lowering costs

Superior brix accuracy and burst capacity ensure consistent drinks throughout the day

Pumps and mixes 2+1 to 11+1 concentrated beverages, including 4+1 high viscosity concentrates and 5+1 juices accurately and consistently

Push and Hold and Portion Control models, (Push and Hold can also be reset for a single size portion dispense)

Burst Capacity: at rate of one 355 ml drinks/min, 70 drinks before exceeding 5°C (24°C ambient and 24°C incoming water temp)



JDF-2S PC LD
(Lighted Door with Portion Control)



JDF-2S
(non lit push and hold)



JDF-2S LD

DESCRIPTION							ELECTRICAL	
Product #	Model	Lighted Display	Portion Control	Remote Switches	Dual Dispense*	Dimensions Height x Width x Depth (centimeters)	Volts	
37900.6001	JDF-2S W/FILTER	NO	NO	NO	NO	84.84 26.67 68.58	120	
37900.6008	JDF-2S LD	YES	NO	NO	NO	84.84 26.67 68.58	120	
37900.6016	JDF-2S PC LD	YES	YES	NO	NO	84.84 26.67 68.58	120	

*Equipment will dispense via multiple nozzles simultaneously

Product #s listed as 120/208V or 120/240V require 3 wires plus ground (2 hot, 1 neutral, ground) and must be connected to 208V service or 240V service, respectively. Please refer to the installation manual for more information.



Juice – JDF-4S

Cold beverage concentrate dispenser with High Intensity® mixing system delivers quality cold beverages from an operator friendly design

- One dispenser delivers both frozen and ambient products increasing profits by lowering costs
- Superior brix accuracy and burst capacity ensure consistent drinks throughout the day
- Pumps and mixes 2+1 to 11+1 concentrated beverages, including 4+1 high viscosity concentrates and 5+1 juices accurately and consistently
- Push and Hold and Portion Control models, (Push and Hold can also be reset for a single size portion dispense)
- Burst Capacity: at rate of three 355ml drinks/min, 145 drinks before exceeding 5°C (24°C ambient and 24°C incoming water temp)



JDF-4S PC LD
(Lighted Door with Portion control)



JDF-4S
(with cold water dispense)



JDF-4S LD
(Lighted Door)

DESCRIPTION									ELECTRICAL
Product #	Model	Lighted Display	Portion Control	Remote Switches	Cold Water Dispense	Dimensions Height x Width x Depth (centimeters)			Volts
37300.6000	JDF-4S	NO	NO	NO	NO	84.84	39.88	69.85	120
37300.6002	JDF-4S	NO	NO	NO	YES	84.84	39.88	69.85	120
37300.6004	JDF-4S LD	YES	NO	NO	NO	84.84	39.88	69.85	120
37300.6006	JDF-4S LD	YES	NO	NO	YES	84.84	39.88	69.85	120
37300.6023	JDF-4S PC LD	YES	YES	NO	NO	84.84	39.88	69.85	120

A clear glass mug filled with water sits on a dark wooden table. The background is a pattern of overlapping diamond shapes in dark blue and light grey. The text "HOT WATER" is centered on the mug.

HOT
WATER

Precision Temperature *Medium Volume*

- 3gal (11.4L) tank
- Digital thermostat provides consistent and accurate temperatures, programmable from 60°-212°F (15.6°-100°C)
- Contemporary, low profile design for front-of-house and self-service
- Thinsulate® tank insulation provides increased energy efficiency
- LED display provides simple temperature adjustment
- Drip tray included



H3X Element

DESCRIPTION							CAPACITY	ELECTRICAL
							WATER INPUT 15.5°C	
Product #	Model	Finish	Temperature Setting °C	Dimensions Height x Width x Depth (centimeters)			L/hr	Volts
45300.6007	H3X	STAINLESS	100	56.64	19.30	52.02	13.8	208
45300.6008	H3X	STAINLESS	100	56.64	19.30	52.02	13.2	120

Precision Temperature *Medium Volume*

5gal (18.9L) tank

Digital thermostat provides consistent and accurate temperatures, programmable from 60°-212°F (15.6°-100°C)

LED display provides simple temperature adjustment



H5X Element
(Black)



H5X Element
(Stainless)

DESCRIPTION							CAPACITY	ELECTRICAL
							WATER INPUT 15.5°C	
Product #	Model	Finish	Temperature Setting °C	Dimensions Height x Width x Depth (centimeters)			L/hr	Volts
43600.6002	H5X	STAINLESS	100	72.40	18.80	48.00	39.7	208
43600.6003	H5X	STAINLESS	100	72.40	18.80	48.00	39.7	240
43600.6006	H5X	STAINLESS	100	72.40	18.80	48.00	17.8	120
43600.6008	H5X (6000W)	STAINLESS	100	72.40	18.80	48.00	59.8	208
43600.6010	H5X (6000W)	STAINLESS	100	72.40	18.80	48.00	59.8	240
43600.6017	H5X	BLACK	100	72.40	18.80	48.00	39.7	208

Product #s listed as 120/208V or 120/240V require 3 wires plus ground (2 hot, 1 neutral, ground) and must be connected to 208V service or 240V service, respectively. Please refer to the installation manual for more information.



Constant Temperature *Pourover & Low Volume*

High quality, easy-to-clean stainless steel exterior and tank for a long life

Includes drip tray

HW2

Hooked to water line so fresh, hot water is always available

7.57L of hot water in a space-saving machine

OHW

Compact styling to accommodate a variety of spaces

Pourover model. No plumbing needed



OHW

HW2

DESCRIPTION						TANK SIZE	CAPACITY	ELECTRICAL
Product #	Model	Dimensions Height x Width x Depth (centimeters)			Temperature Setting °C	L	L/hr	Volts
02550.6000	OHW	42.93	16.51	27.43	93.3	2.4	POUROVER	120
02500.6000	HW2	60.45	18.03	36.32	93.3	7.6	15.5	120

Constant Temperature *Large Volume*

High quality, easy-to-clean stainless steel exterior and tank for a long life

H5E-DV PC

Constant temperature control between 18.3°C-96.1°C ensures consistent water temperature

Dual voltage model; can operate at 120V/15 amp or 120/208-240V/17 amp

Three programmable volume settings and one push and hold continuous dispense button

H5X-DV-PC

Dispenses at temperatures up to boiling 100°C for food prep and cleaning

Dual voltage model; can operate at 120V/15 amp or 120/208-240V/17 amp

Three programmable volume settings and one push and hold continuous dispense button

H10X

Dry-plug prevention for easy installation

Precise temperature 100°C ensures consistent, high quality results



H51E-DV PC

H10X

DESCRIPTION							CAPACITY	ELECTRICAL
							WATER INPUT 15.5°C	
Product #	Model	Dimensions Height x Width x Depth (centimeters)			Temperature Setting °C	Tank Size L	L/hr	Volts
39100.6000	H5E-DV PC	72.14	17.78	39.37	93.3	18.9	19.3	120
							32.6	120/208
							43.2	120/240
26300.6000	H10X-80-208	87.38	25.91	62.23	100	37.9	39.7	208
26300.6001	H10X-80-240	87.38	25.91	62.23	100	37.9	39.7	240

Product #s listed as 120/208V or 120/240V require 3 wires plus ground (2 hot, 1 neutral, ground) and must be connected to 208V service or 240V service, respectively. Please refer to the installation manual for more information.

A tall, clear glass filled with cold water, ice cubes, and fresh raspberries and blueberries. The glass is set on a rustic wooden surface. In the foreground, more raspberries and blueberries are scattered on the wood. The image is overlaid with a series of overlapping, semi-transparent blue geometric shapes (squares and diamonds) on the left side. The text "COLD WATER" is centered in the lower half of the image in a white, sans-serif font.

COLD WATER

BUNN refresh® Tower

Purified, cold water dispenser for still and sparkling water using a patented in-line mistifier

Sleek visual design language worthy of front-of-house settings

One water filtration system included. Purity achieved with water filtration technology certified to reduce cyst, lead, particulates, chloramines, chlorine taste and odor, and 99.99% of common water-borne bacteria.*

Recirculation loop ensures cold water is constantly circulating for consistently low casual drink temperature of 40°F water

In-line patented water mistifier provides delicate balance of purified, cold water and "light" carbonation for longer lasting sparkling water and optimal absorption of flavors

Fast flow faucet accommodates large cups or carafes up to 12" tall

At a rate of two 12oz drinks per minute, can dispense 120 drinks before exceeding 41°F

*As tested with E.Coli ATCC (11229) by manufacturer's laboratory.



BUNN refresh® Tower
Pull & Hold



BUNN refresh® Tower
Portion Control

DESCRIPTION							ELECTRICAL
Product #	Model	Finish	°C	Dimensions* Height x Width x Depth (centimeters)			Volts
45900.6100	BUNN REFRESH TOWER PULL & HOLD	SATIN CHROME/BLACK	4.4	62.74	19.81	37.08	120
45900.6101	BUNN REFRESH TOWER PUSH BUTTON	SATIN CHROME/BLACK	4.4	51.05	19.81	37.08	120

Plumbing: 30-100 PSI. Machine supplied with 3/8" male flare fitting

*Dimensions for tower unit. For tower and undercounter base dimensions please visit bunn.com

Product #s listed as 120/208V or 120/240V require 3 wires plus ground (2 hot, 1 neutral, ground) and must be connected to 208V service or 240V service, respectively. Please refer to the installation manual for more information.



BUNN refresh® Counter Top

Purified, cold water dispenser for still and sparkling water using a patented in-line mistifier

One water filtration system included. Purity achieved with water filtration technology certified to reduce cyst, lead, particulates, chloramines, chlorine taste and odor, and 99.99% of common water-borne bacteria.*

Recirculation loop ensures cold water is constantly circulating for consistently low casual drink temperature of 4.4°C water

In-line patented water mistifier provides delicate balance of purified, cold water and "light" carbonation for longer lasting sparkling water and optimal absorption of flavors

The perfect instrument to incorporate infusions and natural ingredients for crafted beverages

Visual design language worthy of front-of-house settings

At a rate of one 355mL drink per minute, can dispense 60 drinks before exceeding 5°C

**As tested with E.Coli ATCC (11229) by manufacturer's laboratory.*



BUNN refresh®
Portion Control



BUNN refresh®
Push Button



BUNN® refresh®
Push Button

DESCRIPTION							ELECTRICAL
Product #	Model	Finish	°C	Dimensions Height x Width x Depth (centimeters)			Volts
45800.6000	BUNN REFRESH COUNTERTOP PUSH BUTTON	BLACK/STAINLESS	4.4	68.58	25.40	67.31	120
45800.6001	BUNN REFRESH COUNTERTOP PORTION CONTROL	BLACK/STAINLESS	4.4	68.58	25.40	67.31	120
45800.6002	BUNN REFRESH COUNTERTOP PUSH BUTTON	WHITE/STAINLESS	4.4	68.58	25.40	67.31	120
45800.6003	BUNN REFRESH COUNTERTOP PORTION CONTROL	WHITE/STAINLESS	4.4	68.58	25.40	67.31	120
Plumbing: 30-100 PSI. Machine supplied with 3/8" male flare fitting							

A vibrant red frozen granita slushy is served in a clear glass. The slushy has a coarse, crystalline texture and is garnished with a fresh sprig of dill. The glass sits on a bright blue surface. The image is overlaid with several semi-transparent geometric shapes in shades of blue and teal, creating a modern, abstract design. The text "FROZEN GRANITA SLUSHY" is centered in the lower half of the image in a white, sans-serif font.

FROZEN GRANITA SLUSHY

Ultra® Series

Frozen beverage dispenser with reversing auger technology for superior mixing and freezing

MANUAL FILL

- Two 3gal (11.36L) hoppers
- Pour water and product mix directly into hopper; special plumbing not required
- Torque sensor technology maintains consistent product thickness for superior beverages
- Reversing auger insures product quality and product presentation in the hopper
- LED Backlit displays



Ultra-2 HP
Stainless & Black

DESCRIPTION							ELECTRICAL
Product #	Model	Finish	Flat Lid	Dimensions Height x Width x Depth (centimeters)			Volts
34000.6079	ULTRA-2 HP	STAINLESS/WHITE	No	81.28	40.64	62.23	120
34000.6080	ULTRA-2 HP	BLACK	No	81.28	40.64	62.23	120
34000.6081	ULTRA-2 HP	STAINLESS/BLACK	No	81.28	40.64	62.23	120

Ultra® Series

Frozen beverage dispenser with reversing auger technology for superior mixing and freezing

High efficiency LED lighting

Torque sensor technology maintains consistent product thickness for superior beverages

Reversing auger insures product quality and product presentation in the hopper

Designed to be compliant with ADA self service requirements

CF VALVE AUTOFILL

Constant flow control for accurate brixing of product

Internal brixing allows interface with standard BIB pumping

LIQUID AUTOFILL

Two 3gal (11.36L) hoppers

Liquid autofill product hoppers automatically replenish

Designed to be used with Brix Pumps

POWDERED AUTOFILL

Powdered autofill product hoppers automatically replenish

5lb (2.27kg) dry product capacity; large 2gal (7.57L) hoppers



Ultra-2 LAFI



Ultra-2 PAF



Ultra-2 CF Valve

POWDERED AUTOFILL

Product #	Model	Handle	Finish	Logo on PAF Unit	Dimensions Height x Width x Depth (centimeters)			Volts
34000.6026	ULTRA-2 AF	STANDARD	STAINLESS/WHITE	YES	81.03	40.64	62.23	120
34000.6088	ULTRA-2 AF	STANDARD	STAINLESS/BLACK	YES	81.03	40.64	62.23	120
34000.6027	ULTRA-2 AF	STANDARD	BLACK	YES	81.03	40.64	62.23	120
34000.6500	ULTRA-2 PAF	STANDARD	STAINLESS/BLACK	YES	106.17	40.64	63.50	120
34000.6501	ULTRA-2 PAF	STANDARD	STAINLESS/BLACK	YES	106.17	40.64	63.50	120
34000.6504	ULTRA-2 PAF	STANDARD	BLACK	YES	106.17	40.64	63.50	120
34000.6520	ULTRA-2 CF Valve	EXTENDED	BLACK	YES	81.03	40.64	62.23	120
34000.6522	ULTRA-2 CF Valve	EXTENDED	STAINLESS/BLACK	YES	81.03	40.64	62.23	120

Product #s listed as 120/208V or 120/240V require 3 wires plus ground (2 hot, 1 neutral, ground) and must be connected to 208V service or 240V service, respectively. Please refer to the installation manual for more information.



A waiter in a blue uniform is holding a silver tray. On the tray, there is a white cup of coffee with a saucer and a tall glass filled with amber liquid and ice cubes. The background is blurred, showing other people in a social setting. The image is overlaid with a pattern of blue and white diamond shapes.

SERVING & HOLDING

ThermoFresh® Digital Gauge Servers

Holds temperature for hours without traditional warming plates

TF Server

Digital timer begins to count up in one minute increments to specifically display how long the brewed beverage has been stored; requires four AAA batteries; display shows low battery symbol

Brew-thru lid design also features a pour spout for easy emptying and cleaning

Translucent faucet guard for visibility while dispensing

Ideal for use with Single or Dual TF DBC Brewers

TF Server without Stand

Ideal with Infusion Series® Coffee Brewer (ICB)

TF Server Stand

Use for easy dispensing; 17.9cm cup clearance

Built-in drip tray is easily removed for cleaning or providing extra clearance for large vessels



3.8L TF Server
without Stand



TF Server Stand



3.8L TF Server
(Stand included)

SERVERS								COMPATIBLE EQUIPMENT
Product #	Model	Dimensions Height x Width x Depth (centimeters)			Holding Capacity	Includes Stand	Finish	Brewers
42700.6200	TF SERVER DSG3	52.58	23.11	33.02	3.8L	YES	STAINLESS	Single TF DBC, Dual TF DBC, ICB Tall, ICB Twin Tall, ITCB-DV, ITCB-DV HV, ITCB Twin HV
42750.6200	TF SERVER DSG3	57.66	23.11	33.02	5.7L	YES	STAINLESS	
42700.6250	TF SERVER DSG3	32.00	23.11	30.23	3.8L	NO	STAINLESS	
42750.6250	TF SERVER DSG3	37.34	23.11	30.23	5.7L	NO	STAINLESS	ICB-DV ICB Twin
54473.1000	TF SERVER STAND	24.64	23.50	33.02	N/A	N/A	BLACK	N/A

Product #s listed as 120/208V or 120/240V require 3 wires plus ground (2 hot, 1 neutral, ground) and must be connected to 208V service or 240V service, respectively. Please refer to the installation manual for more information.



ThermoFresh® Mechanical Gauge Servers

Holds temperature for hours without traditional warming plates

TF SERVER

Glass sight gauge on front of server allows for visible indication of level capacity

Brew-thru lid design also features a pour spout for easy emptying and cleaning

Translucent faucet guard for visibility while dispensing

Ideal for use with Single or Dual TF DBC Brewers

TF SERVER STAND

Use for easy dispensing; 17.9cm cup clearance

Built-in drip tray is easily removed for cleaning or providing extra clearance for large vessels

TITAN TF SERVER

3gal (11.36L) or 1.5gal (5.67L) capacity

Insulated and portable

Large cup clearance for a variety of dispensing options



Titan TF Server
(3 gal)



Titan TF Server
(1.5 gal)



3.8L TF Server
without Stand



TF Server Stand



5.7L TF Server
(Stand included)

SERVERS								COMPATIBLE EQUIPMENT
Product #	Model	Dimensions Height x Width x Depth (Inches)			Holding Capacity	Includes Stand	Finish	Brewers
44000.6200	TF SERVER	57.66	23.11	33.02	3.8L	YES	STAINLESS	Single TF DBC, Dual TF DBC, ICB Tall, ICB Twin Tall, ITCB-DV, ITCB-DV HV, ITCB Twin HV
44050.6200	TF SERVER	57.66	23.11	33.02	5.7L	YES	STAINLESS	
46300.6000	TITAN TF SERVER	58.17	29.72	38.86	5.7L	NO	STAINLESS	
44000.6250	TF SERVER	32.26	23.11	32.26	3.8L	NO	STAINLESS	ICB-DV ICB Twin
44050.6250	TF SERVER	32.26	23.11	32.26	3.8L	NO	STAINLESS	
54473.1000	TF SERVER STAND	24.64	23.50	33.02	N/A	N/A	BLACK	N/A

Coffee Decanters and Warmers

High quality, durable serving option for quick-turn serving environments

EASY POUR®

BUNN® exclusive design; high quality stainless steel base with drip proof, fast-pour lip

Clear, impact-resistant material complies with FDA regulations for food contact

Glass decanters

Reliable, shatter-resistant, and perfectly balanced with laboratory-grade, stress-free glass

RFID decanters

Replaceable RFID collar tracks coffee freshness with compatible brewers

Warmers

Ideal solution for remote serving; separate "on/off" switch



Glass



Easy Pour®



Stainless Steel



Glass with RFID



WX2 Side by Side

DECANTERS					COMPATIBLE EQUIPMENT
Product #	Model	Capacity	Handle Color	Quantity Per Case	Brewers
06100.0201	EASY POUR	1.9L	BLACK	1	12 CUP DECANTER BREWERS: VP17 VPR VPS AXIOM CW CWT CWTF CRTF RL VLPP
06100.0203	EASY POUR	1.9L	BLACK	3	
06100.6224	EASY POUR	1.9L	BLACK	24	
06101.0201	EASY POUR	1.9L	ORANGE	1	
06101.0203	EASY POUR	1.9L	ORANGE	3	
06101.6224	EASY POUR	1.9L	ORANGE	24	
42400.7103	GLASS (ENGLISH/FRENCH)	1.9L	BLACK	3	
42401.7103	GLASS (ENGLISH/FRENCH)	1.9L	ORANGE	3	
42402.7000	GLASS (ENGLISH/FRENCH, NO LOGO)	1.9L	BLACK	3	
42402.7001	GLASS (ENGLISH/FRENCH, NO LOGO)	1.9L	ORANGE	3	
42400.7024	GLASS	1.9L	BLACK	24	
42401.7024	GLASS	1.9L	ORANGE	24	
42402.7024	GLASS (NO LOGO)	1.9L	BLACK	24	
42402.7025	GLASS (NO LOGO)	1.9L	ORANGE	24	
42400.7203	GLASS W/RFID	1.9L	BLACK	3	AXIOM RFID
42401.7203	GLASS W/RFID	1.9L	ORANGE	3	AXIOM RFID
42402.7055	GLASS W/RFID (NO LOGO)	1.9L	BLACK	3	AXIOM RFID
42402.7056	GLASS W/RFID (NO LOGO)	1.9L	BLACK	24	AXIOM RFID
WARMERS					
Product #	Model	Finish	Number of Warmers	Volts	
06310.6000	WX2 SIDE BY SIDE	STAINLESS	2	120	
06450.6000	WX1	STAINLESS	1	120	
11402.6000	WL2 STEP UP	STAINLESS	2	120	

Product #s listed as 120/208V or 120/240V require 3 wires plus ground (2 hot, 1 neutral, ground) and must be connected to 208V service or 240V service, respectively. Please refer to the installation manual for more information.



Thermal Carafes, Pitchers and Airpots

Thermal Carafe

Highly durable stainless steel interior and exterior

Thermal Pitcher

Stainless steel lining ensures hot coffee for hours

Push Button Airpot

Brew-thru pump assembly - no need to remove for brewing

Lever-Action Airpot

Brew-thru lid with lever-action for easy use



CARAFES						COMPATIBLE EQUIPMENT
Product #	Model	L	Liner	Lid Color	Quantity perCase	Brewers
18022.6002	DELUXE THERMAL CARAFE	1.9	STAINLESS STEEL	BLACK	1	VPR-TC CW15-TC AXIOM-DV-TC SmartWAVE CWTF-TC
18022.6005	DELUXE THERMAL CARAFE	1.9	STAINLESS STEEL	BLACK	12	
40163.0000	THERMAL CARAFE	1.9	STAINLESS STEEL	BLACK	1	
40163.0001	THERMAL CARAFE	1.9	STAINLESS STEEL	ORANGE	1	
40163.0100	THERMAL CARAFE	1.9	STAINLESS STEEL	BLACK	12	
40163.0101	THERMAL CARAFE	1.9	STAINLESS STEEL	ORANGE	12	
40163.6002	THERMAL CARAFE W/RFID	1.9	STAINLESS STEEL	BLACK	1	
40163.6003	THERMAL CARAFE W/RFID	1.9	STAINLESS STEEL	ORANGE	1	
51746.0001	SEAMLESS THERMAL CARAFE	1.9	STAINLESS STEEL	BLACK	1	
51746.0101	SEAMLESS THERMAL CARAFE	1.9	STAINLESS STEEL	BLACK	12	
51746.0002	SEAMLESS THERMAL CARAFE W/RFID	1.9	STAINLESS STEEL	BLACK	1	
51746.0003	SEAMLESS THERMAL CARAFE	1.9	STAINLESS STEEL	1 BLACK, 1 ORANGE	2	
PITCHERS						
Product #	Model	L	Liner	Quantity per Case		Brewers
40400.0000	VACUUM PITCHER	1	STAINLESS STEEL	1		SmartWAVE
40400.0001	VACUUM PITCHER	.3	STAINLESS STEEL	1		SmartWAVE
AIRPOTS						COMPATIBLE EQUIPMENT
Product #	Model	L	Liner	Quantity per Case		Brewers
28696.6000	PUSH-BUTTON	2.2	GLASS	1		VPR-APS CW15-APS ICB-DV AXIOM-DV-APS AXIOM Twin APS SmartWAVE CWTF-APS ITCB-DV (flip tray)
28696.6001	PUSH-BUTTON	2.2	GLASS	6		
13041.6000	PUSH-BUTTON	2.5	GLASS	1		
13041.6001	PUSH-BUTTON	2.5	GLASS	6		
32125.0000	LEVER-ACTION	2.5	STAINLESS STEEL	1		
32125.0100	LEVER-ACTION	2.5	STAINLESS STEEL	6		
32130.0000	LEVER-ACTION	3	STAINLESS STEEL	1		
32130.0100	LEVER-ACTION	3	STAINLESS STEEL	6		
36725.0000	LEVER-ACTION	3.8	STAINLESS STEEL	1		
36725.0100	LEVER-ACTION	3.8	STAINLESS STEEL	6		

Soft Heat® Server System

BUNN-exclusive Soft Heat technology supplies controlled heat to the brewed coffee within the server whenever it's docked on the brewer, ensuring ideal holding temperatures and optimal flavor for longer periods

SH Server

5.7L capacity; choose from five optional holding time settings

Safety-Fresh® brew-thru lid with vapor seal and spill prevention

Soft grip handle for secure portability

SH Docking Station

Remote one and two server docking stations with 10.2cm legs

Instant power contact with servers

Add additional remote stations to increase volume



2SH Docking Station



1 SH Server and Docking Station

DESCRIPTION						ELECTRICAL
Product #	Model	Finish	Dimensions Height x Width x Depth (centimeters)			Volts
27825.6200	INFUSION SERIES® 1SH DOCKING STAND	STAINLESS	23.62	25.91	29.97	120
27825.6201	INFUSION SERIES® 1SH DOCKING STAND W/ COMM*	STAINLESS	23.62	25.91	29.97	120
27875.6200	INFUSION SERIES® 2SH DOCKING STAND	STAINLESS	23.62	51.31	29.97	120
27875.6201	INFUSION SERIES® 2SH DOCKING STAND W/ COMM*	STAINLESS	23.62	51.31	29.97	120
27850.6200	INFUSION SERIES® 1.5 GAL SH SERVER	BLACK/STAINLESS	17.53	37.85	28.45	24

*For More Information on stands with wi-fi communication visit bunn.com

Product #s listed as 120/208V or 120/240V require 3 wires plus ground (2 hot, 1 neutral, ground) and must be connected to 208V service or 240V service, respectively. Please refer to the installation manual for more information.



Universal Airpot Racks

Versatile merchandising system for airpots

- Displays can be combined or taken apart easily for greater flexibility
- Sturdy, carbon-steel wire construction with vinyl coating resists corrosion, easy to clean
- Configurations available for two to six airpots



AIRPOTS						
Product #	Model	Dimensions Height x Width x Depth (centimeters)			Capacity	
35728.0000	UNIV-2 APR (1 UPPER, 1 LOWER)	14.10	7.50	24.10	TWO AIRPOTS	
35728.0001	UNIV-2 APR (2 LOWER)	17.53	37.85	28.45	TWO AIRPOTS	
35728.0002	UNIV-3 APR (3 LOWER)	17.53	58.17	28.45	THREE AIRPOTS	
35728.0003	UNIV-4 APR (2 UPPER, 2 LOWER)	35.56	37.85	63.25	FOUR AIRPOTS	
35728.0004	UNIV-5 APR (3 UPPER, 2 LOWER)	35.56	58.17	63.25	FIVE AIRPOTS	
35728.0005	UNIV-6 APR (3 UPPER, 3 LOWER)	35.56	58.17	63.25	SIX AIRPOTS	

GPR Servers and Remote Warmers

Convenient servers and warming stands allow for easy set-up and maintenance of remote serving stations

Portable Server

- 5.7L capacity
- Top handle allows for easy transport to remote service
- Safety-Fresh® brew-thru lid with vapor seal and spill prevention

Warmer

- Adjustable black plastic legs



SERVERS							
Product #	Model	Dimensions Height x Width x Depth (Inches)			Capacity L	Finish	Brewers
20950.6001	1.5 GPR-FF	24.89	17.02	32.33	5.7	STAINLESS	Single GPR DBC, Dual GPR DBC, AXIOM Single, Single and Dual
12203.6001	RWS1 WARMER SATIN NICKEL LEGS	19.05	20.96	23.62	ONE GPR SERVER	STAINLESS	1.5GPR

Product #s listed as 120/208V or 120/240V require 3 wires plus ground (2 hot, 1 neutral, ground) and must be connected to 208V service or 240V service, respectively. Please refer to the installation manual for more information.

Iced Tea and Iced Coffee Dispensers

Solid stainless construction stands up to demands of foodservice environments

Sump dispense valves assure complete dispensing of beverage

Variety of shapes and sizes for every counter configuration



Square



Oval



Round



Narrow



TDO-N Low Profile Dispenser (Top)
TDO-N Narrow Dispenser (Lower)
w/ Dispense Rack Single LP

[Please see specification table on following page](#)

NARROW								
Product #	Model	Dimensions Height x Width x Depth (Centimeters)			Capacity	Handles	Additional Feature	Compatible Brewers
39600.0001	TDO-N-3.5	55.37	15.75	34.54	13.2L	FRONT/BACK	STANDARD DISPENSE FAUCET	Tall models w/ 73.66cm trunk: TB3, TB6 ITB, ITB DD ITCB, ITCB HV ITCB Twin HV
39600.0031	TDO-N-3.5	55.37	15.75	34.54	13.2L	FRONT/BACK	LIFT DISPENSE FAUCET	
39600.0047	TDO-N-3.5	55.37	15.75	34.54	13.2L	FRONT/BACK	SOLID LID PINCH TUBE FAUCET	
39600.0002	TDO-N-4.0	55.34	15.24	59.94	15L	FRONT/BACK	STANDARD DISPENSE FAUCET	
39600.0081	TDO-N-3.5	55.88	17.78	41.91	13.2L	FRONT/BACK	BREW THRU LID	
39600.0083	TDO-N-3.5	58.42	17.78	39.37	15L	FRONT/BACK	PINCH TUBE FAUCET BREW THRU LID	
43900.0001	TD3T-N	57.66	15.75	38.35	13.2L	FRONT/BACK	LIFT HANDLE BREW-THRU LID	
43900.0002	TD3T-N	57.66	15.75	38.35	13.2L	FRONT/BACK	LIFT HANDLE, SOLID LID	
SQUARE								
03250.0003	TD4	43.43	31.24	43.18	15.1L	SIDE	SOLID LID	Short models w/ 65.41cm trunk: TB3 ITB ITCB
03250.0006	TD4	43.43	31.24	43.18	15.1L	SIDE	BREW-THRU LID	
03250.0004	TD4T	55.63	31.24	45.47	15.1L	SIDE	SOLID LID	Tall models w/ 73.66cm trunk: ITB ITCB ITCB HV
03250.0005	TD4T	55.63	31.24	45.47	15.1L	SIDE	BREW-THRU LID, TALL	
CYLINDER - ROUND								
33000.0000	TDS-3	48.26	24.89	32.51	11.4L	SIDE	STAINLESS LID	TB3 ITB
33000.0023	TDS-3.5	51.82	24.89	32.51	13.2L	SIDE	STAINLESS LID	ITCB ITCBHV
33000.0001	TDS-5	65.02	24.89	32.51	18.9L	SIDE	STAINLESS LID	TU5
CYLINDER - OVAL								
34100.0000	TDO-4	48.77	32.51	40.64	15L	SIDE	SOLID, PLASTIC LID	TB3 ITB ICB ITCB HV
34100.0002	TDO-4	48.77	32.51	40.64	15L	SIDE	BREW-THRU PLASTIC LID	
34100.0001	TDO-5	56.64	32.51	40.64	18.9L	SIDE	SOLID, PLASTIC LID	
34100.0003	TDO-5	56.64	32.51	40.64	18.9L	SIDE	BREW-THRU PLASTIC LID	
LOW PROFILE								
39600.0066	TDO-N-2.0 LP	26.16	15.75	34.54	7.5L	FRONT/BACK	STANDARD DISPENSE FAUCET	Short models w/ 65.4cm trunk: TB3 ITB ITCB
39600.0065	TDO-N-3.5 LP	38.61	15.75	34.54	13.2L	FRONT/BACK	STANDARD DISPENSE FAUCET	
37100.0000	TDO-3.5 LP	25.40	24.89	40.89	13.2L	SIDE	BREW-THRU PLASTIC LID	TB3 LP, ITB LP
ACCESSORIES								
49634.0000	DISPENSE RACK SINGLE LP	62.23	16.51	45.21	n/a	SIDE	n/a	TDO-N-2.0 LP TDO-N-3.5 LP
50845.0000	BOOSTER WIRE FORM	25.40	24.89	40.89	n/a	SIDE	n/a	TDO-N-2.0 LP TDO-N-3.5 LP
37675.0001	REMOTE SERVER STAND	23.11	29.46	35.56	n/a	TOP	n/a	TDO-3.5 LP
50534.1000	SLIDE LID ASSEMBLY	3.81	16.00	38.10	n/a	n/a	n/a	TDO-N-2.0 LP TDO-N-3.5 LP
TEA CONCENTRATE DISPENSERS								
37750.0002	TCD-2	56.64	32.51	48.01	7.6	SIDE	TWO NOZZLE	

A clear glass filled with water, with a blue geometric overlay consisting of several overlapping diamond shapes. The background is a solid blue color. The text "WATER FILTERS" is centered in the middle of the glass.

WATER FILTERS

Water Filtration Systems

Quality beverages begin with quality water

BUNN® water filtration systems, when used with BUNN brewing equipment, ensure that your customers are getting the best tasting beverage possible. The Easy Clear® filters are manufactured to BUNN specifications and address water characteristics such as taste, odor, sediment, and hardness.

Quick Connect valve-in-head design simultaneously shuts off and vents water, allowing for simple and trouble-free cartridge change-outs

System maximum operating pressure is 125psi (862kPa) and operating temperature 100°F (38°C)



EQHP Twin 70L

HIGH PERFORMANCE FILTRATION SYSTEMS								
Part #	Model #	Lifetime Capacity/ Chlorine Reduction	Output Flow Rate	Taste & Odor	Sediment	Lime	Softwater	Replacement Cartridges
30200.1000	EQ-17-TL	5600L	1.9Lpm	•		•		30200.1001
30201.1001	IN-LINE ED-17-TL	5600L	1.9Lpm	•		•		30200.1001
30331.1001	EQ-TL-1	5600L	1.9Lpm	•		•		
30370.1000	EDSS-11-T200F	5600L	1.9Lpm	•	•	•		30370.1001
39000.0001	EQHP10L	37,800L	5.7Lpm	•	•	•		39000.1001
39000.0002	EQHP25L	94,600L	7.9Lpm	•	•	•		39000.1002
39000.0003	EQHP54L	204,400L	18.9Lpm	•	•	•		39000.1003
39000.0004	EQHP10	37,800L	5.7Lpm	•	•			39000.1004
39000.0005	EQHP25	94,600L	7.9Lpm	•	•			39000.1005
39000.0006	EQHP54	204,400L	18.9Lpm	•	•			39000.1006
39000.0007	EQHP-TEA	4350 grains	3.8Lpm	•			•	39000.1007
39000.0008	EQHP-ESP	1,600L	1.9Lpm	•		•		39000.1008
39000.0009	EQHP-SFTN	1350 grains		•			•	39000.1009
39000.0010	SCALE-PRO®	Recommended 6 month change-out				•		39000.1010
39000.0011	EQHP35L	132,400L	12.6Lpm	•	•	•		39000.1011
39000.0012	EQHP-TWIN 70L*	264,900L	25.3Lpm	•	•	•		(2) 39000.1011
39000.0013	EQHP-TWIN 108SP**	408,824L	37.8Lpm	•	•	•		(2) 39000.1006, (1) 39000.1010
39000.0014	EQHP-5C	18,927L	5.7Lpm	•	•			39000.1014
45961.0000	C300 KIT	4,000L		•		•		45961.1001
47152.0000	C500 KIT	6,800L		•		•		47159.0000

*Requires two (2) cartridges. **Requires three (3) cartridges

The background of the image is a white, textured surface resembling crumpled paper. Overlaid on this are several diamond-shaped elements. A series of blue diamonds with rounded corners are arranged in a diagonal line from the top-left towards the bottom-left. In the top-right corner, there are three grey diamonds with rounded corners, also arranged in a diagonal pattern. The text 'PAPER FILTERS' is centered in the lower half of the image.

PAPER FILTERS

Paper Filters

Selection of coffee filters is a vital step in brewing perfect coffee - don't settle for anything less than BUNN® quality coffee filters. Using the results of years of research, BUNN manufactures the best filters from high quality, heavy weight paper, so the water flows properly through the coffee. Our filters are uniquely designed for strength with taller walls to help reduce overflow and grounds in your coffee.



BUNN's paper stock used in the manufacturing of our coffee filters is produced using an elemental chlorine-free (ECF) bleaching method.

Product #	Filter Type	Description	Number per Bag	Bags per Case	Number Cluster	Overall Measure x Base Diameter (centimeters)	Packed per Case	Case Weight (kg)	Cases per Skid/Tier
20115.6000	DECANTER FILTERS	REGULAR C, S, R, O, VLPF, VPR, VPS, VP-17	500	2	50	24.77 x 10.80	1000	1.81	180/15
20116.0000		REGULAR NARROW C, S, R, O, VLPF, VPR, VPS, VP-17	500	2	50	24.13 x 8.26	1000	1.91	180/15
20122.6000		REGULAR FAST FLOW C, S, R, O, VLPF, VPR, VPS, VP-17	500	2	50	24.77 x 10.80	1000	2.04	180/15
20106.6000		RETAIL - 8 & 10 CUP BREWERS	500	2	50	21.59 x 8.26	1000	1.45	231/21
20109.0000	URN FILTERS	URN - U3	252	1	36	45.09 x 18.42	252	2.47	88/11
20112.0000		NARROW BASE URN	250	1	25	47.00 x 15.88	250	2.61	88/11
20124.0000		URN, 11.4L	250	1	25	48.26 x 18.42	250	2.74	88/11
20111.0000		TITAN, URN	252	1	36	50.80 x 19.69	252	2.99	84/12
20125.0000		URN, 22.7L	250	1	25	53.34 x 22.22	250	3.4	72/9
20113.0000		URN, 37.9L	250	1	25	60.33 x 22.22	250	4.45	54/9
20131.0000		URN, 37.9L	252	1	36	61.60 x 27.30	252	4.40	36/6
20120.0000	OTHER FILTERS	SYSTEM III	252	2	36	38.42 x 13.65	504	2.83	108/12
20100.0000		TEA BREWERS, SINGLE & DUAL COFFEE BREWERS, 1.5GAL URNS, ITCB, SYSTEM II	500	1	50	32.38 x 13.34	500	2.04	150/15
20157.0001		GOURMET C FUNNEL	500	2	50	31.75 x 12.07	1000	3.63	60
20138.1000		GOURMET, SINGLE TF, DUAL TF, SINGLE SH, DUAL SH, SINGLE, DUAL, 1.5GAL URNS	500	1	50	34.93 x 13.34	500	2.29	108/12



ACCESSORIES

Accessories and Cleaning Agents



Nitrogen Regulator Kit

CLEANING AGENTS AND ACCESSORIES		
Part #	Model	Quantity Per Case
29875.0000	FLOWJET® SYSTEM	ONE
24634.0000	KAY-5 SANITIZER	200 PACKETS
24634.0001	KAY-5 SANITIZER	50 PACKETS
55605.0000	CAFIZA -CRESCENDO- CLEANING TABLETS (32/BOX)	ONE
36000.1188	CAFIZA CLEANING TABLETS	TWELVE CONTAINERS
36000.1189	CAFIZA CLEANING TABLETS (100ct)	ONE CONTAINER
37306.0000	URNEX DESCALER	ONE 1OZ PACKET
39000.0100	EQHP WATER FILTER GAUGE	ONE
39000.0101	SCALE-PRO INSTALLATION KIT	ONE
39159.0000	GRINDZ GRINDER CLEANER	ONE CONTAINER
39159.0001	GRINDZ GRINDER CLEANER	TWELVE BOTTLES
39265.0000	RINZA MILK CLEANER	ONE BOTTLE
39265.0001	RINZA MILK CLEANER	SIX BOTTLES
39302.0000	REFILLABLE CONTAINER ASSEMBLY	ONE
39637.0000	TABZ BREWER CLEANER	ONE CONTAINER
39637.0001	TABZ BREWER CLEANER	TWELVE CONTAINERS
45961.1001	C300 & C500 REPLACEMENT HEAD	ONE
52820.0000	PRIMARY CO2 REGULATOR KIT	ONE
52367.1000	CO2 TWIN 20LB TANK RACK W/ REGULATOR KIT	ONE
55324.0000	NITRON ₂ ® SCHOLLE QUICK CONNECT ASSEMBLY	ONE
55325.0000	NITRON ₂ ® SCHOLLE QUICK CONNECT EXTENSION TUBE ASSEMBLY	ONE
54060.0000	PRIMARY NITROGEN REGULATOR KIT	ONE
55660.0001	NITRON ₂ ® GAS MODULE	ONE
45536.1002	NITRON ₂ ® ADA KIT	ONE
50199.0001	RINZA MILK TABLETS	ONE
55011.0005	NITRON ₂ ® SCHOLLE SR Y-FITTING TUBE ASSEMBLY	ONE
55300.1522	BW4 COFFEE CLEANING TABLETS	ONE
43500.1446	BW3 & BW4c MILK CLEANING TABLETS	ONE
42933.0001	SURE IMMERSION CLEANING TABLET	ONE
50766.0001	SURE IMEERSION FILTER PAPER	ONE

Stock Funnels



URN FUNNEL

PRODUCT NUMBER 07022.7012

For use with U3 brewers

BLACK PLASTIC SPLASHGARD® FUNNEL WITH DECALS

PRODUCT NUMBER 20583.7003

For use with CDBC, CWT, AXIOM®,
Smart WAVE® Brewers

PRODUCT NUMBER 29351.7001

For use with O, R, CDBD Twin,
CWT Twin and AXIOM® Twin Brewers



BLACK PLASTIC ITCB FUNNEL

PRODUCT NUMBER 53463.7008

For use when brewing coffee with
new Infusion Series® ITB and ITCB Brewers

STAINLESS STEEL SPLASHGARD® FUNNEL

PRODUCT NUMBER 20216.7000

For use with CDBC, CWT AXIOM®
and Smart WAVE® brewers

PRODUCT NUMBER 20217.7000

For use with O, R, CDBC Twin, CWT Twin and
AXIOM® brewers



STAINLESS STEEL SINGLE/DUAL FUNNEL

PRODUCT NUMBER 20201.7201

For use with older Single®, Dual®, and
Soft Heat® brewers



SMART FUNNEL®

PRODUCT NUMBER 32643.7000

Standard w/ bypass

PRODUCT NUMBER 32643.7010

w/D-Ring basket

For use with older BrewWISE®, ThermoFresh®,
Soft Heat®, DBC® and ICB brewers



SST PLATINUM FUNNEL

PRODUCT NUMBER 54675.7008

For use with new
Infusion Series® Brewers



TITAN® FUNNEL

PRODUCT NUMBER 40114.7000

For use with Titan® brewers

GOURMET C FUNNEL

PRODUCT NUMBER 34559.7000

For use with CDBC, CWT AXIOM® and
SmartWAVE® APS and TC brewers

PRODUCT NUMBER 34559.7001

For use with CDBC Twin, CWT Twin and
AXIOM® Twin and TC brewers

Universal design – handle may be moved to
appropriate side

Allows brewing heavier throw weights

PRODUCT NUMBER 34559.7003

For use with older ITCB

TRANSLUCENT COFFEE FUNNEL

PRODUCT NUMBER 20583.7002

For use with VP and CWTF brewers

PRODUCT NUMBER 29351.7000

For use with O, R, CDBC Twin, CWT Twin
and AXIOM®v Twin brewers



TRANSLUCENT TEA FUNNEL

PRODUCT NUMBER 03021.7016

For use with Smart WAVE® brewer

TRANSLUCENT TEA FUNNEL

PRODUCT NUMBER 03021.7004

For use with TB3, TU3, and older
ITCB brewers

PRODUCT NUMBER 03021.0005
(Quick Dispense)

For use with TB3Q, TU3Q, and
older ITB brewers



TRANSLUCENT DUAL DILUTION TEA FUNNEL

PRODUCT NUMBER 03021.7013

For use with TB6 brewer

PRODUCT NUMBER 03021.7014

For use with TB6Q brewer

TRANSLUCENT TEA FUNNEL

PRODUCT NUMBER 53463.7010

For use with new
Infusion Series® ITCB Brewers



NOTE: All funnels shown on this page are designed with SplashGard®
to help deflect hot liquids away from the hand.

Special Purpose Funnels



TRANSLUCENT POUCH PACK FUNNEL


PRODUCT NUMBER [35282.7001](#)

For use with TU3Q brewer

PRODUCT NUMBER [35282.7002](#)

For use with TU3 and TB3 brewers

Use with rectangular tea pouch pack



POUCH PACK FUNNEL FOR SATELLITE BREWERS

PRODUCT NUMBER [35282.7001](#)

For use with older Single and Dual SH brewers

POUCH PACK FUNNEL FOR SATELLITE BREWERS

PRODUCT NUMBER [29151.7000](#)
Black Handle

PRODUCT NUMBER [29151.0001](#)
Orange Handle

Interchangeable handle allows use will all BUNN decanter brewers



POUCH PACK FUNNEL FOR SMALL BREW CHAMBER BREWERS

PRODUCT NUMBER [02073.7010](#)

For use with O and R brewers

PRODUCT NUMBER [02774.0010](#) Brown

PRODUCT NUMBER [02774.0011](#) Black

For use with VP and CWTF brewers



POUCH PACK FUNNEL FOR LARGE BREW CHAMBER BREWERS

PRODUCT NUMBER [02074.7010](#)

For use with O and R brewers

PRODUCT NUMBER [04274.7010](#) Brown

PRODUCT NUMBER [04274.7012](#) Black

For use with VP and CWTF brewers



NOTE: Only funnels #35282.7001, #35282.7002, and #35282.0000 on this page are designed with SplashGard® to help deflect hot liquids away from the hand.

Drip Trays Coffee



INFUSION SERIES® SH BREWERS AND SH STAND

PRODUCT NUMBER [53452.0001](#)



INFUSION SERIES® TWIN SH BREWERS AND 2 SH STAND

PRODUCT NUMBER [53452.0000](#)



RWS1 WARMER

PRODUCT NUMBER [20213.0103](#)



DUAL® BREWERS

PRODUCT NUMBER [20213.0101](#)



LCR-3 HV

PRODUCT NUMBER [41656.0000](#)



AIRPOT RACK

PRODUCT NUMBER [25368.0000](#) Tray

PRODUCT NUMBER [25367.0000](#) Tray Liner



THERMOFRESH SERVER®

PRODUCT NUMBER [38931.0000](#) Tray

PRODUCT NUMBER [38932.0000](#)
Tray Cover



U3 COFFEE URN

PRODUCT NUMBER [07284.0000](#)

Drip Trays *Dispensed Water*



HW2, H5M, and H5X
PRODUCT NUMBER 02497.0000



OHW
PRODUCT NUMBER 02497.0001

Drip Trays *Tea*




TCD and TDO
PRODUCT NUMBER 38029.1000



TDO-N
PRODUCT NUMBER 39626.0000 Tray
PRODUCT NUMBER 39627.0000 Tray Cover

Drip Trays *Hot Dispensed*




FMD-1 and FMD-2
PRODUCT NUMBER 02571.0000 Tray



PRODUCT NUMBER 28966.0000 Tray Cover



FMD-3
PRODUCT NUMBER 28699.0000 Tray
PRODUCT NUMBER 28267.0000 Tray Cover



FMD-4 and FMD-5
PRODUCT NUMBER 34716.0000 Tray
PRODUCT NUMBER 34717.0000 Tray Cover



iMIX-3
PRODUCT NUMBER 36984.0000 Tray
PRODUCT NUMBER 36985.0000 Tray Cover



iMIX-4 and iMIX-5
PRODUCT NUMBER 36670.0000 Tray
PRODUCT NUMBER 36739.0000 Tray Cover



Drip Trays *Cold Dispensed*



JDF-2S
PRODUCT NUMBER 38765.1000



NITRON EXTENDED
PRODUCT NUMBER 44015.1000
Increases cup clearance to 10.25"



JDF-4S and LCR-3
PRODUCT NUMBER 38764.1001



JDF-4S EXTENDED
PRODUCT NUMBER 40789.1000
Increases cup clearance to 10.25"

Drip Trays *Frozen Dispensed*



ULTRA-2 WHITE
PRODUCT NUMBER 28086.0000 Tray
PRODUCT NUMBER 32068.0000 Tray Cover



ULTRA-2 BLACK
PRODUCT NUMBER 28086.0001T Tray
PRODUCT NUMBER 32068.0001 Tray Cover

NITRON₂[®] Accessories



REFILLABLE CONTAINER ASSEMBLY
PRODUCT NUMBER 39302.0000

NITRON SCHOLLE QUICK CONNECT
PRODUCT NUMBER 55324.0000

NITRON SCHOLLE QUICK CONNECT
PRODUCT NUMBER 55325.0000

Best Result in the Cup™



CORPORATE HEADQUARTERS

5020 Ash Grove Drive, Springfield, IL USA 62711
(+1) 217-529-6601 • 800-637-8606



www.bunn.com