

Product data sheet

Specifications



Network Management Card for Easy UPS, 1-Phase

AP9544

Overview

Presentation

The Network Management Card for Easy UPS On-Line (AP9544) enables secure remote monitoring and control of one Easy UPS Online through the easy-to-use web browser interface, via EcoStruxure™ IT Software or another SNMP-enabled system.

A 12-month Secure NMC Subscription, that allows the customer to access future firmware updates, is included with the purchase of the card*. Upon expiration of the provided Secure NMC Subscription the purchase of a new Secure NMC Subscription is required to access future firmware updates.

*The NMC Firmware must be V2.5 or later. Find the latest Firmware in the Software and Firmware section below.

Lead time Usually in Stock

Main

Product or Component Type Network Interface

Provided Equipment User Manual
USB cable

Physical

Height 1.7 in (4.4 cm)

Width 2.05 in (5.2 cm)

Depth 3.1 in (8.0 cm)

Net Weight 0.11 lb(US) (0.05 kg)

Mounting preference No preference

Mounting Mode Not rack-mountable

Conformance

Standards CISPR 32
EN 55024
EN 61000-4-2
EN 61000-4-3
EN 61000-4-4
EN 61000-4-5
EN 61000-4-6
EN 61000-4-8
EN 61000-6-2
EN/IEC 62040-2

Product Certifications FCC Class A
ICES-003
VCCI Class A
AS/NZS
UK PSTI

Environmental

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Ambient Air Temperature for Operation	23.0000000000...113.0000000000 °F (-5...45 °C)
Operating altitude	0...10000 ft
Relative Humidity	0...95 %
Ambient Air Temperature for Storage	5.0000000000...149.0000000000 °F (-15...65 °C)
Storage altitude	0...50000 ft (0.0000000000...15240.0000000000 m)
Storage Relative Humidity	0...95 %

Communications & Management

Communication network type	10/100/1000BASE-T
-----------------------------------	-------------------

Ordering and shipping details

GTIN	731304440161
-------------	--------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.811 in (4.600 cm)
Package 1 Width	6.496 in (16.500 cm)
Package 1 Length	9.055 in (23.000 cm)
Package 1 Weight	10.653 oz (302.000 g)
Unit Type of Package 2	P06
Number of Units in Package 2	44
Package 2 Height	26.772 in (68.000 cm)
Package 2 Width	23.622 in (60.000 cm)
Package 2 Length	31.496 in (80.000 cm)
Package 2 Weight	46.297 lb(US) (21.000 kg)

Contractual warranty

Warranty	2 years repair or replace
-----------------	---------------------------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

Well-being performance

Mercury Free

Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

China Rohs Regulation [China RoHS declaration](#)
Product out of China RoHS scope. Substance declaration for your information.

Environmental Disclosure [Product Environmental Profile](#)

Weee The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Circularity Profile [End of Life Information](#)