



CSP706T | PROFESSIONAL SURGE PROTECTOR

Protect home and office computers, electronics, and home theater equipment

The Professional Surge Protector CSP706T offers vital surge suppression for common home and office devices such as computers and electronics. It prevents spikes in energy caused by storms and electrical power surges and is ideal for safeguarding personal computers, phones/faxes/modems, and consumer electronics. The CSP706T provides 1,650 joules of protection and 7 surge-protected outlets (1 widely-spaced for a transformer plug). Data line protection occurs with RJ11 ports for telecommunication devices (phones, faxes, modems, and DSL lines).

Features of the CSP706T include automatic shutdown, data line protection, a power cord (6 ft.), a right-angle plug with 45° offset, LED indicators, impact-resistant casing, keyhole mounting slots, metal oxide varistor (MOV) technology, and an EMI/RFI noise filter. The CSP706T comes with a Limited Lifetime Warranty and a Connected Equipment Guarantee.

TYPICAL APPLICATIONS

- Mobile Devices
- Personal Electronics
- Cell Phones
- Personal Computers

FEATURES

- Surge suppression: 1,650 J
- Volts: 125 V
- Circuit breaker: 15 A
- Plug type: NEMA 5-15P (45° offset)
- Outlet type: 7 NEMA 5-15R (surge-protected)
- Transformer outlet: 1
- Power cord: 6 ft
- Data line protection: Telephone, DSL, Fax
- EMI/RFI Filtration: Yes
- LED indicators: Yes
- Warranty: Limited Lifetime
- Connected Equipment Guarantee: \$125,000



SPECIFICATIONS

INPUT	
Circuit Breaker	15 A
Cord Length	6 ft (1.8 m)
Input Plug Type	NEMA 5-15P
Maximum Input Current	15 A
OUTPUT	
Outlet Type	7 - NEMA 5-15R
Outlets - Total	7
Outlets - Widely Spaced	1

SURGE PROTECTION & FILTERING	
Attenuation	43 dB
Clamping Voltage	500V (H-G, N-G)
Coax Protection RG6	None
EMI/RFI Filtration	150 KHz 100 MHz Yes
Maximum Surge Current	75,000 A
Maximum Surge Current H-G	15,000 A
Maximum Surge Current H-N	45,000 A
Maximum Surge Current N-G	15,000 A
Maximum Surge Voltage	6,000 V
Response Time	<1 Nanosecond
Surge Suppression (Joules)	1,650 J

CSP706T

PROFESSIONAL SURGE PROTECTOR

SPECIFICATIONS CONT.

PHYSICAL

Color	Black
Form Factors Supported	Keyhole (Wall Mount or Under-counter Installation)
Keyhole Mounting Slots	Yes
Material of Construction	Plastic
Safety Covers	Yes

PHYSICAL DIMENSIONS

Physical Dimensions - WxHxD (cm)	7.01 x 3.4 x 30.71 cm
Physical Dimensions - WxHxD (mm)	70 x 34 x 307 mm
Physical Dimensions - WxHxD (in.)	2.76 x 1.34 x 12.09 in.
Weight (kg)	0.50 kg
Weight (lb)	1.10 lbs.

SHIPPING DIMENSIONS

Shipping Dimensions - WxHxD (cm)	37.47 x 5.59 x 11.18 cm
Shipping Dimensions - WxHxD (mm)	374.65 x 55.88 x 111.76 mm
Shipping Dimensions - WxHxD (in)	14.75 x 2.2 x 4.4 in.
Weight (kg)	0.68 kg
Weight (lb)	1.50 lbs.

CERTIFICATIONS

Environmental	RoHS Compliant
Safety	UL1363

WARRANTY

CEG Amount	\$125,000
Connected Equipment Guarantee	Lifetime
Product Warranty	Limited Lifetime Warranty