



Main

Ambient air temperature for operation	-5...40 °C
Ambient air temperature for storage	-25...65 °C
Colour	Black
Curve equation	Efficiency
Curve load maximum	100 %
Curve X-axis maximum	100 %
Curve X-axis title	Load
Curve X-axis units	Percentage
Curve Y-axis maximum	100 %
Curve Y-axis minimum	50 %
Curve Y-axis title	Efficiency
Curve Y-axis units	Percentage
Depth	107 cm
Height	200.4 cm
Input current limits	200 A
Input voltage	208 V 208 V 3 phases 480 V 3 phases 600 V 3 phases
Max current draw	200 A
Network frequency	60 Hz
Number of input connectors	1 hard wire 5 wire (3P + N + E)
Operating altitude	0...10000 ft
Output voltage	208 V 208 V 3 phases 415 V 3 phases 480 V 3 phases 600 V 3 phases
UPS size	S
Net weight	134 kg
Provided equipment	Installation guide
Relative humidity	0...95 %
Standards	UL 60950-1

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Storage altitude	0.00...3048.00 m
Width	30 cm
Mounting mode	Not rack-mountable
Mounting preference	No preference
Curve X-axis minimum	0 %

Packing Units

Package 1 Weight	155 kg
Package 1 Height	215 cm
Package 1 width	84.8 cm
Package 1 Length	121 cm
SCC14	10731304296253

Offer Sustainability

EU RoHS Directive	Under investigation
-------------------	---------------------

Contractual warranty

Warranty	1 year repair or replace
----------	--------------------------