

Interface Box for Transparent Display

TSP500



FEATURES

- 1,920 x 1,080 (FHD)
- HDMI, DVI, RGB Connectivity
- Lightweight
- Easy Installation

SPECIFICATIONS

TSP500

PANEL	Max Input Resolution (FHD)	1920 x 1080@60Hz(RGB, HDMI, DVI-D)	PHYSICAL SPECIFICATION	Carton Dimensions (W x H x D)	31.4cm x 35.9cm x 12.4cm
	Max Input Resolution (HD)	1366 x 768@60Hz(RGB, HDMI, DVI-D)		Packed Weight	1.96Kg
	Recommended Resolution (FHD)	1920 x 1080@60Hz(RGB, HDMI, DVI-D)		VESA™ Standard Mount Interface	N/A
	Recommended Resolution (HD)	1366 x 768@60Hz(RGB, HDMI, DVI-D)	SPECIAL FEATURES	Temperature Sensor	Yes
	H-Scanning Frequency	30 ~ 67.5kHz(RGB, HDMI, DVI-D)		ENVIRONMENT CONDITIONS	Operation Temperature
	V-Scanning Frequency	60Hz(RGB, HDMI, DVI-D)	Operation Humidity		10% ~ 80%
	Picture mode	Vivid, Standard, Cinema, Sports, Game	POWER		Power Supply
	Color temperature	Warm, Medium, Cool		Power Consumption	
CONNECTIVITY	Input (Rear)			Typical / Smart Energy Saving (on)	25W (12V Input)
	Digital	HDMI(1), DVI-D(1) with HDCP for all input		DPMS	1,4W
	Analog	RGB(1), Shared Component(1), AV (1)		Power Off	1W
	Audio	RGB/DVI-D (3.5Φ, 1)	STANDARD(CERTIFICATION)	Safety	N/A
	External Control	RS232C(1), RJ45(1)		EMC	FCC Class "A", CE, KCC
	USB	USB(1)		ErP / Energy Star	Yes / No (Energy Star 5.1)
	Output (Rear)		MEDIA PLAYER COMPATIBILITY	SuperSign Elite-W Lite	Yes
	Digital	Yes (LVDS)		External Media Player Attachable	N/A
Analog	N/A	SOFTWARE COMPATIBILITY		Supersign Compatibility	N/A
Audio	External Speaker Option		ACCESSORY	Included	Remote Controller, Power Cable, RGB Cable, Manual, ESG, LVDS cable(FHD/HD), IR Dongle
External Control	RS232C(1)	Optional		SP-2000 (Speaker)	
PHYSICAL SPECIFICATION	Color	Black			
	Dimension (W x H x D)	19.8cm x 14.4cm x 2.9cm			
	Weight (head)	0.7Kg			

* WOT : Within Operation Temperature

※ Image may differ slightly from actual product. Specifications are subject to change without prior notice.

