

Product data sheet

Specifications



APC Symmetra RM XR Frame 208/240V

SYRMXR4

Overview

Lead time	Usually in Stock
-----------	------------------

Main

Main Input Voltage	120 V
Product or Component Type	Battery accessory
Number of rack unit	4U
Number of cables	1
Battery Type	VRLA
Provided Equipment	Rack Mounting support rails
Range of Product	Symmetra Battery Systems

Batteries & Runtime

Battery Placement	Battery Cabinet
Battery Slots Empty	4
Included Battery Modules	0
Battery manufacturer	Panasonic
Battery Voltage	120 V
RBC Quantity	4

Physical

Color	Black
Height	7.008 in (178 mm)
Width	19.02 in (483 mm)
Depth	25.2 in (640 mm)
Net Weight	46.10 lb(US) (20.91 kg)
Mounting Mode	Rack-mounted
USB compatible	No

Conformance

Standards	UL 1778
-----------	---------

Environmental

Ambient Air Temperature for Operation	32...104 °F (0...40 °C)
---------------------------------------	-------------------------

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Operating altitude	0...10000 ft
Relative Humidity	0...95 %
Ambient Air Temperature for Storage	32...104 °F (0...40 °C)
Storage altitude	0...50000 ft (0...15240 m)
Storage Relative Humidity	0...95 %

Ordering and shipping details

GTIN	731304098850
------	--------------

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	13.5 in (34.3 cm)
Package 1 Width	32.008 in (81.3 cm)
Package 1 Length	23.0 in (58.4 cm)
Package weight(Lbs)	67.13 lb(US) (30.45 kg)

Contractual warranty

Warranty (in months)	24
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	92 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	88 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	2 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	2 kg CO2 eq.

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACH Regulation	Free of Substances of Very High Concern above the threshold

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Take-back	Yes
-----------	-----