

Product data sheet

Specifications



APC KVM 2G, Analog, 1 Local User, 8 ports



KVM0108A

Overview

Lead time	Usually in Stock
-----------	------------------

Main

Product or Component Type	Switch
Number of rack unit	1U
Provided Equipment	CD with software Installation guide Rack Mounting brackets

Physical

Color	Black
Height	1.7 in (43 mm)
Width	16.7 in (424 mm)
Depth	7.4 in (188 mm)
Net Weight	5.3 lb(US) (2.4 kg)
Mounting Location	Front
Mounting preference	No preference
Mounting Mode	Not rack-mountable

Conformance

Product Certifications	cUL Listed C-tick CE EAC TAA compliance UL-AR VCCI Class A VDE
Standards	FCC Part 15 class A ICES-003 UL 60950-1

Environmental

Ambient Air Temperature for Operation	32...122 °F (0...50 °C)
Operating altitude	0...10000 ft
Relative Humidity	0...80 %
Ambient Air Temperature for Storage	-4...140 °F (-20...60 °C)
Storage altitude	0...50000 ft (0...15240 m)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Storage Relative Humidity	0...80 %
---------------------------	----------

Ordering and shipping details

GTIN	731304285502
------	--------------

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	5.7 in (14.6 cm)
Package 1 Width	13.0 in (33 cm)
Package 1 Length	24.4 in (61.9 cm)
Package weight(Lbs)	8.6 lb(US) (3.9 kg)

Contractual warranty

Warranty (in months)	24
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	8 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	8 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.2 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0.2 kg CO2 eq.

Use Better



Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACH Regulation	Free of Substances of Very High Concern above the threshold

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	95
Circularity Profile	End of Life Information
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Image of product / Alternate images

Alternative

