

# Product data sheet

Specifications



## APC Symmetra RM 2kVA Scalable to 6kVA N+1 208/240V

SYH2K6RMT

⚠ Discontinued on: Dec 31, 2024

⚠ To be end-of-service on: Dec 31, 2034

⚠ To be discontinued

### Overview

Lead time	Usually in Stock
-----------	------------------

### Main

Main Input Voltage	208 V
Product or Component Type	Uninterruptible power supply (UPS)
Main Output Voltage	208 V
Kw Rating	1400 W
Rated power in VA	2000 VA
Input Connection Type	NEMA L6-30P 30 A
output connection type	2 NEMA L6-20R 1 NEMA L6-30R
Number of rack unit	8U
Cable length	10 ft (3.05 m)
Number of cables	1
Battery Type	Lead-Acid battery
Provided equipment	User Manual Rack Mounting brackets Rack Mounting support rails CD with software
Range of Product	Symmetra

### Batteries & Runtime

Run Time	<a href="#">View Runtime Graph</a>
Included Battery Modules	1
Battery Slots Empty	4
Typical recharge time	4 h
Additional information	UPS accepts 1-4 additional battery packs Configurable for 220 : 230 or 240 nominal output voltage
Battery Charge Power (Watts)	153 W rated
Battery life	3...5 year(s)
Extendable Run Time	1

### General

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

product web sub-family	2kVA power increments
Number of power module	4
Number preinstalled power module	1
Number of power module free slots	0
Number of power module filled slots	0
Redundant	Yes

## Physical

color	Black
Height	14.02 in (35.6 cm)
Width	19.02 in (48.3 cm)
Depth	28.74 in (73 cm)
Net Weight	164.35 lb(US) (74.55 kg)
Mounting Location	Front
Mounting preference	Lower
Mounting Mode	Rack-mounted
Two post mountable	0
USB compatible	No

## Input

Input Frequency	50/60 Hz +/- 5 Hz auto-sensing
Number of input connectors	1 Hard Wire 3-wire (2PH + G)
Efficiency at full load	155...276 V
Input Power Factor at Full Load	0.98

## Output

Max Configurable Power (Watts)	4200 W
Harmonic distortion	Less than 5 % at full load
Output Frequency (sync to mains)	57...63 Hz for 60 Hz nominal sync to mains 60 Hz not synced
Crest factor	Up to 5 : 1
Topology	Double Conversion Online
Wave type	Sine wave
Bypass type	Internal Bypass (Automatic and Manual)
Efficiency at full load	91 % full load)
Maximum configurable power in VA	6000 VA

## Conformance

Product Certifications	CSA
Standards	FCC Part 15 class A UL 1778

## Environmental

Ambient air temperature for operation	32...104 °F (0...40 °C)
Relative Humidity	0...95 %
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
Storage Relative Humidity	0...95 %
Storage altitude	0...50000 ft (0.0000000000...15240.0000000000 m)
Acoustic level	60 dBA
Online Thermal Dissipation	430 Btu/h

## Communications & Management

Free slots	2
Pre-Installed SmartSlot™ Cards	Network management card 2 with environmental monitoring
control panel	Multi-function LCD status and control console
Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays
Emergency Power Off (EPO)	Yes

## Ordering and shipping details

GTIN	731304740100
------	--------------

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	20.00 in (50.8 cm)
Package 1 Width	30.98 in (78.7 cm)
Package 1 Length	22.99 in (58.4 cm)
Package 1 Weight	185.39 lb(US) (84.09 kg)

## Contractual warranty


Warranty	2 years repair or replace, optional on-site warranties available, optional extended warranties available
----------	--


Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)


[How we assess product sustainability >](#)

Use Better

 Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
<a href="#">EU RoHS Directive</a>	Compliant with Exemptions
REACH Regulation	<a href="#">REACH Declaration</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a>
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>

 Energy efficiency	
Optimized Energy Efficiency	Energy efficient product

Use Again

 Repack and remanufacture	
Removable battery	User replaceable
Take-back	Yes