

Interface ports, Management Options, UPS Interface Expander 2, additional UPS interface ports with serial shutdown support

AP9624

Overview

Presentation	UPS Management SmartSlot offer with serial shutdown support of up to two additional devices such as Servers and Network Storage Devices.
Lead time	Usually in Stock

Main

Range of Product	Management Options and Cables	
Provided Equipment	RS-232 configuration cable User Manual Warranty card	
Product or Component Type	Expansion unit	
Number of cables	2	

General

Power supply type	Self powered via SmartSlot

Physical

Net Weight	0.90 lb(US) (0.41 kg)	
Width	0.541 ft (0.165 m)	
Height	2.01 in (5.1 cm)	
Depth	4.49 in (11.4 cm)	
Mounting preference	No preference	

Conformance

Standards	EN 55022 Class A		
	EN 55024		
	FCC Part 15 class A		
	IEC 62040-2		
	EN 61000-6-1		
	EN 61000-6-2		
	EN 55011		
	EN 55022		
Product Certifications	C-tick		
	CE		
	Industry Canada		
	VCCI		

Environmental

Storage Relative Humidity	095 %	
Relative Humidity	095 %	

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Ambient Air Temperature for Storage	5113 °F (-1545 °C)
Ambient air temperature for operation	32104 °F (040 °C)
Storage altitude 050000 ft (0.000000000015240.0000000000 m)	
Operating altitude	010000 ft 05000 ft

Ordering and shipping details

GTIN 731304314974

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	2.01 in (5.1 cm)	
Package 1 Width	6.50 in (16.5 cm)	
Package 1 Length	9.25 in (23.5 cm)	
Package 1 Weight	0.90 lb(US) (0.41 kg)	

Contractual warranty

Warranty 2 years repair or replace



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

∇ Environmental footprint	
Carbon footprint (kg CO2 eq, Total Life cycle)	3
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances		
EU RoHS Directive	Compliant with Exemptions	
REACh Regulation	REACh Declaration	
Optimized Energy Efficiency	Energy efficient product	

Use Again

○ Repack and remanufacture		
Circularity Profile	End of Life Information	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.	
Take-back	Yes	