

APC Smart-UPS On-Line, 2200VA, Rackmount 2U, 120V, 6x 5-20R+1x L5-20R NEMA outlets, SmartSlot, Extended runtime, W/ rail kit

SRT2200RMXLA

#### **Overview**

Presentation	High density, double-conversion on-line power protection with scalable runtime.
Lead time	Usually in Stock

Main		
Main Input Voltage	120 V	
Product or Component Type	Uninterruptible power supply (UPS)	
Main Output Voltage	120 V	
Kw Rating	1800 W	
Rated power in VA	2200 VA	
Input Connection Type	NEMA 5-20P	
output connection type	6 NEMA 5-20R 1 NEMA L5-20R	
Number of rack unit	2U	
Cable length	6 ft (1.8 m)	
Number of cables	1	
Provided equipment	CD with software Documentation CD Installation guide Rack mounting hardware Rack Mounting brackets Rack Mounting support rails USB cable Warranty card	
Range of Product	Smart-UPS On-Line	

#### **Batteries & Runtime**

Run Time	View Runtime Graph ☐	
Efficiency	View Efficiency Graph ☐	
Battery Type	Lead-Acid battery	
Battery Voltage	72V	
Extendable Run Time	1	
Included Battery Modules	1	
Battery Slots Empty	0	
Typical recharge time	3 h	
RBC Quantity	1	

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Battery life	35 year(s)
Replacement battery	APCRBC141 ☐ SRT72RMBPUS ☐
Battery Charge Power (Watts)	102 W rated

## General

Number of power module	1400
Number of power module filled slots	0
Number of power module free slots	0
product web sub-family	High density
Redundant	No
Topology	Double Conversion Online

# **Physical**

_		
color	Black	
Height	3.35 in (8.5 cm)	
Width	17.01 in (43.2 cm)	
Depth	22.99 in (58.4 cm)	
Net Weight	55.005 lb(US) (24.95 kg)	
Mounting Location	Front	
Mounting preference	Lower	
Mounting Mode	Rack-mounted	
Two post mountable	0	
USB compatible	Yes	
Mounting position	Horizontal	

# Input

Input Frequency 40 - 70 Hz auto-sensing

# Output

Bypass type	Built-in Bypass
Crest factor	3:1
Harmonic distortion	Less than 2%
Maximum configurable power in VA	2200 VA
Max Configurable Power (Watts)	1800 W
Wave type	Sine wave
Output Frequency (sync to mains)	50/60 Hz +/- 3 Hz sync to mains

## Conformance

Product Certifications ENERGY STAR V2.0 (USA)

#### **Environmental**

Acoustic level	55 dBA	
Online Thermal Dissipation	535 Btu/h	
Operating altitude	010000 ft	
Ambient air temperature for operation	32104 °F (040 °C)	
Ambient Air Temperature for Storage	-4122 °F (-2050 °C)	
Storage altitude	050000 ft (0.000000000015240.0000000000 m)	
IP degree of protection	IP20	
Relative Humidity	095 % non-condensing	
Storage Relative Humidity	095 % non-condensing	

# **Communications & Management**

Emergency Power Off (EPO)	Yes
Free slots	1
Alarm	Audible and visible alarms : prioritized by severity

## **Surge Protection and Filtering**

Surge energy rating 340 J

# Ordering and shipping details

GTIN 731304323051

# **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9.69 in (24.6 cm)
Package 1 Width	31.89 in (81 cm)
Package 1 Length	23.58 in (59.9 cm)
Package 1 Weight	75.001 lb(US) (34.02 kg)

## **Contractual warranty**

Warranty 3 years repair or replace (excluding battery) and 2 years for battery



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

#### Environmental Data explained >

How we assess product sustainability >

#### ∅ Environmental footprint

Environmental Disclosure

Product Environmental Profile

#### **Use Better**

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
SCIP Number	4282bd22-a353-4f82-bb5c-97bbd7f1d1e9
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
<sup>™</sup> Energy efficiency	
Optimized Energy Efficiency	Energy efficient product
ENERGY STAR®	ENERGY STAR UPS V2.0 (USA)

#### **Use Again**

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Removable battery	User replaceable
Take-back	Yes