Specifications



APC Smart-UPS On-Line, 2200VA, Rackmount 2U, 120V, 6x 5-20R+1x L5-20R NEMA outlets, Network Card, Extended runtime, W/ rail kit

SRT2200RMXLA-NC

Overview	
Lead time	Usually in Stock
Main	
Main Input Voltage	120 V
Product or Component Type	Uninterruptible power supply (UPS)
Main Output Voltage	120 V
Kw Rating	1800 W
Rated power in VA	2200 VA
Input Connection Type	NEMA 5-20P
output connection type	6 NEMA 5-20R 1 NEMA L5-20R
Number of rack unit	2U
Cable length	6 ft (1.8 m)
Number of cables	1
Provided equipment	CD with software Documentation CD Installation guide Network Management Card Rack mounting hardware Rack Mounting brackets Rack Mounting support rails USB cable Warranty card
Range of Product	Smart-UPS On-Line

Range of Product

Smart-UPS On-Line

Batteries & Runtime

Run Time	View Runtime Graph	
Efficiency	View Efficiency Graph 🗗	
Battery Type	Lead-Acid battery	
Battery Voltage	72V	
Extendable Run Time	1	
Included Battery Modules	1	
Battery Slots Empty	0	
Typical recharge time	3 h	
RBC Quantity	1	
Battery life	35 year(s)	

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Replacement battery	APCRBC141
Battery Charge Power (Watts)	102 W rated

General

Number of power module	1400
Number of power module filled slots	0
Number of power module free slots	0
product web sub-family	High density
Redundant	No
Тороlоду	Double Conversion Online

Physical

color	Black
Height	3.35 in (8.5 cm)
Width	17.01 in (43.2 cm)
Depth	22.99 in (58.4 cm)
Net Weight	55.1 lb(US) (25 kg)
Mounting Location	Front
Mounting preference	Lower
Mounting Mode	Rack-mounted
Two post mountable	0
USB compatible	Yes
Mounting position	Horizontal

Input

Input Frequency

40 - 70 Hz auto-sensing

Output

Bypass type	Built-in Bypass
Crest factor	3:1
Harmonic distortion	Less than 2%
Maximum configurable power in VA	2200 VA
Max Configurable Power (Watts)	1800 W
Wave type	Sine wave
Output Frequency (sync to mains)	50/60 Hz +/- 3 Hz sync to mains

Conformance

Product Certifications	ENERGY STAR V2.0 (USA)

Environmental

Acoustic level	55 dBA
Online Thermal Dissipation	535 Btu/h

Operating altitude	010000 ft	
Ambient air temperature for operation	32104 °F (040 °C)	
Ambient Air Temperature for Storage	-4122 °F (-2050 °C)	
Storage altitude	050000 ft (0.00000000015240.000000000 m)	
IP degree of protection	IP20	
Relative Humidity	095 % non-condensing	
Storage Relative Humidity	095 % non-condensing	

Communications & Management

Emergency Power Off (EPO)	Yes	
Free slots	0	
Pre-Installed SmartSlot™ Cards	Network management card 3 with environmental monitoring	
Alarm	Audible and visible alarms : prioritized by severity	

Surge Protection and Filtering

Surge energy rating

340 J

Ordering and shipping details

GTIN

731304325154

Packing Units

J	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9.69 in (24.6 cm)
Package 1 Width	31.89 in (81 cm)
Package 1 Length	23.58 in (59.9 cm)
Package 1 Weight	75.001 lb(US) (34.02 kg)

Contractual warranty

Warranty

3 years repair or replace (excluding battery) and 2 years for battery

C Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability \geq

${\mathcal Q}$ Environmental footprint	
Carbon footprint (kg CO2 eq, Total Life cycle)	3372
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances	
EU RoHS Directive	Compliant with Exemptions
REACh Regulation	REACh Declaration
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
ℰ Energy efficiency	
Optimized Energy Efficiency	Energy efficient product
ENERGY STAR®	ENERGY STAR UPS V2.0 (USA)

Use Again

$^{\circlearrowright}$ Repack and remanufacture	
Circularity Profile	End of Life Information
Removable battery	User replaceable
Take-back	Yes