Specifications



APC Smart-UPS On-Line, 3kVA, Rackmount 2U, 120V, 8x 5-20R+1x L5-30R NEMA outlets, Network Card, Extended runtime, W/ rail kit

SRT3000RMXLA-NC

Presentation	High density, double-conversion on-line power protection with scalable runtime	
Lead time	Usually in Stock	
Main		
Main Input Voltage	120 V	
Product or Component Type	Uninterruptible power supply (UPS)	
Main Output Voltage	120 V	
Kw Rating	2700 W	
Rated power in VA	3000 VA	
Input Connection Type	NEMA L5-30P	
output connection type	8 NEMA 5-20R 1 NEMA L5-30R	
Number of rack unit	2U	
Cable length	8 ft (2.4 m)	
Number of cables	1	
Provided equipment	CD with software Documentation CD Installation guide Network Management Card Rack Mounting brackets Rack Mounting support rails USB cable Warranty card	
Range of Product	Smart-UPS On-Line	

#### **Batteries & Runtime**

Run Time	View Runtime Graph □
Efficiency	View Efficiency Graph 🖾
Battery Type	Lead-Acid battery
Battery Voltage	96V
Extendable Run Time	1
Included Battery Modules	1
Typical recharge time	3 h
RBC Quantity	1
Battery life	35 year(s)

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Replacement battery	APCRBC152 L <sup>2</sup>
Battery Charge Power (Watts)	151 W rated

# General

Number of power module filled slots	0
Number of power module free slots	0
product web sub-family	High density
Redundant	No
Тороlogy	Double Conversion Online

# Physical

color	Black
Height	3.35 in (8.5 cm)
Width	17.01 in (43.2 cm)
Depth	25.00 in (63.5 cm)
Net Weight	69.005 lb(US) (31.3 kg)
Mounting Location	Front
Mounting preference	Lower
Mounting Mode	Rack-mounted
Two post mountable	0
USB compatible	Yes
Mounting position	Horizontal

### Input

Input Frequency

40 - 70 Hz auto-sensing

# Output

Bypass type	Internal Bypass (Automatic and Manual)	
Crest factor	3:1	
Harmonic distortion	Less than 2%	
Maximum configurable power in VA	3000 VA	
Max Configurable Power (Watts)	2700 W	
Wave type	Sine wave	
Output Frequency (sync to mains)	50/60 Hz +/- 3 Hz sync to mains	

### Conformance

Product Certifications

ENERGY STAR V2.0 (USA)

#### Environmental

Acoustic level	55 dBA
Online Thermal Dissipation	805 Btu/h
Operating altitude	010000 ft

Ambient air temperature for operation	32104 °F (040 °C)	
Ambient Air Temperature for Storage	5113 °F (-1545 °C)	
Storage altitude	050000 ft (0.00000000015240.000000000 m)	
IP degree of protection	IP20	
Relative Humidity	095 % non-condensing	
Storage Relative Humidity	095 % non-condensing	

#### **Communications & Management**

Emergency Power Off (EPO)	Yes	
Free slots	0	
Pre-Installed SmartSlot™ Cards	Network management card 3 with environmental monitoring	
Alarm	Audible and visible alarms : prioritized by severity	

#### **Surge Protection and Filtering**

Surge energy rating

340 J

### Ordering and shipping details

GTIN

731304325178

#### **Packing Units**

-	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9.69 in (24.6 cm)
Package 1 Width	34.29 in (87.1 cm)
Package 1 Length	23.58 in (59.9 cm)
Package 1 Weight	88.009 lb(US) (39.92 kg)

#### **Contractual warranty**

Warranty

3 years repair or replace (excluding battery) and 2 years for battery

# C Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

#### Environmental Data explained >

How we assess product sustainability  $\geq$ 

${\mathcal Q}$ Environmental footprint	
Carbon footprint (kg CO2 eq, Total Life cycle)	4974
Environmental Disclosure	Product Environmental Profile

#### **Use Better**

Iterational Substances		
Packaging made with recycled cardboard	Yes	
Packaging without single use plastic	No	
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
ℰ Energy efficiency		
Optimized Energy Efficiency	Energy efficient product	
ENERGY STAR®	ENERGY STAR UPS V2.0 (USA)	

#### Use Again

$\circlearrowright$ Repack and remanufacture	
Circularity Profile	End of Life Information
Removable battery	User replaceable
Take-back	Yes