

APC Smart-UPS On-Line, 1500VA, Rackmount 2U, 120V, 6x 5-15R NEMA outlets, Network Card, Extended runtime, W/ rail kit

SRT1500RMXLA-NC

#### Overview

Lead time Usually in Stock

Main		
Main Input Voltage	120 V	
Product or Component Type	Uninterruptible power supply (UPS)	
Main Output Voltage	120 V	
Kw Rating	1350 W	
Rated power in VA	1500 VA	
Input Connection Type	NEMA 5-15P	
output connection type	6 NEMA 5-15R	
Number of rack unit	2U	
Cable length	6 ft (1.8 m)	
Number of cables	1	
Provided equipment	CD with software Communication Cable Documentation CD Installation guide Network Management Card Rack mounting hardware Rack Mounting brackets Rack Mounting support rails Temperature Probe USB cable Warranty card	
Range of Product	Smart-UPS On-Line	

#### **Batteries & Runtime**

Run Time	View Runtime Graph ☐	
Efficiency	View Efficiency Graph ☐	
Battery Type	Lead-Acid battery	
Battery Voltage	48V	
Extendable Run Time	1	
Included Battery Modules	1	
Battery Slots Empty	0	
Typical recharge time	3 h	
RBC Quantity	1	

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Battery life	35 year(s)	
Replacement battery	APCRBC155 □	
Battery Charge Power (Watts)	91 W rated	

## General

Number of power module filled slots	0	
Number of power module free slots	0	
product web sub-family	High density	
Redundant	No	
Topology	Double Conversion Online	

# **Physical**

•		
color	Black	
Height	3.35 in (8.5 cm)	
Width	17.01 in (43.2 cm)	
Depth	20.00 in (50.8 cm)	
Net Weight	48.5 lb(US) (22 kg)	
Mounting Location	Front	
Mounting preference	No preference	
Mounting Mode	Rack-mounted	
Two post mountable	0	
USB compatible	Yes	
Mounting position	Horizontal	

# Input

Efficiency at full load	108150 V 50150 V 40% load	
Input Frequency	40 - 70 Hz auto-sensing	

# Output

Bypass type	Built-in Bypass	
Crest factor	3:1	
Harmonic distortion	Less than 2%	
Maximum configurable power in VA	1500 VA	
Max Configurable Power (Watts)	1350 W	
Wave type	Sine wave	
Output Frequency (sync to mains)	50/60 Hz +/- 3 Hz sync to mains	

## Conformance

Product Certifications ENERGY STAR V2.0 (USA)

## **Environmental**

Acoustic level	50 dBA	
Online Thermal Dissipation	463 Btu/h	
Operating altitude	010000 ft	
Ambient air temperature for operation	32104 °F (040 °C)	
Ambient Air Temperature for Storage	-4122 °F (-2050 °C)	
Storage altitude	050000 ft (0.000000000015240.0000000000 m)	
IP degree of protection	IP20	
Relative Humidity	095 % non-condensing	
Storage Relative Humidity	0 95 % non-condensing	

## **Communications & Management**

Emergency Power Off (EPO)	Yes	
Free slots	0	
Pre-Installed SmartSlot™ Cards	Network management card 3 with environmental monitoring	
Alarm	Audible and visible alarms : prioritized by severity	

## **Surge Protection and Filtering**

Surge energy rating 432 J

## Ordering and shipping details

GTIN 731304330080

## **Packing Units**

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	9.65 in (24.5 cm)	
Package 1 Width	27.17 in (69.0 cm)	
Package 1 Length	23.43 in (59.5 cm)	
Package 1 Weight	71.83 lb(US) (32.58 kg)	

## **Contractual warranty**

Warranty 3 years repair or replace (excluding battery) and 2 years for battery



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

#### Environmental Data explained >

How we assess product sustainability >

☑ Environmental footprint	
Carbon footprint (kg CO2 eq, Total Life cycle)	2584
Environmental Disclosure	Product Environmental Profile

#### **Use Better**

<b>⊗</b> Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
₩ Energy efficiency	
Optimized Energy Efficiency	Energy efficient product
ENERGY STAR®	ENERGY STAR UPS V2.0 (USA)

#### **Use Again**

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Removable battery	User replaceable
Take-back	Yes