Specifications



APC Smart-UPS C, Line Interactive, 1000VA, Rackmount 2U, 120V, 6x NEMA 5-15R outlets, SmartConnect port, USB and Serial communication, AVR,Graphic LCD

SMC1000-2UC

Product availability: Non-Stock - Not normally stocked in distribution facility

#### Overview

Lead time

Usually Ships within 2 Weeks

#### Main

IVIAIII	
Main Input Voltage	120 V
Other Input Voltage	110 V
	125 V
Main Output Voltage	120 V
Other Output Voltage	110 V
	125 V
Kw Rating	600 W
Rated power in VA	1000 VA
Product or Component Type	Uninterruptible power supply (UPS)
Input Connection Type	NEMA 5-15P
output connection type	6 NEMA 5-15R
Number of rack unit	2U
Cable length	8 ft (2.4 m)
Number of cables	1
Battery Type	Lead-Acid battery
Provided equipment	Documentation CD
	Installation guide
	Rack Mounting brackets
	USB cable
Range of Product	Smart-UPS

#### Complementary

Communication port type	SmartConnect Ethernet port
Software package	SmartConnect software for remote power monitoring feature availability varies by terms of use

### **Batteries & Runtime**

Run Time	View Runtime Graph 🖸
Efficiency	View Efficiency Graph 🛱

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Extendable Run Time	0
Included Battery Modules	0
Battery Slots Empty	0
Typical recharge time	3 h
RBC Quantity	1
Battery life	46 year(s)
Replacement battery	APCRBC124
Bettem: Ohenne Deusen (Mette)	70.14

Battery Charge Power (Watts) 72 W rated

# General

Number of power module	0
Number of power module filled slots	0
Number of power module free slots	0
product web sub-family	Cloud-enabled monitoring
Redundant	No

# Physical

color	Black
Height	3.39 in (8.6 cm)
Width	17.01 in (43.2 cm)
Depth	15.98 in (40.6 cm)
Net Weight	45.24 lb(US) (20.52 kg)
Mounting Location	Front
Mounting preference	Lower
Mounting Mode	Rack-mounted
Two post mountable	0
USB compatible	Yes

# Input

Efficiency at full load	85136 V adjustable 93130 V
Input Frequency	50/60 Hz +/- 3 Hz auto-sensing

# Output

•	
Harmonic distortion	Less than 5%
Maximum configurable power in VA	1000 VA
Max Configurable Power (Watts)	600 W
Transfer Time	6ms typical : 10ms maximum
Тороlоду	Line Interactive
Wave type	Sine wave

Output Frequency (sync to mains) 50/60 Hz +/- 3 Hz sync to mains

### Conformance

Product Certifications	cULus ENERGY STAR V2.0 (USA)
Equipment protection policy	Lifetime : \$150000

#### Environmental

Acoustic level	41 dBA
Online Thermal Dissipation	175 Btu/h
Operating altitude	010000 ft
Ambient air temperature for operation	32104 °F (040 °C)
Ambient Air Temperature for Storage	5113 °F (-1545 °C)
Storage altitude	050000 ft (0.00000000015240.000000000 m)
Relative Humidity	095 %
Storage Relative Humidity	095 %

## **Communications & Management**

control panel	Multi-function LCD status and control console
Free slots	0
Communication port support	SmartConnect Ethernet port: for cloud monitoring feature availability varies by terms of use
Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays

## **Surge Protection and Filtering**

Surge energy rating	680 J
Filtering	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : m

# Ordering and shipping details

Category	11309-APC RESALE PRODUCTS	
Discount Schedule	APC1	
GTIN	731304322733	
Returnability	No	
Country of origin	РН	

# **Packing Units**

-		
Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	9.25 in (23.5 cm)	
Package 1 Width	22.44 in (57 cm)	
Package 1 Length	21.06 in (53.5 cm)	
Package 1 Weight	45.66 lb(US) (20.71 kg)	

#### **Contractual warranty**

Warranty

2 years repair or replace

# C Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

#### Environmental Data explained >

How we assess product sustainability  $\geq$ 

${\mathcal Q}$ Environmental footprint	
Carbon footprint (kg CO2 eq, Total Life cycle)	923
Environmental Disclosure	Product Environmental Profile

#### **Use Better**

Materials and Substances		
Packaging made with recycled cardboard	Yes	
Packaging without single use plastic	No	
SCIP Number	B2b22a56-41f2-497e-9ea6-cf093b3b8bd3	
California proposition 65	"WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov"	
ℰ Energy efficiency		
Optimized Energy Efficiency	Energy efficient product	
ENERGY STAR®	ENERGY STAR UPS V2.0 (USA)	
Use Again		

$\circlearrowright$ Repack and remanufacture	
Circularity Profile	End of Life Information
Removable battery	User replaceable
Take-back	Yes