

Product data sheet

Specifications



Device monitoring and management, Network Management Cards, NMC3 with Environmental Monitoring, secure remote UPS monitoring and management

AP9641

Overview

Lead time	Usually in Stock
-----------	------------------

Main

Range of Product	Network Management Cards
Range Compatibility	Galaxy VM Galaxy VX Symmetra PX Easy UPS 3M Advanced Easy UPS 3-Phase Modular Galaxy PX Smart-UPS Smart-UPS Ultra Smart-UPS Online Smart-UPS Modular Ultra Smart-UPS Battery Systems Back-UPS SX3 Refurbished Smart-UPS
Product or Component Type	Device monitoring and management
Provided Equipment	Temperature Sensor Micro-USB cable Installation manual
Number of input phases	1 3
Standards	EN 55024 BS EN 55024 EN 61000-4-2 BS EN 61000-4-2 EN 61000-4-3 BS EN 61000-4-3 EN 61000-4-4 BS EN 61000-4-4 EN 61000-4-5 BS EN 61000-4-5 EN 61000-4-6 BS EN 61000-4-6 EN 61000-4-8 BS EN 61000-4-8 EN 61000-4-11 BS EN 61000-4-11 EN 55035 BS EN 55035 EN 62040-2 BS EN 62040-2 EN 61326-2 BS EN 61326-2 ICES-003 class A VCCI class A EN 61000-6-3 BS EN 61000-6-3 EN 55032: class A BS EN 55032: class A

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

General

Variant option	Environmental monitoring
----------------	--------------------------

Physical

Net Weight	0.20 lb(US) (0.09 kg)
Width	4.76 in (12.1 cm)
Height	1.50 in (3.8 cm)
Depth	4.49 in (11.4 cm)

Conformance

Product Certifications	FCC Class A AS/NZS AS/NZS 3548 (C-Tick) Class A FCC part 15 class A GOST UK PSTI
------------------------	---

Environmental

Storage Relative Humidity	0...95 %
Relative Humidity	0...95 %
Ambient Air Temperature for Storage	5...149 °F (-15...65 °C)
Ambient air temperature for operation	23...113 °F (-5...45 °C)
Storage altitude	0...50000 ft (0.0000000000...15240.0000000000 m)
Operating altitude	0...10000 ft

Communications & Management

Communication Network Type	10/100/1000BASE-T
Authentication	Radius Lightweight Directory Access Protocol (LDAP)
Communication Port Protocol	HTTP over secure sockets Layer (HTTPS) SSH FTP HTTP SNMP DHCP BOOTP (Bootstrap Protocol) TCP/IP

Ordering and shipping details

GTIN	731304355540
------	--------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.05 in (5.200 cm)
Package 1 Width	6.46 in (16.400 cm)
Package 1 Length	9.45 in (24.000 cm)
Package 1 Weight	14.286 oz (405.000 g)

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

🌱 Environmental footprint	
Carbon footprint (kg CO2 eq, Total Life cycle)	123
Environmental Disclosure	Product Environmental Profile

Use Better

♻️ Materials and Substances	
EU RoHS Directive	Compliant
REACH Regulation	REACH Declaration

💡 Energy efficiency	
Optimized Energy Efficiency	Energy efficient product

Use Again

🔄 Repack and remanufacture	
Circularity Profile	End of Life Information
Removable battery	Yes
Take-back	Yes