Specifications



Device monitoring and management, Network Management Cards, NMC3 for Easy UPS On-Line, secure remote UPS monitoring and management

AP9544

Overview		
Presentation	The Network Management Card for Easy UPS On-Line (AP9544) enables secure remote monitoring and control of one Easy UPS Online through the easy-to-use web browser interface, via EcoStruxure [™] IT Software or another SNMP-enabled system. A 12-month Secure NMC Subscription, that allows the customer to access future firmware updates, is included with the purchase of the card*. Upon expiration of the provided Secure NMC Subscription the purchase of a new Secure NMC Subscription is required to access future firmware updates. *The NMC Firmware must be V2.5 or later. Find the latest Firmware in the Software and Firmware section below.	
Lead time	Usually in Stock	
Main		
Range of Product	Network Management Cards	
Range Compatibility	Easy UPS On-Line Easy UPS 1 Ph On-Line	
Product or Component Type	Device monitoring and management	
Provided Equipment	Micro-USB cable Installation manual	
Number of input phases	1	
Standards	CISPR 32 VCCI class A ICES-003 EN 55024 EN 61000-4-2 EN 61000-4-3 EN 61000-4-5 EN 61000-4-5 EN 61000-4-6 EN 61000-4-8	

Physical

Net Weight	0.11 lb(US) (0.05 kg)
Width	2.05 in (5.2 cm)
Height	1.73 in (4.4 cm)
Depth	3.15 in (8.0 cm)

EN 61000-6-2 EN/IEC 62040-2

Conformance

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Product Certifications	FCC Class A	
	AS/NZS	
	UK PSTI	

Environmental

Storage Relative Humidity	095 %	
Relative Humidity	095 %	
Ambient Air Temperature for Storage	5149 °F (-1565 °C)	
Ambient air temperature for operation	23113 °F (-545 °C)	
Storage altitude	050000 ft (0.00000000015240.000000000 m)	
Operating altitude	010000 ft	

Communications & Management

Communication Network Type	10/100/1000BASE-T	
Authentication	Radius	
Communication Port Protocol	HTTP over secure sockets Layer (HTTPS) SSH FTP HTTP SNMP DHCP BOOTP (Bootstrap Protocol) TCP/IP	

Ordering and shipping details

GTIN

731304440161

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	1.81 in (4.600 cm)	
Package 1 Width	6.50 in (16.500 cm)	
Package 1 Length	9.06 in (23.000 cm)	
Package 1 Weight	10.653 oz (302.000 g)	
Unit Type of Package 2	P06	
Number of Units in Package 2	44	
Package 2 Height	26.77 in (68.000 cm)	
Package 2 Width	23.62 in (60.000 cm)	
Package 2 Length	31.50 in (80.000 cm)	
Package 2 Weight	46.297 lb(US) (21.000 kg)	

Contractual warranty

Warranty

2 years repair or replace

C Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >	
How we assess product sustainability $\boldsymbol{\hat{>}}$	
$\ensuremath{ \mathcal{Q} }$ Environmental footprint	
Carbon footprint (kg CO2 eq, Total Life cycle)	69
Environmental Disclosure	Product Environmental Profile
Use Better	
S Materials and Substances	
EU RoHS Directive	Compliant with Exemptions
REACh Regulation	REACh Declaration
Use Again	
${\mathbb O}$ Repack and remanufacture	
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Take-back	No